



# Franklin Institute Library

PHILADELPHIA

Class 672.....

Book q M 83  
ed 10

Accession 5149

## REFERENCE

GIVEN BY

'2-31-78.

221.

ARTICLE V.—The Library shall be divided into two classes; the first comprising such works as, from their rarity or value, should not be lent out, all unbound periodicals, and such text books as ought to be found in a library of reference, except when required by Committees of the Institute, or by Members or holders of second class stock, who have obtained the sanction of the Committee. The second class shall include those books intended for circulation.

ARTICLE VI.—The Secretary shall have authority to loan to Members and to holders of second class stock, any work belonging to the SECOND CLASS, subject to the following regulations:

Section 1.—No individual shall be permitted to have more than two books out at one time, without a written permission, signed by at least two members of the Library Committee; nor shall a book be kept out more than two weeks; but if no one has applied for it, the former borrower may renew the loan. Should any person have applied for it, the latter shall have the preference.

Section 2.—A FINE OF TEN CENTS PER WEEK shall be exacted for the detention of a book beyond the limited time; and if a book be not returned within three months it shall be deemed lost, and the borrower shall, in addition to his fines, forfeit its value.

Section 3.—Should any book be returned injured, the borrower shall pay for the injury, or replace the book, as the Library Committee may direct; and if one or more books, belonging to a set or sets, be lost, the borrower shall replace them or make full restitution.

ARTICLE VII.—Any person removing from the Hall, without permission from the proper authorities, any book, newspaper, or other property in charge of the Library Committee, shall be reported to the Committee, who may inflict any fine not exceeding twenty-five dollars.

ARTICLE VIII.—No member or holder of second class stock, whose annual contribution for the current year shall be unpaid or who is in arrears for fines, shall be entitled to the privileges of the Library or Reading Room.

ARTICLE IX.—If any member or holder of second class stock, shall refuse or neglect to comply with the foregoing rules, it shall be the duty of the Secretary to report him to the Committee on the Library.

ARTICLE X.—Any Member or holder of second class stock, detected in mutilating the newspapers pamphlets or books belonging to the Institute, shall be deprived of his right of membership, and the name of the offender shall be made public.

672 q M 83 ed 10

5149







[BLANK PAGE]



CCA



THOMAS T. TASKER, JR.

STEPHEN P. M. TASKER.

MORRIS, TASKER & Co.


# Illustrated Catalogue.

## PASCAL IRON WORKS

PHILADELPHIA.

TENTH EDITION.

June 1st, 1871.



CLASS FIRST.

## TASKER IRON WORKS

NEW CASTLE, DEL.

BOILER TUBES.  
STEAM, GAS OR WATER TUBES.  
WROUGHT AND CAST-IRON FITTINGS.

MANIFOLDS.  
COIL FITTINGS.  
FLANGES.

RETURN BEND AND WROUGHT-IRON COILS.  
GALVANIZED IRON FITTINGS.  
GAS FITTINGS.

Works and Office—FIFTH AND TASKER STREETS, Philadelphia.

Office—209 SOUTH THIRD STREET, Philadelphia.

Office and Warehouse—No. 15 GOLD STREET, New York.

Office and Warehouse—No. 36 OLIVER STREET, Boston.

PRINTED BY McLAUGHLIN BROTHERS, BOOK AND JOB PRINTERS, Nos. 112 AND 114 SOUTH THIRD STREET

ILLUSTRATED BY L. HAUGG, No. 45 SOUTH FOURTH STREET

1875.



---

ENTERED ACCORDING TO ACT OF CONGRESS, IN THE YEAR 1873, BY

MORRIS, TASKER & CO.

IN THE OFFICE OF THE LIBRARIAN OF CONGRESS, AT WASHINGTON, D. C.

---



# PRICE LIST

FOR

## MORRIS, TASKER & CO.'S

# ILLUSTRATED CATALOGUE.

TENTH EDITION, 1871.

*Persons in ordering will please state the "Edition" they order from.*

Every order for special articles must have accurate plans and dimensions attached; and no order, "same as before," will be received.  
Any article for which no price is quoted on the list will only be made to special order, although such article may be shown in the illustrations.  
It is impossible to make tubes of exact internal diameter.

### LAP WELDED AMERICAN CHARCOAL IRON BOILER TUBES.

TABLE OF STANDARD DIMENSIONS AND PRICES.

PLATE.  
1

*Cut to Specific Lengths to suit Purchasers. Lengths greater than twenty feet at especial rates.*

External Diameter.	Price, per foot.	PRICE. Each Safe End Extra.	*Standard Thickness.	*Nearest Wire Gauge Thickness.	Internal Diameter.	Internal Circumference.	External Circumference.	†Length of Pipe per square foot of inside surface.	†Length of Pipe per square foot of outside surface.	Internal Area.	External Area.	Weight, per foot.
Inches.	\$ c.	\$ c.	Inches.	Inches.	Inches.	Inches.	Inches.	Feet.	Feet.	Inches.	Inches.	lbs.
1	.30	.15	0.072	15	0.856	2.689	3.142	4.460	3.819	0.575	0.785	0.708
1½	.30	.15	0.072	15	1.106	3.474	3.927	3.455	3.056	0.960	1.227	0.9
1½	.30	.15	0.083	14	1.334	4.191	4.712	2.863	2.547	1.396	1.767	1.250
1¾	.30	.17	0.095	13	1.560	4.901	5.498	2.448	2.183	1.911	2.405	1.665
2	.30	.17	0.098	13	1.804	5.667	6.283	2.118	1.909	2.556	3.142	1.981
2½	.34	.19	0.098	13	2.054	6.484	7.069	1.850	1.698	3.314	3.976	2.238
2½	.38	.21	0.109	12	2.283	7.172	7.854	1.673	1.528	4.094	4.909	2.755
2¾	.42	.24	0.109	12	2.533	7.957	8.639	1.508	1.390	5.039	5.940	3.045
3	.50	.27	0.109	12	2.783	8.743	9.425	1.373	1.273	6.083	7.069	3.333
3½	.54	.30	0.119	11	3.012	9.462	10.210	1.268	1.175	7.125	8.296	3.958
3½	.60	.33	0.119	11	3.262	10.248	10.995	1.171	1.091	8.357	9.621	4.272
3¾	.75	.36	0.119	11	3.512	11.033	11.781	1.088	1.018	9.687	11.045	4.590
4	.90	.39	0.130	10	3.741	11.753	12.566	1.023	0.955	10.992	12.566	5.320
4½	1.12	.43	0.130	10	4.241	13.323	14.137	0.901	0.849	14.126	15.904	6.010
5	1.35	.50	0.140	9½	4.72	14.818	15.708	0.809	0.764	17.497	19.635	7.226
6	1.80	.61	0.151	9	5.699	17.904	18.849	0.670	0.637	25.509	28.274	9.346
7	2.25	.	0.172	7½	6.657	20.914	21.991	0.574	0.545	34.805	38.484	12.435
8	3.38	.	0.182	7	7.636	23.989	25.132	0.500	0.478	45.795	50.265	15.109
9	.	.	0.193	6½	8.615	27.055	28.274	0.444	0.424	58.291	63.617	18.002
10	.	.	0.214	5½	9.573	30.074	31.416	0.399	0.382	71.975	78.540	22.19

\* The thickness of Tube can be varied to order, at prices dependent upon the thickness and number of feet wanted.

† In estimating the effective steam-heating or boiler surface of Tubes, the surface in contact with air or gases of combustion (whether internal or external to the Tubes,) is to be taken.

For heating liquids by steam, superheating steam, or transferring heat from one liquid or one gas to another, the mean surface of the Tubes is to be taken.



## WROUGHT IRON WELDED TUBES, IN RANDOM LENGTHS, FOR STEAM, GAS, OR WATER.

1½ inch and below, Butt Welded; proved to 300 pounds per square inch, Hydraulic pressure.  
 1½ inch and above, Lap “ “ 500 “ “ “ “

PLATE.  
2

TABLE OF STANDARD DIMENSIONS AND PRICES.

Inside Diameter.	Price, per Foot.	Price, per Foot, Galvanized.	Actual Outside Diameter.	Thickness.	Actual Inside Diameter.	Internal Circumference.	External Circumference.	Length of Pipe per square foot of inside surface.	Length of Pipe per square foot of outside surface.	Internal Area.	External Area.	Length of Pipe containing one cubic foot.	Weight per foot of length.	Number of threads per inch of screw.
Inches.	\$ c.	\$ c.	Inches.	Inches.	Inches.	Inches.	Inches.	Feet.	Feet.	Inches.	Inches.	Feet.	lbs.	
1/8	.09	.	0.405	0.068	0.270	0.848	1.272	14.15	9.44	0.0572	0.129	2500.	0.243	27
1/4	.09	.15	0.54	0.088	0.364	1.144	1.696	10.50	7.075	0.1041	0.229	1385.	0.422	18
3/8	.10	.15	0.675	0.091	0.494	1.552	2.121	7.67	5.657	0.1916	0.358	751.5	0.561	18
1/2	.12	.18	0.84	0.109	0.623	1.957	2.652	6.13	4.502	0.3048	0.554	472.4	0.845	14
3/4	.16	.24	1.05	0.113	0.824	2.589	3.299	4.635	3.637	0.5333	0.866	270.	1.126	14
1	.23	.33	1.315	0.134	1.048	3.292	4.134	3.679	2.903	0.8627	1.357	166.9	1.670	11½
1¼	.32	.44	1.66	0.140	1.380	4.335	5.215	2.768	2.301	1.496	2.164	96.25	2.258	11½
1½	.40	.55	1.9	0.145	1.611	5.061	5.969	2.371	2.01	2.038	2.835	70.65	2.694	11½
2	.56	.75	2.375	0.154	2.067	6.494	7.461	1.848	1.611	3.355	4.430	42.36	3.667	11½
2½	.90	1.20	2.875	0.204	2.468	7.754	9.032	1.547	1.328	4.783	6.491	30.11	5.773	8
3	1.30	1.65	3.5	0.217	3.067	9.636	10.996	1.245	1.091	7.388	9.621	19.49	7.547	8
3½	1.60	2.10	4.0	0.226	3.548	11.146	12.566	1.077	0.955	9.887	12.566	14.56	9.055	8
4	2.00	2.50	4.5	0.237	4.026	12.648	14.137	0.949	0.849	12.730	15.904	11.31	10.728	8
4½	2.40	3.20	5.	0.247	4.508	14.153	15.708	0.848	0.765	15.939	19.635	9.03	12.492	8
5	2.80	3.75	5.563	0.259	5.045	15.849	17.475	0.757	0.629	19.990	24.299	7.20	14.564	8
6	4.00	5.00	6.625	0.280	6.065	19.054	20.813	0.63	0.577	28.889	34.471	4.98	18.767	8
7	5.50	.	7.625	0.301	7.023	22.063	23.954	0.544	0.505	38.737	45.663	3.72	23.410	8
8	7.00	.	8.625	0.322	7.982	25.076	27.096	0.478	0.444	50.039	58.426	2.88	28.348	8
9	.	.	9.688	0.344	9.001	28.277	30.433	0.425	0.394	63.633	73.715	2.26	34.077	8
10	.	.	10.75	0.366	10.019	31.475	33.772	0.381	0.355	78.838	90.762	1.80	40.641	8

Taper of threads, 1 to 32 on each side.

## WROUGHT IRON WELDED TUBES, EXTRA STRONG.

TABLE OF STANDARD DIMENSIONS AND PRICES.

Dimensions not given below made to order.

3

Nominal Diameter.	Actual Outside Diameter.	Thickness, Extra Strong.	Thickness, Double Extra Strong.	Actual Inside Diameter, Extra Strong.	Actual Inside Diameter, Double Extra Strong.	Price, per Foot, Extra Strong.	Price, per Foot, Double Extra Strong.
Inches.	Inches.	Inches.	Inches.	Inches.	Inches.	\$ c.	\$ c.
1/8	0.405	0.100	.	0.205	.	.12	.
1/4	0.54	0.123	.	0.294	.	.15	.
3/8	0.675	0.127	.	0.421	.	.17	.
1/2	0.84	0.149	0.298	0.542	0.244	.24	.42
3/4	1.05	0.157	0.314	0.736	0.422	.34	.59
1	1.315	0.182	0.364	0.951	0.587	.50	.87
1¼	1.66	0.194	0.388	1.272	0.884	.61	1.07
1½	1.9	0.203	0.406	1.494	1.088	.85	2.05
2	2.375	0.221	0.442	1.933	1.491	1.08	2.50
2½	2.875	0.280	0.560	2.315	1.755	1.91	3.35
3	3.5	0.304	0.608	2.892	2.284	2.39	4.19
3½	4.0	0.321	0.642	3.358	2.716	3.49	6.00
4	4.5	0.341	0.682	2.818	3.136	3.81	6.67







CLASS FIRST.—*Continued.*

## FITTINGS FOR WROUGHT IRON TUBES, (CAST IRON.)

No. PLATE.

NOMINAL DIAMETER. INCHES, . . . .			$\frac{1}{8}$	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4	$4\frac{1}{2}$	5	6	7	8
			\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
16	4	Elbows, (Ls), . . . . .	.06	.07	.08	.12	.15	.22	.34	.44	.55	1.00	1.60	2.75	3.00	3.85	4.75	6.85	20.80	24.80
17	4	Tees, (Ts), . . . . .	.09	.10	.12	.16	.22	.32	.45	.60	.85	1.50	2.25	3.35	3.90	4.40	5.95	7.95	28.30	32.40
18	4	Crosses, (Xs), . . . . .	.13	.15	.17	.22	.28	.35	.52	.72	.96	1.90	2.82	4.06	5.00	6.05	6.82	10.15	37.00	41.55
5	4	Lock Nuts, (hexagonal), . . . . .	.04	.04	.05	.05	.07	.13	.17	.20	.24	.40	.58	.75	.95	1.08	1.15	1.80	6.16	6.65
19	4	Plugs, . . . . .	.04	.04	.05	.05	.06	.08	.11	.13	.21	.36	.49	.75	.83	1.06	1.47	1.90	.	.
20	4	Bushings, . . . . .	.	.	.12	.13	.16	.19	.23	.29	.45	.72	1.00	1.35	1.85	2.40	3.00	4.30	6.00	7.75
21	4	Drop Elbows, . . . . .	.	.	.	.15	.20	.27	.	.	.	.	.	.	.	.	.	.	.	.
22	4	Drop Tees, . . . . .	.	.	.	.20	.25	.36	.	.	.	.	.	.	.	.	.	.	.	.
*23	4	{ Return Bends, } dis., centre to centre, in.,	.	.	.	$1\frac{1}{8}$	$1\frac{3}{8}$	$1\frac{1}{2}$	$2\frac{1}{8}$	$2\frac{3}{8}$	$2\frac{1}{2}$	$3\frac{1}{2}$	$4\frac{1}{4}$	$4\frac{1}{2}$	$5\frac{1}{8}$	6	$6\frac{5}{8}$	$7\frac{7}{8}$	.	.
		{ close pattern, } Price, . . . . .	.	.	.09	.12	.18	.32	.45	.53	.86	1.58	2.12	2.50	3.25	3.80	6.12	7.35	.	.
24	4	{ Return Bends, } dis., cen. to cen., in.,	.	.	.	$1\frac{5}{8}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	$4\frac{1}{2}$	$5\frac{1}{2}$	$6\frac{1}{2}$	$7\frac{1}{2}$	$8\frac{1}{2}$	$9\frac{1}{2}$	11	13	.	.
25	4	{ wide pattern, } Price, . . . . .	.	.	.12	.16	.23	.35	.53	.75	1.20	1.80	2.40	3.10	.	.	.	.	.	.
		{ round or square, }	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
26	4	{ Back and Side Outlet Return Bends,	.	.	.	.	.28	.65	.	.	.	.	.	.	.	.	.	.	.	.
27	4		.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
28	4	Hydrant Nozzles, . . . . .	.	.	.	.40	.	.	.	.	.	.	.	.	.	.	.	.	.	.
29	4	45° Elbows (or $\frac{1}{2}$ Ls), . . . . .	.06	.07	.08	.11	.15	.22	.34	.44	.55	1.00	1.60	2.75	3.00	3.85	4.75	6.85	.	.
30	4	Lateral Branch (Y), . . . . .	.	.	.	.	.	.38	.55	.75	1.10	2.10	3.00	4.15	5.70	.	.	.	.	.

## GALVANIZED FITTINGS FOR WROUGHT IRON TUBES, (CAST IRON.)

		NOMINAL DIAMETER. INCHES, . . . . .	$\frac{1}{8}$	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4	$4\frac{1}{2}$	5	6	7	8
			\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
16	4	Elbows, (Ls), . . . . .	.07	.09	.11	.16	.23	.35	.56	.72	1.08	1.85	2.70	4.40	5.05	6.40	8.00	11.75	27.50	34.50
17	4	Tees, (Ts), . . . . .	.10	.13	.16	.22	.31	.50	.72	1.00	1.38	2.45	3.75	5.70	6.40	8.25	9.25	14.50	37.00	44.60
18	4	Crosses, (Xs), . . . . .	.14	.18	.22	.30	.41	.53	.84	1.14	1.65	3.10	4.37	6.95	8.25	10.25	10.80	16.50	48.00	57.00
5	4	Lock Nuts, (hexagonal), . . . . .	.05	.05	.06	.07	.10	.17	.21	.25	.31	.52	.80	1.10	1.50	1.70	2.00	2.75	7.50	8.50
19	4	Plugs, . . . . .	.04	.04	.06	.06	.08	.11	.16	.21	.32	.56	.78	1.15	1.35	1.80	2.40	3.30	.	.
21	4	Drop Elbows, . . . . .	.	.	.	.19	.27	.39	.	.	.	.	.	.	.	.	.	.	.	.
22	4	Drop Tees, . . . . .	.	.	.	.26	.35	.53	.	.	.	.	.	.	.	.	.	.	.	.
23	4	Return Bends, close pattern, . . . . .	.	.	.15	.18	.28	.53	.72	.88	1.42	2.60	3.85	4.60	6.00	7.25	12.00	14.50	.	.
24	{	Return Bends, wide pattern, . . . . .	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
25		Round or Square, . . . . .	.	.	.16	.23	.35	.56	.88	1.25	1.80	3.15	4.60	5.85	.	.	.	.	.	.

Globe Crosses. Reducing and Corner Fittings. Same prices as of Crosses and Tees, or Elbows, of usual form; the largest outlet being taken as standard for price. The Globe-shape is only used for odd fittings, for which we have no regular pattern.

Sockets for Longscrews made specially, and must so be ordered.

\* In ordinary close return bends for coils, always state the length of tubes to be used in the coils, so that the spread of the tubes will be allowed for.



## CLASS FIRST—Continued.

## MANIFOLDS.

No. PLATE.

ALL MANIFOLDS have left-hand Taper Screws in the outlets, unless specially ordered, either with running or right-hand Taper Screws.

36 5 THEY are also open at both ends, with *right-hand* Taper Thread of same size as outlets, irrespective of size of body. EITHER or both ends, however, can be drilled out to take Screws the size of body, or any size less than the size selected as size of body.

BACK OR SIDE OUTLETS can be attached to any manifold pattern to order; but in ordering, care must be taken to describe the plan of attachment of Back or Side Outlets.

BACK OR SIDE OUTLETS of same size as Front Outlets, will be charged as additional Front Outlets; other sizes, proportionally.

NUMBER OF OUTLETS, . . . . .		2	3	4	5	6	7	8	10	12	14	16	18	20
Size of Body.		\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
For $\frac{3}{4}$ inch Tube, 2 inch centre to centre,	1 inch, . . . . .	.48	.60	.82	.92	1.12	1.26	1.45	1.85	.	.	.	.	.
	1 $\frac{1}{4}$ " . . . . .	.58	.76	1.05	1.25	1.50	1.70	1.85	2.12	2.70	.	.	.	.
	1 $\frac{1}{2}$ " . . . . .	.80	1.02	1.25	1.45	1.70	1.90	2.25	2.80	2.95	3.40	4.35	4.85	5.40
	1 $\frac{3}{4}$ " . . . . .	.76	1.00	1.25	1.50	1.80	2.00	2.20	2.85	3.10	.	.	.	.
For 1 inch Tube, 2 $\frac{1}{2}$ inches, centre to centre,	1 $\frac{1}{2}$ " . . . . .	.88	1.15	1.45	1.90	2.00	2.25	2.55	3.45	4.15	.	.	.	.
	2 " . . . . .	1.26	1.65	2.00	2.25	2.60	2.95	3.15	4.12	4.80	5.20	6.00	7.40	8.30
	2 $\frac{1}{2}$ " . . . . .	1.60	2.00	2.50	3.40	3.60	4.15	4.70	6.00	7.00	7.90	.	.	.
For 1 $\frac{1}{4}$ inch Tube, 3 inches, centre to centre,	3 " . . . . .	2.45	3.00	3.60	4.20	4.85	5.50	6.20	.	.	.	.	.	.
	2 " . . . . .	1.40	1.75	2.10	2.55	2.85	3.20	3.70	.	.	.	.	.	.
For 1 $\frac{1}{2}$ inch Tube, 3 $\frac{1}{2}$ inches, centre to centre,	2 $\frac{1}{2}$ " . . . . .	2.30	2.85	3.40	4.00	4.70	5.35	6.00	.	.	.	.	.	.
	3 " . . . . .	2.90	3.80	4.70	5.65	6.70	8.10	8.80	.	.	.	.	.	.

## MANIFOLD VALVES.

37 5

NUMBER OF OUTLETS, . . . . .		2	3	4	5	6	7	8	10
Size of Body.		\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
For $\frac{3}{4}$ inch Tube, . . . . .	1 $\frac{1}{2}$ inch.	6.40	9.00	12.00	16.00	20.00	21.25	24.50	29.25
" 1 " " . . . . .	2 " . . . . .	8.75	12.25	16.30	20.00	24.00	28.00	32.00	36.50

## DOUBLE MANIFOLDS.

Face Outlets, 1 inch; 2 $\frac{1}{2}$  inches, centre to centre; end or back outlets to order, without extra charge, if not over 1 inch.

38 5

NUMBER OF PAIRS OF OUTLETS,		4	5	6	8	10	12	14	16	18	20	22	24	26	28	30
		\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
Plain Pattern, . . . . .		3.30	3.70	4.65	6.00	7.50	8.40	9.65	10.45	12.20	13.25	.	.	.	.	.
Ornamental base pattern, . . . . .		3.80	4.40	5.65	7.60	8.50	10.00	10.80	12.30	13.90	14.50	15.50	17.50	18.50	20.50	21.50
" top, . . . . .		1.90	2.50	3.10	4.30	4.55	4.75	5.35	6.00	6.35	7.10	7.65	9.20	9.70	10.70	11.20

## COIL STANDS, (PER PAIR.)

39 5

NUMBER OF TUBES HIGH, . . . . .		2	4	6	8	10	12	14	16	18	20	22	24
Size of Tube.	Centre to centre of pairs of Tubes.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
$\frac{3}{4}$	4 $\frac{1}{4}$	.36	.52	.68	.84	1.00	1.16	1.32	1.40	.	.	.	.
1	5	.43	.62	.85	1.05	1.45	1.70	1.80	1.95	2.20	2.25	2.55	2.80
1 $\frac{1}{4}$	6 $\frac{3}{4}$	.76	1.02	1.62	2.20	2.80	3.40	.	.	.	.	.	.
1 $\frac{1}{2}$	7 $\frac{1}{2}$	1.14	1.48	1.82	2.35	2.95	3.50	.	.	.	.	.	.
2	9 $\frac{1}{4}$	2.40	3.00	3.60	4.20	4.80	5.40	.	.	.	.	.	.



## SUPPORTS FOR TUBES.

		NUMBER OF TUBES,	1	2	3	4	5	6	7	8	10	12	14
			\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
No.	PLATE.												
40	5	Hook Plates,	$\frac{3}{4}$ Tubes, 2 in. centre to centre,	.15	.17	.20	.24	.32	.35	.39	.43	.	.
41	5												
41	5		1 " $2\frac{1}{2}$ " " "	.17	.22	.26	.37	.43	.47	.54	.60	.	.
41	5		1 $\frac{1}{4}$ " 3 " " "	.19	.28	.35	.44	.59	.65	.70	.92	.	.
41	5		1 $\frac{1}{2}$ " 3 $\frac{1}{2}$ " " "	.20	.29	.40	.44	.63	.75	.80	.95	.	.
41	5	"	2 " 4 $\frac{1}{2}$ " " "	.27	.48	.65	.75	.80	.95	1.00	1.10	.	.
41	5	"	2 $\frac{1}{2}$ " 5 $\frac{1}{2}$ " " "	.35	.	.	.	.	.	.	.	.	.
41	5	"	3 " 6 $\frac{1}{2}$ " " "	.60	.	.	.	.	.	.	.	.	.
42	5	Ring and Corner Plates,	$\frac{3}{4}$ " 2 " " "	.19	.20	.25	.30	.40	.45	.50	.60	.	.
43	5		1 " 2 $\frac{1}{2}$ " " "	.20	.25	.30	.35	.45	.50	.65	.75	.	.
44	5	Wall Plates,	$\frac{3}{4}$ " 2 " " "	.	.32	.39	.43	.52	.58	.	.	.	.
44	5	"	1 " 2 $\frac{1}{2}$ " " "	.	.36	.44	.50	.55	.68	.	.	.	.
45	5	Rosette Plates,	$\frac{3}{4}$ " 2 " " "	.	.28	.	.58	.	.80	.	.90	1.00	1.25
45	5	"	1 " 2 $\frac{1}{2}$ " " "	.	.30	.	.62	.	.82	.	1.10	1.30	1.60
46	5	{ Movable Hook Plates for Laundry Coils,	$\frac{3}{4}$ " { each Plate with } .	.	1.00	.	1.60	.	2.45	.	3.25	3.85	4.60
			1 " { Hooks complete, } .	.	1.10	.	1.80	.	2.70	.	3.60	4.25	5.10
47	5	Ring Plates,	$\frac{3}{4}$ " projecting 2 inches,	.20	.	.	.	.	.	.	.	.	.
48	5	"	1 " " "	.22	.	.	.	.	.	.	.	.	.
49	5	Stand Plates,	$\frac{3}{4}$ " height 3 $\frac{1}{2}$ inches,	.30	.	.	.	.	.	.	.	.	.
49	5	"	1 " " "	.38	.	.	.	.	.	.	.	.	.
50	5	Expansion Hanger with not over one foot of Rod.											
		Size of Suspended Tube,			$\frac{3}{4}$	1	1 $\frac{1}{4}$	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$	3	3 $\frac{1}{2}$	4
		Price,			.34	.36	.48	.52	.68	.70	1.00	1.03	1.25
51	5	Same double, Rings as ordered,			.42	.47	.65	.72	.98	1.05	1.50	1.75	1.95

## CAST IRON FLANGES.

[illegible]



## CLASS FIRST.—Continued.

## CAST IRON OVAL FLANGES.

No. PLATE.		SIZE OF TUBE, . . . . .	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2
			\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
53	5	$2\frac{5}{16}$ inches, centre to centre, of $\frac{1}{2}$ inch bolts, .	.18	.20	.22	.26	.	.	.	.
		$3\frac{1}{4}$ inches, centre to centre, of $\frac{5}{8}$ inch bolts, .	.	.	.29	.32	.36	.40	.	.
		$4\frac{3}{4}$ inches, centre to centre, of $\frac{3}{4}$ inch bolts, .	.	.	.	.	.51	.55	.60	.65

## CAST IRON FLANGES, WITH BOSSES.

- 54 5 Diameters corresponding to those of flanges upon Cast Iron Pipe, for connecting Wrought Iron Tubes to Cast Iron Pipe.  
The price given in heavy figures are those of Standard Pipe Flanges.

DIAMETER OF FLANGES.	NUMBER OF BOLTS.	SIZE OF BOLTS.	SIZE OF TUBE TO WHICH THE FLANGES BELONG.							
			3	$3\frac{1}{2}$	4	$4\frac{1}{2}$	5	6	7	8
			\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
$6\frac{1}{2}$	4	$\frac{1}{2}$	1.14	.	.	.	.	.	.	.
7	4	$\frac{9}{16}$	1.30	1.52	.	.	.	.	.	.
$7\frac{1}{2}$	4	$\frac{9}{16}$	<b>1.42</b>	1.55	.	.	.	.	.	.
8	5	$\frac{9}{16}$	.	<b>1.82</b>	1.87	.	.	.	.	.
$8\frac{1}{2}$	5	$\frac{5}{8}$	.	.	2.00	2.10	.	.	.	.
9	5	$\frac{5}{8}$	.	.	<b>2.10</b>	2.20	.	.	.	.
$9\frac{1}{2}$	6	$\frac{5}{8}$	.	.	.	2.95	3.00	.	.	.
10	6	$\frac{5}{8}$	.	.	.	.	<b>3.20</b>	.	.	.
$10\frac{1}{2}$	6	$\frac{5}{8}$	.	.	.	.	3.75	3.90	.	.
11	6	$\frac{5}{8}$	.	.	.	.	.	<b>4.05</b>	.	.
12	8	$\frac{5}{8}$	.	.	.	.	.	4.65	6.30	.
$13\frac{1}{2}$	8	$\frac{5}{8}$	.	.	.	.	.	.	8.70	<b>9.00</b>

## COLLARS.

56 5		SIZE, . . . . .	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3
		Price, . . . . .	\$0.12	\$0.13	\$0.14	\$0.15	\$0.16	\$0.17	\$0.18	\$0.19

## FLANGE UNIONS WITH BOLTS AND NUTS.

55 5		SIZE OF TUBE, . . . . .	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4
		Diameter of Flange, . . . . .	4	$4\frac{1}{4}$	5	$5\frac{1}{2}$	6	$6\frac{3}{4}$	$7\frac{1}{2}$
		Price, . . . . .	\$1.85	\$2.28	\$2.66	\$3.40	\$4.10	\$4.90	\$5.80

## MALLEABLE IRON UNIONS.

57 5		SIZE OF TUBE, . . . . .	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$
		Price, . . . . .	\$0.26	\$0.28	\$0.34	\$0.42	\$0.52	\$0.64	\$0.84	\$1.40	\$2.32	\$3.72	\$5.40



FOR PRICES OF ARTICLES ON THIS PAGE, SEE SPECIAL PRICE LIST.

CLASS FIRST.—*Continued.*

RADIATING COILS.

- No. PLATE.  
 63 } 6 Wall Coils, with Return Bends. Same price, per foot of pipe used, as given in list below for Box Coils (No. 70), with additional charge for all manifolds, and for excess of price of rosette or movable hook plates over plain hook plates, as per lists of prices of those articles.  
 64 }  
 65 } 6 Wall Coils, with Hook Plates and Manifolds (to be built at the place where used). Prices to be estimated from materials used, separately, as on lists.  
 66 } N. B.—Coils made with straight tubes, between two manifolds, will not remain tight. Allowance is required for expansion, either by Elbows, as shown on figures No. 65 or 66; or by Return Bends, as shown in figures 63 or 64, or in some similar way.

70 7 RETURN BEND OR BOX COILS. (MADE UP WITH MANIFOLDS AND STANDS READY FOR USE.)

The height being governed by the Stands, and the width by the Manifolds, as previously given in this Catalogue.

LENGTH OF TUBES IN COIL, . . . . .	2 ft.	2 ft. 3.	2 ft. 6.	3 ft.	3 ft. 6.	4 ft.	4 ft. 6.	5 ft.	6 ft.	7 ft.	8 ft.	9 ft.	10 ft.	12 ft.
Price, per foot, of Tube used, $\frac{3}{4}$ in. Tube,														
“ “ 1 “														

VERTICAL TUBE COILS.

Two rows of Tubes, 2 feet 7 inches long; whole height, 3 feet 2 inches.

PAIRS OF TUBES. 1 INCH, . . . . .	4	5	6	7	8	10	12	14	16	18	20	22	24	26	28	30
71 7 With Ornamental Cover and Moulding and Base Manifold, unpainted, . . . . .																
Same—Bronzed, plain, green or chocolate,																

VERTICAL TUBE COILS, (CIRCULAR.) (WITH ORNAMENTAL COVER AND MOULDING AND BASE.)

Forty Tubes; outside diameter, 25 inches; whole height, 3 feet 2 inches.

73 7 Unpainted, . . . . .																
Bronzed, plain, green or chocolate, . . . . .																
Marble in place of Iron Top, extra, . . . . .																

COIL SCREENS.

Height of Screen, from floor to underside of marble top, . . . . .	1 ft. $3\frac{1}{2}$ in.	1 ft. $8\frac{1}{4}$ in.	2 ft. $1\frac{1}{2}$ in.	2 ft. 6 in.
Number of $\frac{3}{4}$ inch tubes the Coil may have in height, . . . . .	6	8	10	12
“ 1 “ “ “ “ “ . . . . .	4	6	8	10

The usual height is 2 ft. 6 in., and is suited for 12- $\frac{3}{4}$  inch or 10-1 inch high Coils.

In ordering, state one, two, three, or four sides. 2 ft. 6 in. high will be assumed, unless otherwise ordered.

- 76 } 8 Price, per running foot, (all heights), measuring outside the body of the Screen, without marble or iron top.  
 77 }

Plain castings, unpainted, . . . . .																
“ “ painted, . . . . .																
Bronzed, chocolate or green, projecting ornaments, gold bronze, . . . . .																
White or colored, with figures and projection, gold bronze, . . . . .																
Gold bronzed, . . . . .																
Marble Tops, OG edge, one inch thick, measured outside of top, per square foot, . . . . .																

COILS OF BENT TUBE.

- 80 9 Tuyere Coils, 1 inch Tube, 18 cents per pound, net cash.  
 81 9 Tuyere with Coil. Coil as above. Castings, per pound, 5 cents, net cash.



CLASS FIRST.—*Continued.*

No. PLATE.

82 9

## SOAP COILS, WITH STRAPS COMPLETE, WITH INTERNAL BLOW-UP-PIPE.

SIZE OF TUBE, . . . .	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$
	\$ c.	\$ c.	\$ c.	\$ c.
Coils under 30 feet long, .	.	1.22	1.44	1.53
“ 50 “ . . . .	.	1.10	1.27	1.36
“ 75 “ . . . .	.	.92	1.14	1.23
Coils over 75 “ . . . .	.90	1.14	1.22	1.42



## COILS OF TUBE OF ORDINARY THICKNESS, FORMED OF LENGTHS WELDED TOGETHER.

Nos. 83, 84, 85, 86, 87, 88, 89. Plate 9. The drawings show the general forms of Coils. It is impossible to give any price per foot of pipe for unusual shapes or dimensions. The table below gives rates for usual kinds, *without strapping*. Coils of ordinary tube are proved at 300 lbs. pressure; those of extra strong are proved at 1000 lbs. pressure; double extra strong Coils proved at any pressure ordered.

Coils will not be made of less diameter nor containing a greater length of tube than given in the list, except at the risk of the party ordering, although it is possible that such may be made at no greater cost.

INSIDE DIAMETER OF TUBE. INCHES, . . . .	BUTT WELDED TUBES.						LAP WELDED TUBES.					
	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4
Least Inside Diameter of Coil. Inches, . . . .	5	7	9	11	14	18	22	30	38	46	54	62
Greatest length of Tube in one coil, welded up. Feet,	60	80	100	130	150	180	200	200	175	150	125	100
	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
Coils in lengths, 20 feet and over to 40 feet, . . . .	.68	.70	.72	.85	1.02	1.30	1.58	2.56	3.66	4.90	6.47	9.00
“ 40 “ 200 “ . . . .	.34	.36	.43	.56	.70	.92	1.18	1.75	2.55	3.00	4.00	4.75

## COILS OF EXTRA STRONG TUBE, FORMED OF LENGTHS WELDED TOGETHER.

Nos. 83, 84, 85, 86, 87, 88, 89. Plate 9.

INSIDE DIAMETER OF TUBE. INCHES, . . . .	BUTT WELDED TUBES.						LAP WELDED TUBES.		
	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$
Least Inside Diameter of Coil. Inches, . . . .	$4\frac{1}{2}$	6	7	8	10	13	16	19	24
Greatest length of Tube in one Coil, welded up. Feet, . . . .	60	80	100	130	150	180	200	200	175
	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
Coils in length, 20 feet and over to 40 feet, . . . .	.74	.76	.80	.94	1.13	1.44	1.74	2.75	4.05
“ 40 “ 200 “ . . . .	.38	.41	.47	.61	.79	1.00	1.28	1.78	2.75

## SPECIAL COILS, CONSTRUCTED FROM WROUGHT IRON TUBE AND FITTINGS.

90 9

Nos. 95, 96, 97, 98, 99, 100. Plate 10. The figures show different arrangements of Tubes, which can be varied or made any size to order, all the materials being standard and usual articles of our stock.

## GAS FITTINGS

## PER POUND.

Plates 12, 13, 14, give the usual numbers as adopted by all manufacturers for each size or kind of fitting.

*In ordering be careful to refer to the edition of the catalogue.*

END OF CLASS FIRST.



[BLANK PAGE]



CCA



# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS FIRST.





Plate 1.

## LAP WELDED BOILER TUBES, STANDARD SIZES.

INSERTED JOINT.



FLUSH JOINT.





[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FIRST.

Plate 2.

WROUGHT IRON WELDED TUBES, STANDARD SIZES.





[BLANK PAGE]



CCA



# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FIRST.


Plate 3.

## EXTRA STRONG WROUGHT IRON WELDED TUBES, STANDARD SIZES.





$\frac{1}{8}$ " EXTRA STRONG.







TUBE OF SPECIAL THICKNESS.  
AS ORDERED.



$\frac{3}{8}$ " EXTRA STRONG.



$\frac{1}{2}$ " DOUBLE EXTRA STRONG.





[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FIRST.

Plate 4.


No 7.



Steam, Gas or Water pipe. Wrought or Galvanized Iron. Butt welded.


No 11.

No 10.




4°

No 12.



10°


No 13.




17°

No 6.


Springs from main.



Wrought Bend.



Section of Steam or taper screw joint.



Section of a hydraulic or cone joint.

No 9.

No 20.



Bushing.

No 8.



Shoulder & close nipples.

No 7.



Locknuts.

Cap.

No 5.



No 4.



No 5.



No 28.



Hydrant Nozzle, Cast Iron.



No 15.

Hydrant Nozzle, wrought Iron.



Longscrew.

No 19.



Plug.

No 3.




Reducing Sockets.

No 2.



Socket.


No 17.




Tees.



Tees.



Ells.




No 14.

Hook.

No 18.




Crosses.




Globe Crosses, Reducing & Corner Fittings.

No 26.



Back Outlet Return Bend.




Square Return Bend.




No 23.

Return Bend.

No 24.



Return Bend.




Drop Elbow.




45° Elbow.

No 29.

No 27.



Side Outlet Return Bend.



Lateral Branch or Y.



Drop Tee.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE

10<sup>th</sup> EDITION


CLASS FIRST.

Plate 5

No 36. Manifolds.



No 37 Valve Manifold.




No 52.

Flange.




No 54.

Bossed Flange.



No 39. Pair of Coil Stands.



No 38.



Double Manifold.


No 40.

No 42.



Hook Plate. Corner Plate.  
to allow Expansion.

No 55.



Flange Union.  
with Bolts.

No 48.



Projecting Single  
Ring Plate.

No 43.



Ring Plate

No 47.



Single  
Ring Plate

No 45.



Rosette Plate.

No 41.



Single  
Hook Plate.



No 49.  
Pipe Stand.

No 53




Oval Flange

No 56.



Collar.

No 46.




Movable Hook Plate  
for Laundry Coils.

No 51.



Double  
Expansion Hanger

No 50.



Expansion  
Hangers.

No 57.



Malleable Iron  
Union Joint.


No 44.



Wall Plate.










# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS FIRST.


Plate 6.




*Radiator for Walls with Manifolds.*



*Radiator for Walls with Return Bends.*



*Radiator for Corners with Valve Manifolds.*



*Radiator for Drying Closets with Return Bend.*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FIRST.


Plate 7

No 70.




*Return Bend or Box Coil.*

No 73.



*Circular Vertical tube Coil.*

No 71.



*Vertical Tube Coil.*




[BLANK PAGE]



CCA




N<sup>o</sup> 77.



*Coil Screen.*

N<sup>o</sup> 76.



*Coil Screen.*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE


10<sup>th</sup> EDITION

CLASS FIRST.


Plate 9




*Heater Coil.*



*Heater Coil*




*Tuyere Coil.*




*No. 89.*

*Tymp Coil.*


*No. 90.*



*Soap Coil.*



*Trunion Coil with internal circulating tubes.*




*Helical Tank Coil.*




*No. 85.*

*Hour glass Coil.*




*No. 86.*

*Double cone Coil.*



*No. 87.*

*Spiral Tank Coil.*



*No. 81.*

*Tuyers with Coil of wrought iron pipe.*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FIRST.


Plate 10.

No 98.




*Condensing square Tank Coil.*

No 99.




*Condensing flat return bend Coil.*

No 97.




No 100.




*Square Tank Coil.*

No 96.



*Return bend flat circular Tank Coil.*

No 95.



*Square spiral Tank Coil.*

FRANKLIN  
INSTITUTE  
LIBRARY.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FIRST.

Plate 12.



## MALLEABLE IRON GAS FITTINGS.




### SERVICE ELBOWS.

MALE AND FEMALE.

### DROP ELBOWS.



MALE & FEMALE




### DROP ELBOWS.

LONG OUTLET.

### ELBOWS WITH SIDE OUTLETS.




### TEES.



★ See Plate 14.







# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS FIRST.


Plate 13.

## MALLEABLE IRON GAS FITTINGS.


### TEES.



### CROSSES.



### DROP ELBOWS. FLANGES RIGHT AND LEFT.



★ See Plate 14.



THE UNIVERSITY OF CHICAGO PRESS

1	2	3	4	5	6	7	8
9	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32
33	34	35	36	37	38	39	40
41	42	43	44	45	46	47	48
49	50	51	52	53	54	55	56
57	58	59	60	61	62	63	64
65	66	67	68	69	70	71	72
73	74	75	76	77	78	79	80
81	82	83	84	85	86	87	88
89	90	91	92	93	94	95	96
97	98	99	100	101	102	103	104
105	106	107	108	109	110	111	112
113	114	115	116	117	118	119	120
121	122	123	124	125	126	127	128
129	130	131	132	133	134	135	136
137	138	139	140	141	142	143	144
145	146	147	148	149	150	151	152
153	154	155	156	157	158	159	160
161	162	163	164	165	166	167	168
169	170	171	172	173	174	175	176
177	178	179	180	181	182	183	184
185	186	187	188	189	190	191	192
193	194	195	196	197	198	199	200
201	202	203	204	205	206	207	208
209	210	211	212	213	214	215	216
217	218	219	220	221	222	223	224
225	226	227	228	229	230	231	232
233	234	235	236	237	238	239	240
241	242	243	244	245	246	247	248
249	250	251	252	253	254	255	256
257	258	259	260	261	262	263	264
265	266	267	268	269	270	271	272
273	274	275	276	277	278	279	280
281	282	283	284	285	286	287	288
289	290	291	292	293	294	295	296
297	298	299	300	301	302	303	304
305	306	307	308	309	310	311	312
313	314	315	316	317	318	319	320
321	322	323	324	325	326	327	328
329	330	331	332	333	334	335	336
337	338	339	340	341	342	343	344
345	346	347	348	349	350	351	352
353	354	355	356	357	358	359	360
361	362	363	364	365	366	367	368
369	370	371	372	373	374	375	376
377	378	379	380	381	382	383	384
385	386	387	388	389	390	391	392
393	394	395	396	397	398	399	400
401	402	403	404	405	406	407	408
409	410	411	412	413	414	415	416
417	418	419	420	421	422	423	424
425	426	427	428	429	430	431	432
433	434	435	436	437	438	439	440
441	442	443	444	445	446	447	448
449	450	451	452	453	454	455	456
457	458	459	460	461	462	463	464
465	466	467	468	469	470	471	472
473	474	475	476	477	478	479	480
481	482	483	484	485	486	487	488
489	490	491	492	493	494	495	496
497	498	499	500	501	502	503	504
505	506	507	508	509	510	511	512
513	514	515	516	517	518	519	520
521	522	523	524	525	526	527	528
529	530	531	532	533	534	535	536
537	538	539	540	541	542	543	544
545	546	547	548	549	550	551	552
553	554	555	556	557	558	559	560
561	562	563	564	565	566	567	568
569	570	571	572	573	574	575	576
577	578	579	580	581	582	583	584
585	586	587	588	589	590	591	592
593	594	595	596	597	598	599	600
601	602	603	604	605	606	607	608
609	610	611	612	613	614	615	616
617	618	619	620	621	622	623	624
625	626	627	628	629	630	631	632
633	634	635	636	637	638	639	640
641	642	643	644	645	646	647	648
649	650	651	652	653	654	655	656
657	658	659	660	661	662	663	664
665	666	667	668	669	670	671	672
673	674	675	676	677	678	679	680
681	682	683	684	685	686	687	688
689	690	691	692	693	694	695	696
697	698	699	700	701	702	703	704
705	706	707	708	709	710	711	712
713	714	715	716	717	718	719	720
721	722	723	724	725	726	727	728
729	730	731	732	733	734	735	736
737	738	739	740	741	742	743	744
745	746	747	748	749	750	751	752
753	754	755	756	757	758	759	760
761	762	763	764	765	766	767	768
769	770	771	772	773	774	775	776
777	778	779	780	781	782	783	784
785	786	787	788	789	790	791	792
793	794	795	796	797	798	799	800
801	802	803	804	805	806	807	808
809	810	811	812	813	814	815	816
817	818	819	820	821	822	823	824
825	826	827	828	829	830	831	832
833	834	835	836	837	838	839	840
841	842	843	844	845	846	847	848
849	850	851	852	853	854	855	856
857	858	859	860	861	862	863	864
865	866	867	868	869	870	871	872
873	874	875	876	877	878	879	880
881	882	883	884	885	886	887	888
889	890	891	892	893	894	895	896
897	898	899	900	901	902	903	904
905	906	907	908	909	910	911	912
913	914	915	916	917	918	919	920
921	922	923	924	925	926	927	928
929	930	931	932	933	934	935	936
937	938	939	940	941	942	943	944
945	946	947	948	949	950	951	952
953	954	955	956	957	958	959	960
961	962	963	964	965	966	967	968
969	970	971	972	973	974	975	976
977	978	979	980	981	982	983	984
985	986	987	988	989	990	991	992
993	994	995	996	997	998	999	1000



# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS FIRST.


Plate 14.

## MALLEABLE IRON GAS FITTINGS.


### DROP TEES, FEMALE.





### DROP TEES, MALE.



### CAPS.




### PLUGS.




### EXTENSION PIECE


### REDUCING SOCKETS.




### LOCK NUTS.




### PIPE STRAPS.




### PIPE HOOKS.




Omitted on Plate 12.



165




227.




Omitted on Plate 13.

Omitted on Plate 14.



461



535.







*Persons in ordering will please state the "Edition" they order from.*

## CLASS SECOND.

Every order for special articles must have accurate plans and dimensions attached; and no order, "same as before," will be received. Any article for which no price is quoted on the list will be made only to special order, although such article may be shown in the illustrations.

### VALVES AND COCKS.

TABLE OF STANDARD DIMENSIONS OF STEAM VALVES AND COCKS.

The lists of Prices refer to Valves and Cocks only of these dimensions. Any change in diameter of flanges, or in length from face to face, or end to end, must be made by special order; and it is to be noted, that the cost of such changes is often quite disproportionate to the price of the standard articles.

DIAMETERS OF OPENINGS IN VALVES OR COCKS, . . .	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4	5	6	8	10	12
Diameter of Flanges. Inches, . . . . .	.	.	.	.	.	.	.	6	7	$7\frac{1}{2}$	8	9	10	11	$13\frac{1}{2}$	16	19
Diameter of centre of Bolts. Inches, . . . . .	.	.	.	.	.	.	.	$4\frac{3}{4}$	$5\frac{1}{2}$	6	$6\frac{1}{2}$	$7\frac{1}{4}$	$8\frac{3}{8}$	$9\frac{3}{8}$	$11\frac{3}{4}$	14	$16\frac{3}{4}$
Number of Bolts in Flange, . . . . .	.	.	.	.	.	.	.	4	4	4	5	5	6	6	8	10	10
Diameter of Bolts. Inches, . . . . .	.	.	.	.	.	.	.	$\frac{1}{2}$	$\frac{1}{2}$	$\frac{3}{16}$	$\frac{*3}{16}$	$\frac{*5}{8}$	$\frac{5}{8}$	$\frac{5}{8}$	$\frac{5}{8}$	$\frac{3}{4}$	$\frac{3}{4}$
Rock Patent Ring Valves, screw ends (brass), } Nos. 27, 32. Face to face, }	.	.	$2\frac{3}{16}$	$2\frac{5}{8}$	$3\frac{1}{8}$	$3\frac{1}{16}$	$4\frac{3}{8}$	$5\frac{5}{16}$	$6\frac{5}{8}$	$7\frac{1}{16}$	.	.	.	.	.	.	.
Rock Patent Ring Valves, screw ends (iron body), } Nos. 12, 33. Face to face, }	.	.	.	.	$3\frac{5}{8}$	4	$4\frac{1}{2}$	$5\frac{1}{2}$	7	8	.	.	.	.	.	.	.
Face to face of Flanges of Iron Body Valves, Nos. 1, 3, { Inches and decimals, }	.	.	.	.	.	.	.	5.75	7.25	9.25	10.25	11.25	13.25	15.25	19.00	23.00	27.00
Face to face of Flanges of Iron Body Cocks, No. 40, }	.	.	.	.	.	.	.	.	.	8.40	9.50	10.60	13.85	.	.	.	.
{ End to end of IRON BODY VALVES, No. 1, }	.	.	.	.	.	.	.	.	.	9.25	10.25	11.25	13.25	15.25	.	.	.
{ Distance end to end of Tubes, when made up } in Iron Body Valves, No. 1, }	.	.	.	.	.	.	.	.	.	7.00	8.07	8.77	10.55	12.35	.	.	.
{ End to end of IRON BODY VALVES, No. 3, }	.	.	.	.	4.15	4.50	5.10	5.90	7.30	9.25	10.25	.	.	.	.	.	.
{ Distance end to end of Tubes, when made up } in Iron Body Valves, No. 3, }	.	.	.	.	2.87	3.17	3.54	4.48	5.14	7.00	8.07	.	.	.	.	.	.
{ End to end of BRASS VALVES, No. 20, }	1.45	1.78	2.20	2.65	3.30	3.85	4.35	5.30	6.75	7.75	.	.	.	.	.	.	.
{ Distance end to end of Tubes, when made } up in Brass Valves, No. 20, }	0.87	1.18	1.42	1.85	2.28	2.78	3.25	4.10	4.97	5.85	.	.	.	.	.	.	.
{ End to end of IRON BODY COCKS, No. 40, }	.	1.85	2.50	2.90	3.45	4.10	4.55	5.45	7.10	8.40	9.50	10.60	13.85	.	.	.	.
{ Distance end to end of Tubes, when made } up in Iron Body Cocks, No. 42, }	.	1.08	1.50	1.99	2.17	2.77	3.19	4.03	4.94	6.12	7.12	8.12	11.15	.	.	.	.
{ End to end of BRASS COCKS, No. 41, }	1.53	1.85	2.50	2.90	3.45	4.10	4.55	5.45	7.10	8.40	9.50	10.60	.	.	.	.	.
{ Distance end to end of Tubes, when made } up in Brass Cocks, No. 41, }	0.95	1.25	1.72	2.10	2.43	3.03	3.45	4.29	5.22	6.50	7.50	8.50	.	.	.	.	.
{ End to end of IRON ROUND-WAY COCKS, } Nos. 92, 93, }	.	.	.	3.50	4.10	4.85	5.36	6.60	8.20	11.62	.	.	.	.	.	.	.
{ Distance end to end of Tubes, when made } up in Iron Round-way Cocks, Nos. 92, 93, }	.	.	.	2.49	2.82	3.52	4.00	5.18	6.04	9.34	.	.	.	.	.	.	.
{ End to end of BRASS ROUNDWAY COCKS, } Nos. 92, 93, }	.	.	.	3.10	3.66	4.35	4.97	6.35	7.70	11.10	.	.	.	.	.	.	.
{ Distance end to end of Tubes, when made up } in Brass Round-way Cocks, Nos. 92, 93, }	.	.	.	2.30	2.54	3.28	3.87	5.19	5.92	9.20	.	.	.	.	.	.	.
Face to face of EXPANSION JOINTS, No. 10, when cold or drawn out.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.	.
6 inch traverse, . . . . .	.	.	.	.	.	.	.	.	.	21.25	.	21.65	22.05	22.45	23.25	24.05	.
10 inch traverse, . . . . .	.	.	.	.	.	.	.	.	.	25.25	.	25.65	26.05	26.45	27.25	28.05	.
End to end of EXPANSION JOINTS, No. 10, Traverse, . . . . .	.	.	6.90	7.67	8.54	9.67	10.46	12.08	13.75	.	.	.	.	.	.	.	.
	.	.	1.80	2.05	2.28	2.45	2.65	3.03	3.43	.	.	.	.	.	.	.	.

The dimensions of Angle, Cross, or Safety Valves, from centre to face of flange or end, can be got by taking one-half the length face to face, or end to end of ordinary valves of corresponding sizes, from the above table.

\* The  $3\frac{1}{2}$  inch flanges can have  $4\frac{5}{8}$  bolts, and the 4 inch flanges can have  $4\frac{3}{4}$  bolts; but the joint is not likely to be so good as when the tabular numbers and dimensions are used.



## CLASS SECOND.—Continued.

## VALVES AND COCKS.

		DIAMETERS OF OPENINGS, . .	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4	5	6	8	10	12
No.	PLATE.		\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
GLOBE AND ANGLE VALVES.																			
12 } 33 }	2 3	{ Rock Patent Ring Valve, iron body, flange, Rock Patent Ring Valve, iron body, screw, Rock Patent Ring Valve, brass, screw,																	
13	2	{																	
27 } 32 }	3 3	{																	
1	1	{ *Iron Body Steam Valves, flange ends, Iron Body Steam Valves, screw ends, Brass Steam Valves, screw ends,	.90	1.00	1.35	1.85	2.50	3.50	4.75	7.35	12.50	20.00	33.00	50.00	.	.	.	.	.
3	1	{					3.38	4.25	5.00	7.25	14.00	18.00	23.60	31.00	41.00	.	.	.	.
20	3	{ All Iron Steam Valves, screw ends,			5.20	5.90	6.65	7.45	9.30	11.15	13.30	.	.	.	.	.	.	.	.
CROSS VALVES.																			
4	1	{ Iron Body Steam Valves, flange ends, Iron Body Steam Valves, screw ends,						5.50	6.90	9.50	18.50	22.50	29.00	37.00	48.00	63.00	.	.	.
4	1	{					3.78	4.75	5.75	8.50	17.50	21.00	26.00	35.00	46.00	61.00	.	.	.
22	3	{ Brass Steam Valves, screw ends,	1.20	1.45	1.80	2.70	3.85	5.30	6.80	10.35	24.00	35.00	.	.	.	.	.	.	.
CHECK VALVES, HORIZONTAL, VERTICAL OR ANGLE.																			
5	1	{ Iron Body Check Valves, flange ends, Iron Body Check Valves, screw ends,								7.00	14.50	17.50	21.00	29.00	38.00	51.00	.	.	.
28, 29, 30,	3	{ Brass Check Valves, screw ends,	1.00	1.10	1.35	2.00	2.85	3.90	5.00	7.65	15.00	24.00	.	.	.	.	.	.	.
BACK PRESSURE VALVES.																			
6	1	{ Iron Body Back Pressure Valves, flange ends, Iron Body Back Pressure Valves, screw ends,								17.50	21.50	26.00	34.00	36.50	49.00	64.50	116.00	.	.
6	1	{								16.00	19.00	26.00	.	38.00	.	.	.	.	.
† SAFETY VALVES, GLOBE, ANGLE OR HORIZONTAL.																			
2	1	{ Iron Body Safety Valves, flange ends, Iron Body Safety Valves, screw ends,								12.50	22.50	28.00	35.00	43.00	57.50	72.50	152.00	.	.
25	3	{						6.25	7.75	11.50	19.60	26.50	33.50	41.00	.	.	.	.	.
25	3	{ Brass Safety Valves, screw ends			3.00	4.25	5.75	8.00	10.50	16.00	27.00	.	.	.	.	.	.	.	.
26	3	{ Do. do. angle, do.																	
THROTTLE VALVES.																			
101	6	{ Iron Body Throttle Valves, to go in flange joints, Iron Body Throttle Valves, with flanges for tubes and bolts,							4.00	6.50	8.00	12.00	17.90	20.30	25.00	32.00	.	.	.
101	6	{								12.80	14.15	15.85	17.90	20.30	25.00	32.00	.	.	.
106	6	{ Brass Throttle Valves, screw ends,			2.65	3.45	4.85	6.50	8.65	14.25	22.20	33.35	.	.	.	.	.	.	.
STEAM AND WATER COCKS, BEST STEAM METAL.																			
40	4	{ Iron Cocks, all iron, flange ends, Iron Cocks, all iron, screw ends,		.85	.95	1.10	1.45	1.85	2.35	3.90	6.90	9.50	13.50	18.00	46.50	.	.	.	.
40	4	{ Iron Cocks, brass plugs, flange ends,								8.30	13.85	22.25	34.00	39.75	95.00	.	.	.	.
42	4	{ Iron Cocks, brass plugs, screw ends,		1.20	1.30	1.70	2.20	2.90	3.85	6.80	11.75	19.50	30.50	40.00	89.00	.	.	.	.
41	4	{ Brass Cocks, screw ends, Brass Cocks, with union (screw or solder) one end and screw the other,	.65	.75	1.25	1.60	2.50	3.80	5.25	7.50	16.00	28.00	.	.	.	.	.	.	.
45	4	{	1.55	1.80	2.15	3.00	4.20	5.80	8.00	13.60	23.25	.	.	.	.	.	.	.	.
Not drawn.		{ Iron Cocks, all iron, Round- way, flange ends, Iron Cocks, all iron, Round- way, screw ends,								8.80	13.70	20.50	29.50	41.25	.	.	.	.	.
92 & 93	6	{				1.80	2.50	3.35	4.40	7.30	11.60	17.75	26.00	37.00	.	.	.	.	.
Not drawn.		{ Iron Cocks, brass plugs, Round-way, flange ends, Iron Cocks, brass plugs, Round-way, screw ends,								15.00	23.10	34.50	50.00	71.25	.	.	.	.	.
92 & 93	6	{				2.50	3.90	5.50	7.40	13.50	21.00	31.75	46.50	67.00	.	.	.	.	.
92 & 93	6	{ Brass Cocks, Roundway, screw or pitcher nose, Three-way Cocks, all iron, flange ends, Three-way Cocks, all iron, screw ends,				3.20	5.00	7.20	9.90	17.20	27.70	42.20	.	.	.	.	.	.	.
Not drawn.		{								7.45	11.85	18.15	27.00	38.40	.	.	.	.	.
50	4	{					1.95	2.50	3.15	5.20	8.70	14.00	21.75	32.00	.	.	.	.	.
Not drawn.		{ Three-way Cocks, iron, brass plugs, flange ends, Three-way Cocks, iron, brass plugs, screw ends,								10.35	17.10	27.15	41.50	59.90	.	.	.	.	.
50	4	{					2.70	3.55	4.65	8.10	13.95	23.00	36.25	53.50	.	.	.	.	.
50	4	{ Brass Three-way Cocks, screw ends,			2.15	2.95	4.15	5.90	8.25	14.50	26.00	43.00	.	.	.	.	.	.	.

\* Iron Body Steam Valves have all surfaces of contact brass, loose disks, and spherical seats. Valves 1 inch to  $2\frac{1}{2}$  inches, have inside valve screws; above  $2\frac{1}{2}$  inches, Valves have outside valve screws. Brass Steam Valves, of all sizes, have inside valve screws.

† What is known as a Globe Safety Valve is shown, (figs. 2, plate 1, and figs. 25, plate 3.) Horizontal Safety Valves made to order, same prices as other Safety Valves; these correspond in form to what is known as a Globe Valve. Our Standard Safety Valve has a lever or arm, with Ball, for 80 pounds maximum pressure. Safety Valves for other pressures, not over 120 pounds, made as ordered, with an extra charge of per cent.



## CLASS SECOND.—Continued.

## VALVES, COCKS, &amp;c.

DIAMETER OF OPENINGS. INCHES, . . . . .		$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4	5	6	8	10
No. PLATE.		\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
10	2	Expansion Joints.	{ Iron body with brass sleeves, flange, 6 inch traverse, }	.	.	.	.	.	.	.	26.40	.	35.50	46.75	60.50	96.25	140.00
		"	{ Iron body with brass sleeves, flange, 10 inch traverse, }	.	.	.	.	.	.	.	31.20	.	42.00	55.25	71.50	113.25	160.00
11	2		{ Iron body with brass sleeves, screw, traverse from table, }	.	.	.	.	3.50	4.80	8.00	12.00	16.80	.	.	.	.	.
70	5	"	{ Brass Expansion Joints, screw, traverse from table, }	.	.	2.40	3.20	4.40	6.40	9.60	.	.	.	.	.	.	.
108	6	Swing Joints.	Brass Steam Swing Joints, screw, .	.	.	2.00	2.60	3.60	5.00	6.80	11.80	.	.	.	.	.	.
75	5	Union Joints.	{ Brass Unions, both ends screw, }	.	.	.	.	.	.	.	.	.	.	.	.	.	.
74	5	"	{ Brass Unions, one end screw and one end solder, }	.55	.65	.80	1.15	1.60	2.10	2.70	4.00	5.75	.	.	.	.	.
99	6	Foot & Check Valves.	{ Iron Vertical Foot Valves, leather seat, flange, }	.	.	.	.	.	.	7.20	9.60	12.15	14.90	17.75	24.00	30.50	.
107	6	"	{ Iron Vertical Foot Valves, leather seat screw, }	.	.	.	.	3.20	4.00	5.70	7.50	9.40	11.40	13.50	18.00	23.00	.
102	6	"	Strainers, (flange, if ordered, extra,)	.	.	.	.85	1.10	1.45	1.90	2.60	3.80	5.40	.	.	.	.
105	6	"	{ Iron Horizontal Hinge Valves, leather or brass valve, on iron seat, screw, }	.	.	.	.	.	.	7.70	10.00	13.00	.	.	.	.	.

## GAUGE COCKS, OIL CUPS, STEAM WHISTLES.

All brass finished work.

51	4*	Gauge Valves.	{ Self-packing stem, wood wheel, }	Length over all, . . . . .	6 inches, 8 inches, $9\frac{1}{2}$ inches.
				Diameter of shank, (tube thread), . . . . .	$\frac{1}{2}$ " $\frac{3}{4}$ " 1 "
				Price, . . . . .	\$3.25 \$5.00 \$7.20
52	4	Gauge Cocks.	{ Locse valve, stem for regrinding valve, with seat; compression lever handle, }	Diameter of shank, (tube thread), . . . . .	$\frac{1}{2}$ $\frac{3}{4}$ 1 $1\frac{1}{4}$ inches.
				Price, . . . . .	\$2.33 2.33 2.33 2.33
53	4	Gauge Cocks.	{ With hollow plug, steamboat pattern, }	Length over all, . . . . .	5 inches.
				Diameter of shank, (tube thread), . . . . .	$\frac{3}{4}$ or 1 "
				Price, . . . . .	\$5.50 (finished), \$5.00 (rough).
56	4	Gauge Cocks.	{ Mississippi pattern, }	Diameter of plain shank, . . . . .	$\frac{3}{8}$ $\frac{1}{2}$ $\frac{3}{4}$ 1 $1\frac{1}{4}$ $1\frac{1}{2}$ inches.
				Price, . . . . .	\$1.50 1.50 1.66 2.00 3.00 3.75
57	4	Gauge Cocks.	{ Plain Gauge Cock, }	Diameter of shank, . . . . .	$\frac{3}{8}$ $\frac{1}{2}$ $\frac{3}{4}$ inches.
				Price, . . . . .	\$0.90 1.00 1.10
55	4	Gauge Cocks.	{ New York pattern, compression, lever handle, }	Length over all, . . . . .	4 inches.
				Diameter of shank, (tube thread), . . . . .	$\frac{1}{2}$ "
				Price, . . . . .	\$1.50
54	4	Air or Pet Cocks.	{ There are three sizes of body, but the openings through these Cocks are one-eighth inch diameter, }	Diameter of shank, (tube thread size), . . . . .	$\frac{1}{8}$ $\frac{1}{4}$ $\frac{3}{8}$ $\frac{1}{2}$ $\frac{3}{4}$ inch.
				Price, . . . . .	\$0.80 1.00 1.50 1.50 1.50
72	5	Oil Cups.	{ Plain Oil Cups, }	Diameter of bowl, $\frac{7}{8}$ 1 $1\frac{3}{16}$ $1\frac{1}{2}$ $1\frac{5}{8}$ 2 2 $2\frac{1}{4}$ $2\frac{3}{4}$ inches.	
				Price, . . . . .	\$0.90 1.05 1.35 1.50 1.85 2.70 3.70 4.45 6.15
71	5	Oil Cups.	{ Globe Oil Cups, with double Cocks and Air Cock, }	Height over all, $4\frac{1}{4}$ 5 6 $6\frac{1}{2}$ $7\frac{1}{2}$ 9 $9\frac{1}{2}$ 10 inches.	
				Diameter of Globe, $1\frac{5}{8}$ $1\frac{7}{8}$ $2\frac{1}{8}$ $2\frac{1}{2}$ 3 $3\frac{1}{4}$ 4 $4\frac{1}{4}$ "	
				Number, . . . . .	00 0 1 2 3 4 5 6
				Price, . . . . .	\$5.33 6.67 7.33 8.67 10.00 12.67 21.33 26.67
86	5	Steam Whistles.	{ Steam Whistles }	Diameter of Bell, 2 $2\frac{1}{2}$ 3 $3\frac{1}{2}$ 4 5 6 inches.	
				Price, . . . . .	\$16.00 19.33 22.00 24.00 26.67 36.00 48.00

\* The shanks of Gauge Valves or Cocks will have tube threads the size given, or will be left plain the proper sizes for tube threads. If other sizes of shanks are wanted, they will be made to order—



CLASS SECOND—Continued.

## ARTICLES OF OCCASIONAL DEMAND.

END OF CLASS SECOND.




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION


CLASS SECOND.

Plate 1.




No 1.

*Flanged Globe Valve.*




No 3.

*Screwed Globe Valve.*




No 5.

*Globe Vertical & Horizontal  
Check Valve.*




No 2.

*Globe Safety Valve.*



No 4.

*Globe Cross Valve.*



No 6.

*Globe Back-pressure Valve.*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION


CLASS SECOND.

Plate 2.




No. 70.

*Expansion Joint, Cast Iron  
with Brass Sleeve, Flange Ends.*




No. 71.

*Expansion Joint,  
Cast Iron with Brass Sleeve, Screw Ends.*




No. 72.

*Rock Patent  
Ring Valve, (Iron Body, Flange.)*




No. 73.

*Rock Patent Ring Valve  
(Iron Body, Screw.)*




No. 76.

*Water Tank Valve  
with Strainer.*



No. 74.

*Flanged Globe Angle Valve.*



No. 75.

*Screwed Globe Angle Valve.*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS SECOND.


Plate 3.



Globe Valve.



Angle Valve.




Cross Valve.




Angle Pressure Valve.




Globe Corner Valve.



Globe Safety Valve.




Angle Safety Valve.



Rock Patent Ring Valve.




Horizontal Check Valve.




Vertical Check Valve.



Angle Check Valve.



Twin Safety Valve.




Sect. of Rock Patent Brass Ring Valve.

## DESCRIPTION.

A—represents the Valve Stem.  
B—is the Ring which is open and expandible, and is loosely attached to the Disks F and G by the Rib E E.  
C—shows the wedge-shaped opening in the Ring.  
D—is the Wedge which is attached to the Shell of the Valve at one side of the Seat with the point upward.  
E E—is a Rib which is a part of the Ring.  
F and G—are the Disks attached to the Valve-stem, which are upon either side of the Rib E, and by which the Ring is raised and lowered.

It will be seen that the open portion of the Ring (which passes in loosely) will be expanded by the Wedge, and that it will tightly close both openings when it reaches a point near the bottom of its seat.

This Valve never needs grinding, has a verticle motion only, or does not revolve, and leaves a clear and unobstructed passage for the flow of the liquid.



Section of Rock Pat. Ring Valve, Iron Body flanged.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS SECOND.

Plate 4.

No 40.




Iron Cock, flanged  
No 46.




Cock Wrench

No 41




Brass Cock.

No 42.




Iron Cock with  
Brass or Iron Plug.

No 43.




Angle Cock  
for Sugar house use.  
No 50.

No 44.




Gas Meter Cock,  
one end Male screw the  
other end solder.

No 45.




Brass Steam Cock  
with soldering Union.  
No 49.

No 47.




Gas Meter Cock.


No 48.



Gas Meter Cock  
with soldering union.




Gas Service Cock.



Threeway iron Cock.

No 51.




Gauge Valve, wooden Wheel.

No 52.



Gauge Cock,  
Lever handle.

No 53.



Gauge Cock.

No 54.



Air or pet Cocks.

No 55.



New York  
Gauge Cock.

No 56.




Mississippi Gauge Cock.

No 57.




Gauge Cock.

No 58.




Straight Hydrant Cock  
& waste.

No 60.




Crooked Hydrant Cock  
& waste.

No 61.



Hydrant Cock.

No 58.



Iron pipe stop.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS SECOND.


Plate 5.

No 65.




Brass Bibb Cock, Lever handle with male Screw.

No 66.




Brass Bibb Cock, Hose screw nozzle.

No 67.




Brass Bibb Cock, Lever handle, plain end.

No 68.




Large Bibb Cock, female Screw.

No 69.



Basin Cock.

No 70.



Brass expansion Joint.

No 71.



Globe Oil Cup with double Cocks & Air Cock.

No 72.




Oil Cup.

No 73.




Bath Boiler Union, straight.

No 74.



Union Joint one end Screw the other Solder.

No 75.



Union Joint both ends Screw.

No 76.



Basin Plug & Chain.



No 77.

Basin Plug & Chain.

No 78.



Bath tub Strainer.

No 79.




Wash tube waste and Plug.

No 80.



Bath Boiler Union, Goose neck.

No 86.



Steam Whistle.

No 81.



Boiler Ferrule.

No 82.



Soldering Nipple. Hose Nipple Parement wash.

No 83.



male and female end.

No 84.



male end. Hose Nipple Parement wash.

No 85.



Hose reducing Socket Parement wash.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS SECOND.

Plate 6.





[BLANK PAGE]



CCA



*Persons in ordering will please state the "Edition" they order from.*

## CLASS THIRD.

Every order for special articles must have accurate plans and dimensions attached, and no order, "same as before," will be received.  
Any article for which no price is quoted on the list will be made only to special order, although such article may be shown in the illustrations.

### TOOLS FOR FITTING WROUGHT IRON TUBES.

The threads upon wrought iron tubes are as follows: on  $\frac{1}{8}$  inch, 27 to the inch; on  $\frac{1}{4}$  and  $\frac{3}{8}$  inch, 18 threads to the inch; on  $\frac{1}{2}$  and  $\frac{3}{4}$  inch, 14 threads to the inch; on 1,  $1\frac{1}{4}$ ,  $1\frac{1}{2}$ , and 2 inches, 11 $\frac{1}{2}$  threads to the inch; on  $2\frac{1}{2}$  to 8 inches, 8 threads to the inch.

No.	PLATE.	SOLID DIES, P. W. (GATES' PATENT).		
1	1	2 inches square by $\frac{1}{2}$ inch thick, for $\frac{1}{8}$ , $\frac{1}{4}$ , or $\frac{3}{8}$ inch tubes,	3 inches square by $\frac{3}{4}$ inch thick, for $\frac{1}{2}$ , $\frac{3}{4}$ , or 1 inch tubes,	4 inches square by 1 inch thick, for $1\frac{1}{4}$ , $1\frac{1}{2}$ , or 2 inch tubes,
		Each, . . . . \$1.43	\$2.30	\$4.20
2	1	SCREWING STOCKS FOR SOLID DIES, (WITH GUIDES).		
3	1			
		No. 1. for $\frac{1}{4}$ , $\frac{3}{8}$ , and $\frac{1}{2}$ inch tubes,	No. 2. for $\frac{3}{4}$ and 1 inch tubes,	No. 3, (with leader screws), for $1\frac{1}{4}$ , $1\frac{1}{2}$ , and 2 inch tubes,
		Each, . . . . \$2.75	\$3.90	\$7.05
		Same, complete with Dies, each, . . . . 7.05	8.50	19.65
		Guides for same, if wanted separate, each, .25	.35	.50

### TAPS, REAMERS, AND DRILLS.

		Diameter of Tube, in inches,	$\frac{1}{8}$	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4
4	1	Tap Wrenches, . . . . .	\$0.95	\$0.95	\$1.00	\$1.00	\$2.05	\$2.05	\$2.05	\$3.35	\$3.35	\$4.25	\$4.25	\$5.00	\$5.00
5	1	Taps, right or left hand, . . . . .	.53	.65	.70	.95	1.32	1.68	1.91	2.31	3.41	5.22	7.37	9.95	13.34
6	1	Fluted Reamers, . . . . .	1.50	1.60	1.80	2.00	2.50	3.05	3.75	4.50	6.50	9.00	12.00	16.75	22.00
7	1	Drills, . . . . .	.91	.91	.95	.98	1.04	1.14	1.23	1.35	1.56				
8	1	Chasers, (outside), . . . . .	.65	.65	.65	.65	.65	.65	.65	.65	.65	.65	.65	.65	.65
9	1	Chasers, (inside), . . . . .	.97	.97	.97	.97	.97	.97	.97	.97	.97	.97	.97	.97	.97
10	1	Eccentric Reamers, . . . . .	.96	1.00	1.05	1.33	1.80	2.41	2.56	3.06	4.19				
11	1	Stock and Dies for Brass Tubes, . . . . .													\$12.00
12	1	Gas Fitters' Torches, . . . . .													1.05
13	1	Gas Fitters' Blow-pipes, . . . . .													1.10
14	1	Gas Fitters' Proving Pumps, . . . . .						No 1, \$32.00			No 2, \$34.00			No 3, \$27.00	
15	1	Drip Pumps, for Gas Main Drips, . . . . .													33.33
16	1	Patent Flue Cutter, . . . . . $1\frac{1}{2}$ inch flues,													
		Each, . . . . .	\$16.00												
		Patent Flue Cutter, . . . . . 2 inch flues,													
		Each, . . . . .	\$18.00												
		Patent Flue Cutter, . . . . . $2\frac{1}{2}$ inch flues,													
		Each, . . . . .	\$21.00												
		Patent Flue Cutter, . . . . . 3 inch flues,													
		Each, . . . . .	\$25.00												
		Patent Flue Cutter, . . . . . $3\frac{1}{2}$ inch flues,													
		Each, . . . . .	\$30.00												
		Patent Flue Cutter, . . . . . 4 inch flues,													
		Each, . . . . .	\$36.00												
		Patent Flue Cutter, . . . . . $1\frac{1}{2}$ and $1\frac{3}{4}$ inch flues,													
		Each, . . . . .	\$20.00												
		Patent Flue Cutter, . . . . . 2 and $2\frac{1}{4}$ inch flues,													
		Each, . . . . .	\$22.50												
		Patent Flue Cutter, . . . . . $2\frac{1}{2}$ and $2\frac{3}{4}$ inch flues,													
		Each, . . . . .	\$26.00												
		Patent Flue Cutter, . . . . . 3 and $3\frac{1}{4}$ inch flues,													
		Each, . . . . .	\$30.50												
		Patent Flue Cutter, . . . . . $3\frac{1}{2}$ and $3\frac{3}{4}$ inch flues,													
		Each, . . . . .	\$36.00												
17, 23	1	Universal Gas Tube Vise, . . . . .							No. 17, $\frac{1}{4}$ to 2 inch tube,				No. 23, $\frac{3}{4}$ to 4 inch tube,		
		Each, . . . . .							\$22.80				\$42.40		
18	1	Same, with Bench piece, without stand, . . . . .							14.80						
		Set of New Dies for same, per set, . . . . .													\$5.00
19	1	Vise Clamp for holding tubes in an ordinary vise, each, . . . . .													9.00
20	1	Breast Drill, each, . . . . .													8.15
21	1	Crow for Drilling and Tapping Street Mains, . . . . .							$1\frac{1}{2}$ to 3 inch mains,		3 to 6 inch mains,		4 to 12 inch mains,		
		Each, . . . . .							\$11.25		\$14.25		\$18.62		
22	1	Ratchet Wrench, each, . . . . .													\$17.60
		Diameter of Tubes, in inches, . . . . .		$2\frac{1}{2}$	3	$3\frac{1}{2}$	4	$4\frac{1}{2}$	5	6	7	8			
30	2	Clevis Tongs, . . . . .		\$5.40	\$6.20	\$7.00	\$8.00	\$9.10	\$10.00	\$12.50	\$15.00	\$18.00			
		Extra Hooks for same, . . . . .		1.80	2.10	2.40	2.60	3.00	3.55	4.20	5.00	5.50			



CLASS THIRD.—*Continued.*

No.	PLATE.	No. 31.	No. 32.	No. 33.	No. 34.	No. 35.			No. 36.	No. 37.			No. 38.	No. 39.	No. 40.	No. 41.			
	2					1	2	3		1	2	3							
		Chisels	cold,	cape,	wall drill,	calking,			set,	driving,			wood,	plaster,	long wood,	floor,			
		Each,	\$0.56	\$0.58	\$0.51	\$0.61	\$0.85	\$0.77	\$0.56	\$0.36	\$1.15	\$0.85	\$0.82	\$0.60	\$1.84	\$1.13	\$2.12		
42	2	Augers,	$\frac{1}{4}$ inch tube,	$\frac{3}{8}$ inch tube,	$\frac{1}{2}$ inch tube,	$\frac{3}{4}$ inch tube,	1 inch tube,	$1\frac{1}{4}$ inch tube,	$1\frac{1}{2}$ inch tube,	$1\frac{3}{4}$ inch tube,	2 inch tube,								
		Each,	\$1.12	\$1.12	\$1.50	\$1.87	\$2.25	\$2.62	\$3.00	\$3.37									
43	2	Wolfkiel's Patent Wrench,	No. 1.			No. 2.			No. 3.										
			$\frac{1}{2}, \frac{5}{8}, \frac{3}{4}$ inch bolts,			$\frac{7}{8}, 1, 1\frac{1}{2}$ inch bolts,													
44	2	Foster's Patent Tube Cutter,							No. 1.			No. 2.			No. 3.				
		Each,							$\frac{1}{4}$ to 1 inch tubes,					1 to 2 inch tubes,					
		Knives for same,							\$8.00					\$10.00					
		Rolls for same,							.60					.75					
									.30					.30					
45	2	Dudgeon's Patent Tube Expander.																	
		External Diameter of Tube, in inches,	1	$1\frac{1}{4}$	$1\frac{1}{2}$	$1\frac{3}{4}$	$1\frac{7}{8}$	2	$2\frac{1}{4}$	$2\frac{1}{2}$	$2\frac{3}{4}$	3	$3\frac{1}{4}$	$3\frac{1}{2}$	4	$4\frac{1}{2}$	5	6	7
		Each,	\$20	\$20	\$20	\$25	\$25	\$30	\$35	\$42	\$48	\$55	\$60	\$70	\$85	\$100	\$120	\$130	\$180
46	2	Stanwood's Patent Tube Cutter,				No. 1.			No. 2.			No. 3.							
		Each,				$\frac{1}{8}$ to $\frac{3}{4}$ inch tubes,			$\frac{3}{4}$ to 2 inch tubes,			2 to 3 inch tubes,							
		Wheels for same,				\$7.50			\$9.00			\$18.00							
						.56			.70			1.20							
47	2	Peake & Guillaudeu's Patent Wrench,				No. 1.			No. 2.			No. 3.							
		Each,							16 inch arm,										
									1 to 2 inches square,										
									\$3.50										
48	2	Tube Tongs.																	
		Diameter of Tubes, in inches,	$\frac{1}{8}$	$\frac{1}{4}$	$\frac{3}{8}$	$\frac{1}{2}$	$\frac{3}{4}$	1	$1\frac{1}{4}$	$1\frac{1}{2}$	2	$2\frac{1}{2}$	3	$3\frac{1}{2}$	4				
		Price, per pair,	\$1.00	\$1.10	\$1.20	\$1.30	\$1.55	\$2.00	\$2.20	\$2.55	\$3.35	\$4.30	\$4.75	\$5.75	\$6.75				
49	2	Brown's Patent Adjustable Tongs,	No. 1.			No. 2.			No. 3.			No. 4.			No. 5.				
		Per pair,	$\frac{1}{8}$ to $\frac{3}{4}$ tube,			$\frac{1}{4}$ to $1\frac{1}{2}$ tube,			1 to $2\frac{1}{2}$ tube,			$1\frac{1}{2}$ to 3 inch,			$2\frac{1}{2}$ to 4 inch,				
			\$3.00			\$4.00			\$5.00			\$9.00			\$12.00				
50	2	Meter and Burner Pliers,																	
		No. 00.	No. 0.	No. 1.	No. 2.	No. 3.	No. 4.	No. 5.											
		$\frac{3}{8}$ to $\frac{1}{2}$ inch tube and burner,	$\frac{1}{4}$ to $\frac{3}{8}$ inch tube and burner,	$\frac{1}{8}$ to $\frac{3}{8}$ inch tube and burner,	$\frac{1}{8}$ to $\frac{1}{2}$ inch tube and burner,	$\frac{1}{8}$ to $\frac{3}{4}$ inch tube and burner,	$\frac{3}{8}$ to 1 inch tube, and burner,	$\frac{1}{8}$ to 1 inch tube and burner,											
		Per pair,	\$0.95	\$1.10	\$2.20	\$2.75	\$3.30	\$3.85	\$4.40										
51	2	Moore's Patent Wrench,	No. 1.			No. 2.			No. 3.			No. 4.							
		8 inch lever, for $\frac{3}{8}, \frac{1}{2}$ , and $\frac{5}{8}$ inch squares, $\frac{5}{8}$ and $\frac{3}{4}$ inch hexagon,				10 inch lever, $\frac{3}{4}$ and $\frac{7}{8}$ inch squares, $\frac{7}{8}$ and 1 inch hexagon,			14 inch lever, 1 and $1\frac{1}{4}$ inch squares, $1\frac{1}{8}$ and $1\frac{3}{8}$ inch hexagon,			16 inch lever, $1\frac{1}{2}$ and $1\frac{3}{4}$ inch squares, $1\frac{1}{2}$ and $1\frac{3}{4}$ inch hexagon,							
		Each,			\$3.00		\$4.00		\$5.00			\$7.00							
52	2	Moore's Patent Drill,	No. 1.			No. 2.			No. 3.			No. 4.							
		8 inch lever,				10 inch lever,			14 inch lever,			16 inch lever,							
		Each,			\$5.00		\$6.50		\$8.00			\$10.00							
53	2	Extra Wrench Gears, for Moore's Patent Wrench,			.50		.60		.75			1.00							

## SCREWING STOCKS FOR CUTTER DIES, (WITH LEADER SCREW AND GUIDES).

1	3	Solid Dies, see price list before given.																		
58	3																			
		Each, complete,																		
		* Sets of Cutters for the above, (each set of 4 cutters),																		
		Guides for same, if wanted separate, each,																		

\* It is best to return the stocks for cutter dies, if a new set of cutters is wanted; but if the stock has a number upon it, (which those lately made have), we can furnish a set of cutters likely to fit, if the grooves are not worn.







CLASS THIRD.—*Continued.*

## SCREWING MACHINE, No. 4.

No. PLATE.

- 76 5 For 1 inch to 6 inch tube, with Countershaft, Universal Gripping Chuck, Universal Steady Rest in Cutting Head, Universal Rest for back of Spindle, Gate for Carrying Screwing Dies, etc., etc., made to use Solid Dies 1 to 2 inch, and Cutter Dies  $2\frac{1}{2}$  to 6 inch. Complete, . . . . . \$1214.00

Countershaft to run 120 revolutions per minute, having 20 inch pulleys for 4 inch belts, giving the following speeds:

Fast Gears,	{	1 inch tube,	40 revolutions per minute.	Slow Gears,	{	2½ and 3 inch tubes,	11½ revolutions per minute.
		1¼ and 1½ inch tubes,	28 " "			3½ and 4½ inch tubes,	8 " "
		2 and 1½ inch tubes,	19½ " "			5 and 6 inch tubes,	5½ " "

Articles belonging to No. 4 Machine, if wanted separate:

See view of machine.	{	Rest Slides for Universal Rest at back of Spindle, per pair, . . . . .	9.22
		Large Steel Gripping Dies for Chuck for $2\frac{1}{2}$ to 6 inch tubes, per pair, . . . . .	
		Small Steel Gripping Dies for Chuck for 1 to 2 inch tubes, per pair, . . . . .	
		Large Steel Rest Dies for Cutting Head for $2\frac{1}{2}$ to 6 inch tubes, per pair, . . . . .	
		Small Steel Rest Dies for Cutting Head for 1 to 2 inch tubes, per pair, . . . . .	

Also, there can be supplied for No. 4 Machine, (as shown in dotted lines for No. 3 Machine, on plate 4,) hand-gearing, extra, . . . 20.00

(With this two men can easily cut and screw 5 and 6 inch tubes, and one man any smaller size).

[We have an arrangement of counter-hanging, with mitre gears, so that No. 3 Screwing Machine can be placed conveniently in the workshop, when the line of shafting will not allow the use of an ordinary countershaft.] Price, extra, . . . . . 32.00

- 77 5 Die Holder for Solid Dies, each, . . . . . 5.45
- 78, 79 5 Solid and Cutter Dies, see price list before given.







CLASS THIRD.—*Continued.*

## BARWICK PATENT WRENCH

AND

## PIPE TONGS

Are adapted to any shaped object, round, square, flat or oval; for instance, in tightening a bolt they will grip either the nut, head or shank. They will twist off a piece of pipe and not alter its diameter.



## THE PACKER RATCHET DRILLS, &c.

The Packer Ratchets sold by us, are forged from the Best Norway Iron, with Steel Pall and Gear, and are the original and genuine Ratchets that have been before the public for so many years, and which have given such entire satisfaction. They have been adopted by the UNITED STATES GOVERNMENT; and are in use in Navy Yards, and on board Steamships; also, in all the principal Machine Shops in the United States and Canadas.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS THIRD.

Plate 1.





1918

1918

NAME	RANK	COMPANY	REGIMENT	BATTALION	COMPANY
JAMES H. HARRIS	CAPTAIN	1ST REGT	1ST REGT	1ST REGT	1ST REGT
JOHN A. SMITH	MAJOR	2ND REGT	2ND REGT	2ND REGT	2ND REGT
WILLIAM B. JONES	LIEUTENANT	3RD REGT	3RD REGT	3RD REGT	3RD REGT
CHARLES E. BROWN	CAPTAIN	4TH REGT	4TH REGT	4TH REGT	4TH REGT
EDWARD G. MILLER	MAJOR	5TH REGT	5TH REGT	5TH REGT	5TH REGT
FRANK L. DAVIS	LIEUTENANT	6TH REGT	6TH REGT	6TH REGT	6TH REGT
ALBERT C. WILSON	CAPTAIN	7TH REGT	7TH REGT	7TH REGT	7TH REGT
HAROLD K. GIBSON	MAJOR	8TH REGT	8TH REGT	8TH REGT	8TH REGT
ROBERT M. HARRIS	LIEUTENANT	9TH REGT	9TH REGT	9TH REGT	9TH REGT
LAWRENCE P. SMITH	CAPTAIN	10TH REGT	10TH REGT	10TH REGT	10TH REGT
GEORGE W. JONES	MAJOR	11TH REGT	11TH REGT	11TH REGT	11TH REGT
JOHN D. BROWN	LIEUTENANT	12TH REGT	12TH REGT	12TH REGT	12TH REGT
WILLIAM E. MILLER	CAPTAIN	13TH REGT	13TH REGT	13TH REGT	13TH REGT
FRANK J. DAVIS	MAJOR	14TH REGT	14TH REGT	14TH REGT	14TH REGT
ALBERT H. WILSON	LIEUTENANT	15TH REGT	15TH REGT	15TH REGT	15TH REGT
HAROLD K. GIBSON	CAPTAIN	16TH REGT	16TH REGT	16TH REGT	16TH REGT
ROBERT M. HARRIS	MAJOR	17TH REGT	17TH REGT	17TH REGT	17TH REGT
LAWRENCE P. SMITH	LIEUTENANT	18TH REGT	18TH REGT	18TH REGT	18TH REGT
GEORGE W. JONES	CAPTAIN	19TH REGT	19TH REGT	19TH REGT	19TH REGT
JOHN D. BROWN	MAJOR	20TH REGT	20TH REGT	20TH REGT	20TH REGT
WILLIAM E. MILLER	LIEUTENANT	21ST REGT	21ST REGT	21ST REGT	21ST REGT
FRANK J. DAVIS	CAPTAIN	22ND REGT	22ND REGT	22ND REGT	22ND REGT
ALBERT H. WILSON	MAJOR	23RD REGT	23RD REGT	23RD REGT	23RD REGT
HAROLD K. GIBSON	LIEUTENANT	24TH REGT	24TH REGT	24TH REGT	24TH REGT
ROBERT M. HARRIS	CAPTAIN	25TH REGT	25TH REGT	25TH REGT	25TH REGT
LAWRENCE P. SMITH	MAJOR	26TH REGT	26TH REGT	26TH REGT	26TH REGT
GEORGE W. JONES	LIEUTENANT	27TH REGT	27TH REGT	27TH REGT	27TH REGT
JOHN D. BROWN	CAPTAIN	28TH REGT	28TH REGT	28TH REGT	28TH REGT
WILLIAM E. MILLER	MAJOR	29TH REGT	29TH REGT	29TH REGT	29TH REGT



# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS THIRD.

Plate 2.










# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION


CLASS THIRD.

Plate 3.


No 58.




No IV & V Screwing Stock.




No 59



No 1 Screwing Machine. —  
1/4 to 1 1/4" tube.



No 60



No 2 Screwing Machine for Power or hand. — 1/4 to 2" tube.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS THIRD.

Plate 4.



No 63.



No. 3 Screwing Machine, for Power or Hand,  $\frac{3}{8}$  to 4 inch Tube.  
(IMPROVED.)



[BLANK PAGE]



CCA



# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE

10<sup>th</sup> EDITION

CLASS THIRD.

Plate 5

No 7.




*Solid Die.*




*Solid Die Holder  
for No 4 Machine.*

No 76.




No 78.




*Die with Cutters  
for No 4 Machine  
2½, 3, 3½ & 4 inch.*

No 79.



*Die with Cutters  
for No 4 Machine  
4½, 5 & 6 inch.*



*No 4 Screwing Machine, 1 inch to 6 inch tube.*



[BLANK PAGE]



CCA



*Persons in ordering will please state the "Edition" they order from.*

## CLASS FOURTH.

Every order for special articles must have accurate plans and dimensions attached, and no order, "*same as before*," will be received. Any article for which no price is quoted on the list will be made only to special order, although such articles may be shown in the illustrations.

## PLUMBER'S MATERIALS.

## CAST IRON DRAIN PIPE AND FITTINGS.

[illegible]

\*Flanges for Hoppers, 40 cents added to the above prices.

30	Round Bottom Drain Trap, top 14×14×12 inches deep; grate 13 inches square, for 3, 4 or 6 inch drain pipe,												\$5	40									
	DIAMETER OF TUBE IN INCHES, . . . . .												$\frac{3}{4}$	1	1 $\frac{1}{4}$	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$					
31	Bell Trap, Nozzle Screwed for Tube Thread, or plain, .												\$0.40	\$0.50	\$0.65	\$0.90	\$1.40	\$2.00					
	DIAMETER IN INCHES, . . . . .												2 in.	3 in.	4 in.	5 in.	6 in.	7 in.	8 in.	10 in.	12 in.		
	Length over all, each piece, . . . . .												5 feet.	5 feet.	5 feet.	5 feet.	6 feet.	6 feet.	6 ft. 2 in.	6 feet.	6 feet.		
32	Conductor Trap, . . . . .														\$7.00								
33	Yard Trap, top 20 $\frac{1}{2}$ ×13 $\frac{1}{2}$ ×13 $\frac{1}{2}$ inches deep; grate 7 inches square, for 3, 4 or 5 inch drain pipe,																				\$10	25	
33	" " 26 $\frac{1}{2}$ ×16 $\frac{1}{2}$ ×16 $\frac{1}{2}$ " " 9 " " 6 or 8 " "																				15	25	
	DIAMETER IN INCHES, . . . . .												2 in.	3 in.	4 in.	5 in.	6 in.	7 in.	8 in.	10 in.	12 in.		
	Length over all, each piece, . . . . .												5 feet.	5 feet.	5 feet.	5 feet.	6 feet.	6 feet.	6 ft. 2 in.	6 feet.	6 feet.		
34	Bell Trap, . . . . .												\$1.40	\$2.00	\$3.00	\$4.60	\$7.00	\$10.40	\$15.00				
PLATE																							
38	2	Tasker's Patent Hydrant and Case, . . . . .																				\$10	00



No. PLATE  
2

	Plain.	Painted.	Galvanized.	Enameled.
	\$ c.	\$ c.	\$ c.	\$ c.
Basin Washstands, with feet, with brass plug and waste, . . . . .	6.50	7.50	9.00	11.25
“ “ “ fitted with one cock and pedestal, plug and waste, complete, . .	8.85	9.85	11.35	14.00
“ “ “ “ two cocks and pedestals, “ “ “ . . . .	11.15	12.15	13.65	16.70
“ “ with pedestal, “ brass plug and waste, and soap dish, . . . . .	8.00	9.00	11.00	13.25
“ “ “ “ one cock and pedestal, plug, waste, and soap dish, complete,	10.35	11.35	13.35	16.00
“ “ “ “ two cocks and pedestals, “ “ “ “	12.70	13.70	15.70	18.75
e “ “ with feet, “ one cock and pedestal, two plugs and wastes, complete, .	19.35	21.35	24.35	35.45
“ “ “ “ two cocks and pedestals, “ “ “	21.70	23.70	26.70	38.40
“ “ “ “ four “ “ “ “	26.40	28.40	31.40	44.30
“ “ “ “ two brass plugs and wastes, . . . . .	17.00	19.00	22.00	32.50

		No. 1.				No. 2.				No. 3.			
		Long.	Wide.	Deep.	High over all.	Long.	Wide.	Deep.	High over all.	Long.	Wide.	Deep.	High over all.
42	Painted, Hidden Overflow and Plug, . . . . }	5 ft. 9½ in.	2 ft. 4 in.	1 ft. 7¼ in.	2 ft. 0 in.	2 ft. 8 in.	2 ft. 2 in.	1 ft. 6¾ in.	1 ft. 11 in.	5 ft. 4½ in.	2 ft. 0 in.	1 ft. 4⅞ in.	1 ft. 9½ in.
		\$23.00				\$22.00				\$21.00			
42	Painted, with two angle valves, and Waste and Overflow Valve, and Strainer, for Hospital use, }												
		\$35.50				\$24.50				\$33.50			
43	Plain Castings, Hidden Overflow and Plug, . . . }												
		\$21.60				\$20.70				\$19.80			
44	Round Tank, diameter 2 feet 9½ inches by 1 foot 10 inches deep,												
45	*Oblong Tank or Bosh, dimensions over all, 3 feet 5½ inches long by 1 foot 5¾ inches wide by 1 foot 7 inches deep, . . . .												\$12.50
46	Large Oval Tank, dimensions over all, 4 feet 11¾ inches long by 2 feet 2¼ inches wide by 2 feet 0¼ inch deep, . . . .												40.00
	With outlets for flange connections, these can be used for Green-House Hot Water Cisterns.												42.00
	*This can be made any length shorter than here given, to order.												

Showing how to use Drain Pipes, the Fittings in Buildings.

47	Pavement Pipe; diameter 4 in. $\times$ 2 ft. 9 in. long; top, 5 in. square,		
48	Stop Cock Box, ornamental water or gas lid, 9½ inches square,		\$2 00
49	“ “ plain, “ “ 6 “ “		1 25
50	Gas Cock Box, 5 inches square,		40
			30

## 51

Weight.	Dimensions.	Capacity.	Price, Plain.	Price, Galvanized.	Price, Vulcanized Rub'r-Coat'd.
lbs.	Gals.	\$ c.	\$ c.	\$ c.	\$ c.
110	4' x 12"	23.5	15.75	19.95	18.45
131	4' x 14"	32.	19.95	26.25	23.80
144	4' x 16"	42.	24.15	32.60	30.50
171	4' x 18"	53.	28.50	36.00	33.50
178	4' x 20"	65.	33.75	42.00	39.70

Weight.	Dimensions.	Capacity.	Price, Plain.	Price, Galvanized.	Price, Vulcanized Rub'r-Coat'd.
lbs.	Gals.	\$ c.	\$ c.	\$ c.	\$ c.
259	4' x 24"	94.	48.90	60.00	57.55
126	5' x 12"	29.4	18.00	24.15	22.60
139	5' x 14"	40.	23.10	30.45	28.45
176	5' x 16"	52.	27.00	35.00	33.00
193	5' x 18"	66.	31.50	40.75	36.75

Weight.	Dimensions.	Capacity.	Price, Plain.	Price, Galvanized.	Price, Vulcanized Rub'r-Coat'd.
lbs.	Gals.	\$ c.	\$ c.	\$ c.	\$ c.
241	5' x 20"	82.	39.00	52.00	49.75
305	5' x 24"	118.	52.00	70.00	67.25
148	6' x 12"	35.3	24.10	31.00	29.50
156	6' x 14"	48.	30.50	37.10	35.35
191	6' x 16"	63.	30.50	43.50	41.60

Weight.	Dimensions.	Capacity.	Price, Plain.	Price, Galvanized.	Price, Vulcanized Rub'r-Coat'd.
lbs.	Gals.	\$ c.	\$ c.	\$ c.	\$ c.
232	6' x 18"	79.	38.00	51.00	49.00
279	6' x 20"	98.	48.00	61.50	59.00
338	6' x 24"	141.	60.50	78.50	75.00
318	7' x 20"	113.	50.25	68.00	65.00
425	8' x 24"	188.	83.50	105.00	102.00

BATH BOILERS OF LARGER OR SMALLER SIZES MADE TO ORDER.


For Back Log Boilers,  $\frac{3}{4}$ " lead pipe connections, consisting of two boiler ferrules, and a piece of  $\frac{3}{4}$ " galvanized tube 6 inches shorter than the boiler, \$2.00  
For Circulating Boilers,  $\frac{3}{4}$ " lead pipe connections, two goose-neck unions, and two straight boiler unions, and a piece of  $\frac{3}{4}$ " galvanized tube 6 inches shorter than the boiler, 3.00  
To guard against the possibility of accidents our Boilers are made of the best charcoal iron. They weigh more than any other Boilers in the market, and are all proved by a cold water pressure of 80 lbs. per square inch.








## CLASS FOURTH.—Continued.

No.	PLATE.				Plain.	Painted.	Galvanized.	Enameled.
78	4	Corner Slop Sink, or Manger Box,		$16\frac{1}{2}$ inches radius, $\times$ 8 in. deep,	\$2.80	\$3.30	\$4.45	\$10.80
				$16\frac{1}{4}$ " " $10\frac{1}{4}$ " . . . . .	3.10	3.60	5.00	11.10
				17 " " $12\frac{1}{4}$ " . . . . .	3.40	3.90	5.65	11.40
				$21\frac{1}{2}$ " " $8\frac{1}{2}$ " . . . . .	3.10	3.60	5.00	11.10

SINKS.	Dimensions.	Without traps, Plain outlet, or none, if or- dered, Plain Castings.	With Trap and Collar for lead pipe, or tapped with Galvanized Tube.		
			Plain Castings.	Galvanized.	Enameled.
79	Square corner Sinks.		\$ c.	\$ c.	\$ c.
	Inches—23¾ long, 15½ wide, 5 deep,	2.20	2.80	3.65	7.00
	" 29¾ " 17½ " 5¾ " " " " " " " "	3.15	3.75	5.20	10.25
	" 31¾ " 20¼ " 5¾ " " " " " " " "	4.70	5.45	7.30	13.00
	" 37 " 20¼ " 5¾ " " " " " " " "	5.00	5.75	7.75	14.00
	" 56¾ " 24 " 6 " " " " " " " " "	11.10	11.85	17.75	21.60
	" 46¼ " 19¼ " 4¾ " " " " " " " " "	8.00	8.75	12.45	21.50
	" 72 " 22¼ " 6 " (for tube legs.) " " " " " " " "	22.00	22.75	34.50	. .
80	Round corner Sinks, two round corners, corners 6 inches ra- dius, flange ¾ inch wide.		\$ c.	\$ c.	\$ c.
	" 23½ " 17½ " 5¼ " " " " " " " " "	3.30	3.90	5.25	8.10

No.		Plain.	Painted.	Galvanized.	Enameled.
81	Basin Sink, with brass plug and waste,	\$4.75	\$5.35	\$6.15	\$9.10
82	Double Basin Sink, with two brass plugs and wastes,	13.25	14.50	18.25	20.00

SINKS.	Dimensions.	Without traps, Plain outlet, or none, if or- dered, Plain Castings.	With Trap and Collar for lead pipe, or tapped with Galvanized Tube.		
			Plain Castings.	Galvanized.	Enameled.
83	Round corner Sinks, two round corners, corners 6 inches ra- dius, flange ¾ inch wide.		\$ c.	\$ c.	\$ c.
	Inches—26 long, 17½ wide, 5¼ deep, (corners 2 in. radius.)	3.50	4.10	5.50	9.80
	" 28¼ " 19½ " 5¼ " " " " " " " " "	3.90	4.65	6.20	11.40
	" 33¼ " 21½ " 5½ " " " " " " " " "	4.90	5.65	7.60	15.40
	" 35¼ " 21½ " 7¼ " " " " " " " " "	5.90	6.65	9.50	17.90
	" 41½ " 21 " 5½ " " " " " " " " "	8.00	8.75	12.00	18.50
	" 43 " 21½ " 5¾ " " " " " " " " "	5.10	5.85	7.90	15.60
	" 22¾ " 18 " 4 " (flange ½ in.) " " " " " " " "	2.00	2.75	3.50	7.25
	" 24½ " 17½ " 3¾ " ( " 1½ in.) " " " " " " " "	2.90	3.50	4.65	9.25
	" 52 " 26 " 7 " (corner 8 in. radius, flange ¾ in.)	17.25	18.00	27.20	32.25
	" 85 " 30¼ " 10¼ " " 4 in. " " " " " "	36.60	37.35	56.85	. .
	Same, square cornered top.				

		Plain.	Painted.	Galvanized.	Enameled.
84	Oval Wash Basin, 13 inches $\times$ 10 $\frac{1}{2}$ in. $\times$ 4 $\frac{1}{2}$ in. deep inside, 1 $\frac{1}{2}$ inch flange, with plug and chain, .	\$1.75	\$2.05	. .	\$3.55
85	Round Wash Basin, back overflow, 12 inches diameter, $\times$ 5 inches deep inside, $\frac{3}{4}$ inch flange, .	1.75	2.05	. .	3.40
85	" " " 14 inches diameter, 6 inches deep, $\frac{3}{4}$ inch flange, . . .	2.50	2.80	. .	4.30
86	Square Slop Sink, or {  } 19 $\frac{1}{2}$ $\times$ 19 $\frac{1}{2}$ $\times$ 10 $\frac{1}{2}$ inches, . . . . .	3.75	4.25	\$6.45	11.75
	Manger Box, slop- front, . . . . .				
	Bell Trap, attached to Slop Sink, for 1 inch lead pipe connections, extra, . . . . .	.65	.75	.90	1.25

87 Round corner Sink, with overflow, extra price.

88	Military Hospital Water Closets, 16 in. wide by 16 in. deep, 6 ft. 7 ft. 8 ft. 9 ft. 10 ft. 12 ft. long, (all inside dimensions, flange 1½ in. wide.)	\$21.80	\$25.00	\$28.00	\$31.25	\$34.35	\$40.60
	Price,						
	Add for Overflow Plug, Lever, and Drain Pipe, either straight or bend, (1 foot 9 inches long,) " " " " " "						\$7 50
	Add for Clapper Valve and Drain Pipe, either straight or bend, " " " " " "						5 60



CLASS FOURTH.—*Continued.*

## VIEWS OF WATER CLOSET ARRANGEMENTS.

Showing how to use Drain Pipes, the Fittings in Buildings.

No. PLATE.

6

90	Side-walk Gutter, half octagon, cover loose, diamond; whole lengths, 8 feet and 6 feet; price per foot, . . . . .	\$1 20
91	Branch for No. 90; price each, . . . . .	1 50
92	Bend for No. 90; " . . . . .	1 20
93	Side-walk Gutters, London pattern, cover attached, diamond, with cleaning slit; whole length, 6 feet each, price per foot, . . . . .	1 25
94	Branch for No. 93; price each, . . . . .	1 50
95	Bend for No. 93; " . . . . .	1 25
96	Side-walk Gutter, half round pattern, cover loose, reeded; whole lengths, 6 feet each; price per foot, . . . . .	1 00
97	Branch for No. 96; price each, . . . . .	1 20
98	Bend for No. 96; " . . . . .	75
99	Side-walk Gutter, square, cover loose, fluted; whole lengths, 6 feet; price per foot, . . . . .	1 00
100	Return End for No. 99: price each, . . . . .	2 50
101	Bend for No. 99; " . . . . .	80
102	Branch for No. 99; " . . . . .	1 25
103	Eaves Gutter, half round, 7 inches diameter, (spout outlets put on as ordered, price extra,) laying length 5 feet; price per foot, . . . . .	1 00
103	" " 10 " " " " " " " " 5 " " . . . . .	1 75
104	Hip Corner for No. 103; price each, . . . . .	2 50
105	Corner for 103; price each, . . . . .	2 50
108	Vault Ring and Cover, (oval,) 2 ft. 6 in. $\times$ 1 ft. 9 in., . . . . .	
109	Sewer Inlet, plate, 5 ft. 8 in. long $\times$ 2 ft. 8 in. wide, . . . . .	
110	Vault Frame and Cover, (square or oblong,) to order, . . . . .	

DIAMETER OF COVER OR GRATE, . . . . .		1 ft. 1 in.	1 ft. 5 in.	1 ft. 6 in.	1 ft. 8 in.
		\$ c.	\$ c.	\$ c.	\$ c.
111	Vault Rings, (circular), . . . . .	1.00	1.25	2.00	2.50
111	Vault Covers, . . . . .	1.25	1.75	2.25	2.90
111	Vault Grates, . . . . .	1.50	1.75	2.40	3.30

113	Box Scraper, . . . . .	\$0 90
114	Scraper, . . . . .	45
115	Scraper, . . . . .	70

INTERNAL DIAMETER, . . . . .		3 inches.	3½ inches.	4 inches.	4½ inches.
116	Spout Case with offsets, with or without nozzle, as ordered; price each, . . . . .	..	..	..	..
117	" " nozzle, 6 feet length; price each, . . . . .	\$4.50	\$5.25	\$6.25	\$7.25
118	" " " 3 feet 6 inches lengths; price each, . . . . .	2.75	3.25	3.80	4.35



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FOURTH.

Plate 1.





[BLANK PAGE]



CCA





# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS FOURTH.


Plate 2.




Wash stand with feet.




Wash stand with Pedestal.



Double Basin Wash stand with feet.




Bath Tub with supply & waste Valves and overflow combined. (generally for Hospitals)




Bath Tub with secret Overflow.






Round Tank.



Oblong Tank or Bosh.




Large Oval Tank.



Bath Boilers.




Patent Hydrant.



Stop Cock Box, plain or Gas Lid.




Stop Cock Box, plain or Gas Lid.




Stop Cock Box, plain or Gas Lid.

Pavement Pipe, plain or Gas Lid.




Circulating Hot Water Boiler.



Tubular Stand for upright Bath Boilers.



Water Back.



Water Back of Range.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FOURTH.


Plate 3.

No 56.




Single Soil Branch.

No 57.




Double Soil Branch.

No 58.



Slop Hopper with Lid.

No 59.




Oval Hopper.

No 60.



Oval Hopper with wooden Rim.

No 61.



Corner Urinal.

No 63.



Circular Hopper with flange.

No 64.




No 68.




Drain Grate.

No 65.




Stable Trap.  
(Box Pattern.)

No 66.



Stable Trap.  
(Deep Pattern.)


No 67.




Stable Trap.  
(Shallow Pattern.)

No 71.

Heavy Single Soil Branch for Hospitals



No 69.




Water Closet Spring Valve,  
generally for  
Hospitals.


Chain Pulleys for  
No 69.



Heavy Double  
Soil Branch.  
for Hospitals.



No 72.



Heavy Belly Trap,  
with or without Hand hole








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


70<sup>th</sup> EDITION

CLASS FOURTH.


Plate 4.



No 75  
Evaporators.  
No 77.




No 76.  
Corner Sink, to fit Post or Pipe  
(Manger Box.)  
No 78.




Round corner Sink.



Corner Slop Sink.  
(Manger Box.)




No 79



Square corner Sink




No 80




Round corner Sink



No 81.  
Basin Sink.




No 83



No 82.  
Double Basin Sink.



Round corner Sink with square corner top  
No 86.




Section through Plug  
of No 88.




No 84.



No 85.




Square Slop Sink.  
(Manger Box.)  
No 88.



No 87.

Sink with Overflow.

Oval Wash Basin. Round Wash Basin,  
back overflow.



Military Hospital Water Closet.



[BLANK PAGE]




CCA




## WATER CLOSET ARRANGEMENTS.


FIRST.




SECOND.




THIRD.



FOURTH.



FIFTH.



Outline Section.

Front View.

The supply of water to hoppers can be made by spring Valve No. 69 attached to door.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FOURTH.

Plate 6.





[BLANK PAGE]



CCA



Persons in ordering will please state the "Edition" they order from.

## CLASS FIFTH.

Every order for special articles must have accurate plans and dimensions attached, and no order, "same as before," will be received.

Any article for which no price is quoted on the list will be made only to special order, although such article may be shown in the illustrations.

The lists of Prices refer to Flange Pipe and Fittings only of the given dimensions. Any change in diameter of flanges, or in length from face to face, or end to end, must be made by special order; and it is to be noted, that the cost of such changes is often quite disproportionate to the price of the standard articles.

### CAST IRON GAS OR WATER MAIN, (BELL JOINTS.)

All Proved under Hydraulic Pressure, 300 lbs. per Square Inch.

Inside Diameter.	Lengths.	Weight per Length.	Extra Lengths.	Weight Extra Lengths.	Price per Foot.
12 inches.	9 feet.	640 lbs.	12 feet 4.24 inches.	863 lbs.	Depends on the Iron Market.
10 "	9 "	487 "	12 " 4.08 "	656 "	
8 "	9 "	355 "	12 " 3.92 "	476 "	
6 "	9 "	241 "	12 " 3.76 "	322 "	
4 "	9 "	145 "	. . . . .	. . . . .	
3 "	9 "	104 "	. . . . .	. . . . .	
2½ "	8 "	65 "	. . . . .	. . . . .	
2 "	6 "	40 "	. . . . .	. . . . .	
1½ "	6 "	30 "	. . . . .	. . . . .	

INCHES.	(Old Pattern) 1½	2	(Old Pattern) 2½	3	4	6	8	10	12	Prices depend upon the Iron Market.
	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	lbs.	
Equal or Reducing Crosses X. Weight each,	14	35	43	60	95	190	355	520	710	
Equal or Reducing Tees T. " "	10	25	39	45	75	150	240	355	485	
Double Bell, . . . . . " "	6	15	23	30	55	120	195	275	355	
Elbows L. . . . . " "										
Bevil Hub, (Eighth Bend,) . . . . .										
Reducing Pipes, Bell large or small end, as ordered, . . . . .										
Offset Pipe, . . . . .										
Y Branch, . . . . .										
Cap or Plug, . . . . .										
Sleeve, . . . . .										

### CAST IRON PIPE WITH FACED FLANGES.

Finished with Bolts and Nuts, suitable for Steam Work, proved to 300 pounds per square inch Pressure, and intended for 75 pounds per square inch Working Pressure.

Internal Diameter of Pipes.	Thickness of Iron of Body.	Outside Diameter of Flanges.	Diameter of Centre of Holes for Bolts.	Number of Bolts.	Diameter of Bolts.	Length of each piece of Pipe.	Price per foot, for whole lengths, with Bolts, finished.	Price of L's with Bolts, finished.	Price of T's with Bolts, finished.	Price of X's with Bolts, finished.
3 inches.	.328 inches.	7½ inches.	6 inches.	4	½ inch.	8 feet.				
3½ "	.341 "	8 "	6½ "	4	⅞ "	8 "				
4 "	.354 "	9 "	7¼ "	*5	⅞ "	8 "				
5 "	.380 "	10 "	8⅜ "	6	⅞ "	8 "				
6 "	.406 "	11 "	9⅜ "	6	⅞ "	9 "				
8 "	.458 "	13½ "	11¾ "	8	⅞ "	9 "				
10 "	.510 "	16 "	14 "	10	¾ "	9 "				
12 "	.527 "	19 "	16¾ "	10	¾ "	9 "				
16 "	.667 "	23½ "	21 "	14	¾ "	9 "				

\* The 4 inch Pipe Flanges can have 4 ⅝ Bolts in place of the tabular number; but the joint will be better if the number and dimensions given are followed.

Pipes of special lengths, or with special outlets, Elbows, T's, X's or Flanges, to dimensions, made to order.



CLASS FIFTH.—Continued.

No. PLATE

12 1

13

14

15

HEAVY CAST IRON PIPE WITH FACED FLANGES.

Finished with Bolts and Nuts, suitable for Steam Work; proved to 300 pounds per square inch Pressure, and intended for 100 pounds per square inch Working Pressure.

Internal Diameter of Pipe.	Thickness of Iron of Body.	Outside Diameter of Flanges.	Diameter of Centre of Holes for Bolts.	Number of Bolts.	Diameter of Bolts.	Length of each piece of Pipe.	Price per foot, for whole lengths, with Bolts, finished.	Price of L's with Bolts, finished.	Price of T's with Bolts, finished.	Price of X's with Bolts, finished.
3 inches.	.383 inches.	7½ inches.	6 inches.	4	9/16 inch.	8 feet.	\$1.00	Same Patterns and Prices as for 75 lbs. Pressure.	Same Patterns and Prices as for 75 lbs. Pressure.	Same Patterns and Prices as for 75 lbs. Pressure.
3½ "	.393 "	8 "	6½ "	*5	9/16 "	8 "	1.20			
4 "	.414 "	9 "	7½ "	*5	9/16 "	8 "	1.40			
5 "	.444 "	10 "	8½ "	6	9/16 "	8 "	1.80			
6 "	.474 "	11 "	9½ "	6	9/16 "	9 "	2.15			
8 "	.535 "	13½ "	11½ "	8	9/16 "	9 "	3.20			
10 "	.596 "	16 "	14 "	10	9/16 "	9 "	4.40			
12 "	.657 "	19 "	16½ "	10	9/16 "	9 "	5.90			
16 "	.778 "	23½ "	21 "	14	7/8 "	9 "	9.00			

\* The 3½ Pipe Flange can have 4 5/8 Bolts, and the 4 inch Pipe Flange 4 3/4 Bolts; but the joint is not likely to be so good as when the tabular number and dimensions are used.

Pipes of special lengths, or with special outlets, Elbows, T's, X's or Flanges, to dimensions, made to order.

PLATE

2 TABLE OF DIMENSIONS OF FLANGED AND BELL ELBOWS, TEES AND CROSSES.

PLATE

3

STOP VALVES, DOUBLE WEDGE VALVES, INSIDE OR OUTSIDE SCREWS, BELL OR FLANGED ENDS.

(Large Sizes, Geared, as shown in plate 24, if ordered, price extra,) suited for 75 pounds Working Pressure.

Internal Diameter of Valve.	All Iron.		Brass Faces to Valves and Brass Nuts.		All Bearings or Screw Surfaces of Brass.		Dimensions.		
	Inside Screws.	Outside Screws.	Inside Screws.	Outside Screws.	Inside Screws.	Outside Screws.	Face to Face of Flanges.	Diameter of Flanges.	End to end of Pipes, when laid in bell of Valves.
3 inches.	\$16.25	\$18.00	\$17.00	\$19.00	\$18.00	\$20.00	Inches.	Inches.	Inches.
4 "	20.00	22.00	21.00	23.00	22.50	24.75	13½	7½	6¾
6 "	29.75	33.00	31.50	35.00	34.00	37.50	14¾	9	7
8 "	43.00	47.50	46.00	50.50	50.00	55.00	15¾	11	8
10 "	62.00	69.00	66.00	73.00	72.00	80.00	17¾	13½	9¾
12 "	86.00	95.00	91.00	100.00	100.00	110.00	19	16	10½
16 "	148.50	144.00	155.50	171.00	170.00	187.00	20½	19	12
20 "	222.00	244.00	231.00	254.00	250.00	275.00	24½	23½	15¾
							27	28½	16¾



## CLASS FIFTH.—Continued.

## FIRE PLUGS AND CASES.



The nozzle on both 3 and 4 inch are the same, both having inside screw (with cast iron cap) suited for standard 9 inch hose. If other nozzles are wanted, they will be made to special order.

The ordinary length of Fire Plugs is for four feet from level of centre of roadway to that of centre of main, but they are made to order for any depth of line that may be required.

They are furnished complete, with hose nozzle and caps, and internal waste.

	3 inch (No. 28.)	4 inch (No. 28.)	4 inch subway (No. 30.)
Fire Plugs, . . . . .	\$18.00	\$28.00	\$28.00
Add for each foot of increased length, . . . . .	1.00	1.50	1.50

	3 inch (No. 26.)	4 inch (No. 25.)	4 inch subway (No. 27.)
Cases for Fire Plugs, . . . . .	\$10.00	\$15.00	\$10.00

Fire Hydrant Valve, for Factories, Railroad Depots, &c., with Nut or Wheel Valve 2½ inches, . . . . . \$9.00

Iron Foot Valve, 2 in., \$7.20; 2½ in., \$9.60; 3 in., \$12.50; 3½ in., \$14.95; 4 in., \$17.75; 5 in., \$24.00; 6 in., \$30.65. See CLASS SECOND.

Strainers, Galvanized Bossed Flange; diameter of Tube and of Flange as ordered. See CLASS FIRST.

Strainers, Galvanized iron, 3 inches, 4 inches, 5 inches, 6 inches, 8 inches. See CLASS SECOND.

Expansion Joints, 3 inches, 4 inches, 5 inches, 6 inches, 8 inches. See CLASS SECOND.

Water Tank Valve, with Strainer, 4 inches only. See CLASS SECOND.

## GAS STOP VALVES, DOUBLE FACE, INSIDE SCREW, ALL IRON, BELL OR FLANGED ENDS.

Internal Diameter of Valve.	PRICE.	DIMENSIONS.		
		Face to Face of Flanges.	Diameter of Flanges.	End to end of Pipes when laid in bell of Valves.
		Inches.	Inches.	Inches.
3 inches, . . . . .	\$15.00	8	7½	5
4 " . . . . .	22.00	9	9	5½
6 " . . . . .	33.00	10	11	6½
8 " . . . . .	47.00	12	13½	8
10 " . . . . .	59.00	14	16	9
12 " . . . . .	74.00	16	19	10
16 " . . . . .	114.00	18	23½	12
20 " . . . . .	193.00	20	28½	14½
24 " . . . . .	....	22	33	18
30 " . . . . .	....	..	..	..

Hinge Valve, bell end, same price as Double Wedge Valve, all iron.

" flange end, " " "

## RAILROAD STATION WATER COLUMNS.

Price of 6 inch Swing Joint, without ornaments or arm, . . . . .	\$45 00
" 6 inch Station Plug, ready for connections, . . . . .	75 00
" Column, with Bed-plate; holding-down bolts and washers; Connecting Pipes; Swing Joint, with galvanized iron pipe arm 9 feet long; Station Plug; complete, ready to set up as drawn, . . . . .	475 00

The foundation needs about 14 yards excavation and 4 M of brickwork.



THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.

THE UNIVERSITY OF CHICAGO PRESS

CHICAGO, ILLINOIS, U.S.A.




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION



CLASS FIFTH.

Plate 1.



*No. 1. Cast iron Water or Gas Pipe. Bell Joints.*



*No. 2.*




*No. 3.*



*Crosses*


*Tees.*

*No. 4.*




*Double Bell.*

*No. 5.*



*Elbow.*

*No. 6.*




*Bevel hub.*

*No. 10.*




*Cap or Plug.*




*No. 7. Reducing Pipes.*

*No. 8.*



*Offset Pipe.*

*No. 9.*




*Branch.*

*No. 11 Sleeve.*



*No. 12.*




*Cast iron Steam or Water Pipe, Flange Joints.*

*No. 13.*



*Elbow.*

*No. 14.*




*Tees.*



*No. 15.*



*Crosses.*



*Pipes with special Outlets to order.*



*Blank Flange.*



*Elbows, special lengths to order.*



[BLANK PAGE]



CCA



















































































































































# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS FIFTH.

Plate 2.

## DIMENSIONS of FLANGED ELBOWS, TEES & CROSSES, center to face of Flange

diameter of Flanges	6 inches	7 inches	7½ inches	8 inches	9 inches	10 inches	11 inches	13½ inches	16 inches	19 inches	23½ inches	28½ inches
" of center of bolts	4¾ "	5½ "	6 "	6½ "	7½ "	8½ "	9½ "	11¾ "	14 "	16¾ "	21 "	25¾ "
Number " bolts	4	4	4	5	5	6	6	8	10	10	14	16
Size " "	½ "	½ "	9/16 "	9/16 "	5/8 "	5/8 "	5/8 "	5/8 "	¾ "	7/8 "	7/8 "	1 inch
	2	2½	3	3½	4	5	6	8	10	12	16	20
2												
2½												
3												
3½												
4												
5												
6												
8												
10												
12												
16												
20												
	2	2½	3	3½	4	5	6	8	10	12	16	20

## DIMENSIONS of BELL JOINT ELBOWS, TEES & CROSSES

the above dimensions give the Length from center to bottom of bell or end of spiggots



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS FIFTH.


Plate 3.




No. 20.



No. 21.




No. 22.



No. 23.


Stop Valves, outside Screw.  
Flange ends. Bell ends.

Stop Valves, inside Screw.  
Flange ends. Bell ends.




No. 24.

Stop Valve with Gearing.  
(20 inch & upward.)




No. 25.

4 inch Fire Plug Case.




No. 28.

Sect. of Stop Valve,  
Outside Screw,  
Bell ends.




Upper Part of 3 inch  
Sub-way  
Fire Plug.




No. 31.

4 inch Fire Plug.




No. 29.

Upper part of  
3 in. Fire Plug.




No. 32.

Hydrant  
Valve.



Sect. of  
3 & 4 inch Fire Plug

4 & 5 feet from Centre of main to  
level of Center of Street,  
as ordered.




No. 30.

4 inch Sub-way  
Fire Plug.



No. 26.


3 inch Fire Plug Case.



No. 27.

Case for No. 30.








N<sup>o</sup> 34.



Iron Foot Valve  
(Flange.)  
See Class II.

N<sup>o</sup> 35.



Strainer.  
See Class II.


N<sup>o</sup> 36




Expansion Joint, cast iron  
with Brass Sleeve,  
flange ends.  
See Class II.

N<sup>o</sup> 42.  
Station Water Column.


Length as ordered.



N<sup>o</sup> 37.




Water Tank Valve with Strainer.  
(see Class II.)




Section of  
Double Face Valve.

N<sup>o</sup> 38.




Double Face Valve,  
(for Gas) flange ends.

N<sup>o</sup> 39




Double Face Valve  
(for Gas) bell ends.

N<sup>o</sup> 40.




Hinge Valve, bell ends,  
leather faced Valve.

N<sup>o</sup> 41.



Hinge Valve, flange ends,  
leather faced Valve.

N<sup>o</sup> 43



N<sup>o</sup> 43 Station Plug, outside screw.











CLASS SIXTH.—*Continued.*

No. PLATE.

20 3

## WOODWARD'S STEAM PUMP.

No.	Diameter of steam Cylinder in inches.	Diameter of water Cylinder in inches.	Suction. in.	Steam. in.	Discharge. in.	Exhaust. in.	Gallons discharged per minute.	PRICE.
0	2½	1¾	¾	¾	¾	¾	3 to 5	\$125.00
1	4	2	1	¾	½	1	8 to 12	200.00
2	5	2½	1½	¾	1	1	26 to 39	275.00
3	7	3½	2	1	1½	2	52 to 78	375.00
4	9	5	2½	1½	2	2	85 to 120	550.00
5	12	7	3	1½	2½	2½	167 to 240	650.00
6	14	8	4	2	3½	3	225 to 300	850.00
7	16	9	5	2	4	3	414 to 518	1200.00
8	18	12	6	2	5	3	726 to 900	1400.00
9	20	14	7	3	5	5	900 to 1200	2000.00
10	22	16	· ·	· ·	· ·	· ·	1500 to 1800	· · · ·
11	24	18	· ·	· ·	· ·	· ·	1700 to 2000	· · · ·
12	26	20	· ·	· ·	· ·	· ·	2000 to 2500	· · · ·
13	30	20	8	4	8	5	2500 to 2800	4000.00

N. B.—The pulley fly-wheel on this Engine can be used for driving other machinery.

21 }  
22 } 3

## WORTHINGTON STEAM PUMPS.

Numbers Designating Sizes.			Diameter of Steam Cylinder in inches.	Diameter of Water Plunger in inches.	Length of Stroke in inches.	No. of Strokes per minute varying with kind of work and pressure.	Displacement in gallons per single stroke.	PRICE.
No. 1,	·	·	3¾	2¼	3	80 to 175	54 1000	\$ 80.00
" 2,	·	·	5	3	6	80 to 150	19 100	150.00
" 3,	·	·	6½	4½	9	80 to 150	64 100	250.00
" 4,	·	·	9	6	9	80 to 150	110 100	400.00
1st pattern " 5,	·	·	12	7	9	80 to 150	158 100	500.00
2d " " 5,	·	·	16	7	9	80 to 150	156 100	550.00
1st " " 6,	·	·	12	10¼	9	75 to 125	336 100	625.00
2d " " 6,	·	·	16	10¼	9	75 to 125	336 100	700.00
3d " " 6,	·	·	18½	10¼	9	75 to 125	336 100	775.00
1st " " 7,	·	·	12	14	9	70 to 120	627 100	750.00
2d " " 7,	·	·	16	14	9	70 to 120	627 100	825.00
3d " " 7,	·	·	18½	14	9	70 to 120	627 100	900.00

N. B.—In case of fire or other emergency, the speed of the pump may be considerably increased beyond the figures stated above.

23 3

## WORTHINGTON'S DUPLEX STEAM PUMPS.

			Diameter of Steam Cylinder in inches.	Diameter of Water Plungers in inches.	Length of Stroke in inches.	No. of Strokes per minute varying with kind of work and pressure.	Displacement in gallons per stroke.	PRICE.
			4½	2¾	4	100 to 150	22 100	\$225.00
			6	4	6	80 to 125	68 100	400.00
			7½	4½	10	80 to 125	144 100	700.00
			10	6	10	75 to 125	255 100	800.00
			12	7	10	75 to 125	348 100	900.00
			14	7	10	75 to 125	348 100	1000.00
			14	10¼	10	75 to 125	746 100	1300.00
			16	10¼	10	75 to 125	746 100	1400.00
			18½	10¼	10	75 to 125	746 100	1500.00
			14	14	10	75 to 125	14	1600.00
			18½	14	10	75 to 125	14	1750.00
			14	15	15	75 to 125	224 100	2250.00

N. B.—In case of fire or other emergency, the speed of the pump may be considerably increased beyond the figures stated above.



## CLASS SIXTH—Continued.

No. PLATE.

24 3

## CLARK'S PATENT STEAM AND FIRE REGULATOR.

Size.			High Pressure.	Low Pressure.	Size.			High Pressure.	Low Pressure.
No. 1. Under 5 horse power, . . .			\$25.00		No. 3. For 120 horse power, . . .			\$100.00	\$115.00
No. 2. For 10 horse power, . . .			40.00		" " 140 " " . . .			105.00	120.00
" " 15 " " . . .			45.00		" " 160 " " . . .			110.00	125.00
" " 20 " " . . .			50.00		" " 180 " " . . .			115.00	130.00
No. 3. " 30 " " . . .			60.00	\$75.00	" " 200 " " . . .			120.00	135.00
" " 40 " " . . .			65.00	80.00	" " 250 " " . . .			125.00	140.00
" " 50 " " . . .			70.00	85.00	" " 300 " " . . .			130.00	145.00
" " 60 " " . . .			75.00	90.00	" " 350 " " . . .			135.00	150.00
" " 70 " " . . .			80.00	95.00	" " 400 " " . . .			140.00	155.00
" " 80 " " . . .			85.00	100.00	" " 450 " " . . .			145.00	160.00
" " 90 " " . . .			90.00	105.00	" " 500 " " . . .			150.00	165.00
" " 100 " " . . .			95.00	110.00					

In estimating the Horse Power of Boilers,  
 10 square feet of heating surface for plain Cylinder Boilers,  
 12 " " " " (fire and flue) " "  
 16 " " " " (fire and tubes) Tubular Boilers,

As considered equal  
 to one horse power.

## VENTILATING FANS FOR HOSPITALS AND PUBLIC BUILDINGS.

Diameter.	Usual number of revolutions per minute.	Unresisted discharge, cubic feet of air per minute.	Discharge with proper Ducts (approximate) cubic feet of air per minute.	Area of Air Duct,* square feet.	Price, Boxed, ready for shipment, at Philadelphia, including pair of Pedestals, Pulley, and usual length of Shaft. Disc and Rim not turned or painted.
14 feet Single, . . .	70@125	110,000@200,000	55,000@100,000	62	\$750.00
12 " " . . .	80@150	77,000@145,000	39,000@ 72,000	46	550.00
10 " " . . .	100@175	56,000@ 98,000	28,000@ 49,000	32	425.00
8 " " . . .	125@220	35,000@ 58,000	17,000@ 29,000	20½	300.00
6 " " . . .	160@300	19,500@ 36,000	10,000@ 18,000	11½	250.00
5 " " . . .	200@350	14,000@ 24,000	7,000@ 12,000	8	200.00
6 " Double, . . .	160@300	39,000@ 72,000	20,000@ 36,000	23	500.00

\* The area of Air Duct given is the least suitable dimension near the Fan, or two-thirds that of distributing Flues or outlets. Ducts of considerable length, or outlets at a distance from the Fan, should have greater area.

## BLOWING FAN FOR BOILERS, MILL FURNACES, &amp;c.

Diameter of Blades.	Revolutions per Minute, (usual number.)	Quantity of Coal per 24 hours for which they will supply air, (approximate,) resistance of Ducts being taken at 2 inches water pressure.	Price.
6 feet.	500 to 800	70 to 120 gross tons.	\$900.00

## UPRIGHT TUBULAR BOILERS.

Size.			Proportions of Boilers.								Price.
Diameter of Shell.	Length of Shell.		Area of Grate.	Total Heating Surface.	Ratio of Grate to Heating Surface.	Number of Flues.	Diameter of Flues.	Length of Flues.		Horse Power.	
Inches.	Feet.	Inches.	Decimal Sq. Ft.	Decimal Sq. Ft.	Number.	Number.	Inches.	Feet.	Inches.	Decimals.	
20	4	1½	1.07	20.7	$\frac{1}{20}$	19	1½	2	3	1.5	
20	4	10½	1.07	25.6	$\frac{1}{24}$	19	1½	3	0	1.65	
24	5	0	1.75	35.7	$\frac{1}{20}$	19	2	3	0	2.6	
24	5	9	1.75	42.5	$\frac{1}{24}$	19	2	3	9	2.85	
28	5	1½	2.64	55.9	$\frac{1}{20}$	31	2	3	0	3.95	
28	5	10½	2.64	66.9	$\frac{1}{24}$	31	2	3	9	4.3	
28	6	7½	2.64	77.9	$\frac{1}{28}$	31	2	4	6	4.6	
32	5	3	3.70	76.9	$\frac{1}{20}$	43	2	3	0	5.58	
32	6	0	3.70	91.9	$\frac{1}{24}$	43	2	3	9	6.	
32	6	9	3.70	107.2	$\frac{1}{28}$	43	2	4	6	6.47	
36	5	6	4.91	100.	$\frac{1}{20}$	43	2½	3	1½	7.35	
36	6	3	4.91	118.9	$\frac{1}{24}$	43	2½	3	10½	8.	
36	7	0	4.91	137.8	$\frac{1}{28}$	43	2½	4	7½	8.6	








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION.

CLASS SIXTH.


Plate 1.

No 2.  
Steam Table for warming  
Soup, Coffee, Tea & Milk.





No 4.

Mangle for Laundries.



Hotel Drain Table for Dishes.



No 3.  
Steam Carrying Table and Dishes  
with Platters & Covers.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION.

CLASS SIXTH.


Plate 2.

No 6.



*Cooking Range for Hotels &c.*

No 7.




*Broiling Oven.*

No 8.




*Lard Kettle.*

No 9.




*Double Bottom Copper Kettles.*

No 12.




*Hot Water Back.*

No 10.




*Double Steam Kettle.*

No 11.



*Kettle with Steam Coil.*

No 14.



*Hot Water Box.*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION.


CLASS SIXTH.

Plate 3.



No 20.

Woodward's Steam Pump.




No 24.

Clark's Pat. Damper Regulator.


Damper Rod.

Steam Connection.




No 27.

Worthington's No 4 1/2 Steam Pump.




No 23.

Worthington's Duplex Steam Pump.




No 22.

Worthington's No 3 Steam Pump.



No 25.

Ventilating Fan with Shaft, Pedestals & Pulley.



No 26.

Blowing Fans.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION.

CLASS SIXTH.


Plate 4.

N<sup>o</sup> 31.




*Single Boiler Front  
(hexagonal Columns)*

N<sup>o</sup> 32.




*Double Boiler Front (hexagonal Columns)*

N<sup>o</sup> 33.



*Single Boiler Front  
(fluted Columns)*

N<sup>o</sup> 34.



*Double Boiler Front (fluted Columns).*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE

10<sup>th</sup> EDITION.

CLASS SIXTH.


Plate 5.



*Upright  
Tubular Boiler:*


*No. 40. Single Boiler Front  
(plain)*

*No. 41. Double Boiler Front (plain.)  
No. 43.*




*Coil Header.*

*No. 44.*




*Horizontal Tubular Boiler.*



*No. 2 & 3 Wringing Machines.*



*No. 45.*



*Hospital Food Car.*



[BLANK PAGE]



CCA



*Persons in ordering will please state the "Edition" they order from.*

## CLASS SEVENTH.

Every order for special articles must have accurate plans and dimensions attached, and no order, "same as before," will be received.

Any article for which no price is quoted on the list will be made only to special order, although such article may be shown in the illustrations.

### HEATING APPARATUS AND MATERIALS. GREEN-HOUSE PIPE AND FITTINGS.

No. PLATE

1

DIAMETER IN INCHES,			3	4
			<del>45</del>	<del>60</del>
1	Pipe, (lays 9 feet, measures 9 feet 2½ inches,)	per foot,	<del>\$0 60</del>	<del>\$0 75</del>
2	Evaporating Pipe, (4 feet 6 inches long,)	each,	3 50	4 50
3	Flanged Ell, faced and drilled, with bolts, { 3 in. flanges, 6½ in. diam. }	"	2 10	2 65
	{ 4 " " 8 " " }			
4	Flanged Bell, " " " { 3 " " 6½ " " }	"	1 80	2 25
	{ 4 " " 8 " " }			
5	Saddle Flanged Ell, drilled, with bolts, { 3 " " 6½ " " }	"	2 10	2 65
	{ 4 " " 8 " " }			
6	Eighth Bend,	"	1 00	1 35
7	Ell, (or bend,)	"	1 00	1 35
8	Plug,	"	25	35
9	Cap,	"	35	50
10	Reducers, (bell small end,)	"		1 50
11	Double Bell,	"	75	1 10
12	Sleeve,	"	45	60
13	Offset Pipe, bell one end, (offset, 9 inches,)	"	2 60	3 50
14	Return bend, bell one end, (3 in.—c. to c. 4¼ in.) (4 in. c. to c. 7⅝ in.)	"	1 80	2 40
				2 00
15	Return Bend, bell both ends, (3 in.—c. to c. 4¼ in.) (4 in. { c. to c. 5½ in. }	"	1 70	2 25
	{ c. to c. 7⅝ in. }			2 50
	{ c. to c. 10½ in. }			
16	Back Outlet Return Bend, bells both legs, outlet spigot, (3 in.—c. to c. 4¼ in.) (4 in.—c. to c. 7⅝ in.)	"	2 10	2 80
17	Y Cross, bells on both outlets and one end of run,	"		4 20
18	Y Branch, bell on outlet and one end of run,	"		3 00
19	Cross, bells on both outlets and one end of run,	"	2 30	3 00
20	Tee, bell on outlet and one end of run,	"	1 50	2 00
21	Eighth Bend, extra length, (1 foot 6 inches extra length,)	"	1 90	2 50
22	Tee, Reducing, bell on outlet and one end of run,	"		2 00
23	Back Outlet Return Bend, bells on outlet and one leg, one leg spigot, (3 in.—c. to c. 4¼ in.) (4 in.—c. to c. 7⅝ in.)	"	2 10	2 80
24	" " bell on outlet, both legs spigot, ( " " " ) ( " " " )	"	2 10	2 80
25	" " bells on all ends, ( " " " ) ( " " " )	"	2 10	2 80
26	H Branch, (with bottom bell outlet,) two pair high, ( " " " ) ( " " " )	"	4 80	6 00
Not drawn.	" " " three " ( " " " ) ( " " " )	"	6 40	8 00
27	Three Branch Tee, ( " " " ) ( " " " )	"	3 20	4 00
28	Two " " ( " " " ) ( " " " )	"	2 40	3 00
Not drawn.	Four " " ( " " " ) ( " " " )	"	4 00	5 00
	Flanged ends, bell ends, spigot ends, or both outlets, as shown by dotted lines on 27 and 28, as may be ordered, additional price per end or outlet,	"	80	1 00
29	Expansion Pipe Roller, 2½ in. Roller, 2 ft. 8½ in. long, \$4.40; 1 ft. 7½ in. long, \$3.75.			
30	Roller Stands, 3 pipes high by 2 pipes wide, (6 pipes,)		1 45	1 80
"	" " 3 " " 3 " " (9 " )		1 80	2 20
Not drawn.	" " 4 " " 2 " " (8 " )		1 80	2 20
31	" " 2 " " 2 " " (4 " )		1 20	1 50
"	" " 2 " " 3 " " (6 " )		1 45	1 80
"	" " 2 " " 4 " " (8 " )		1 80	2 20
32	" " 2 pipes high by 1 pipe wide,		70	90
"	" " 3 " " 1 " "		95	1 20
"	" " 4 " " 1 " "		1 20	1 50
33	" " 2 top and 1 bottom, (3 pipes,)		95	1 20

35021



CLASS SEVENTH.—*Continued.*

## GREEN-HOUSE BOILERS, CAST IRON DOORS AND FRAMES, DAMPERS.

No.	PLATE		
	2		
36		"Burbige & Healy" Corrugated Boiler, 28 in. diameter, suited for 750 ft. of 4 in. pipe, with one pair of flow and return branches,	\$ 97 00
36		" " " " " " " " " " two " " " "	100 00
37		" " Ribbed, " 20 in. " " 500 ft. of " " one " " " "	67 00
37		" " " " " " " " " " two " " " "	70 00
38		" " " " 16 in. " " 275 ft. of " " one " " " "	47 00
38		" " " " " " " " " " two " " " "	50 00
38		Check Plates, for 28 in. boiler, \$2.00; for 20 in. boiler, \$1.25; for 16 in. boiler, \$1.00.	
39		Sectional Ring Boiler, 20 in. diameter, suited for 675 ft. of 4 in. pipe, with one pair of flow and return branches,	70 00
39		" " " " " " " " " " two " " " "	70 00
40		Portable Boiler-setting, galvanized sheet iron case and fire brick lining, with grates, etc., etc., for setting complete, for 28 in. Burbige & Healy Boiler, including boiler,	205 00
40		" " " " " " " " " " 20 in. " " " "	160 00
40		" " " " " " " " " " 16 in. " " " "	135 00
40		" " " " " " " " " " 20 in. Sectional Ring Boiler, including boiler,	160 00
41		Green House Single Wedge Valve, for shutting any portion of apparatus, (all surfaces brass,)	10 00 12 50
42		" " Throttle Valve, for regulation only,	5 00 6 25
43		" " Box Valve, for shutting off any portion of apparatus,	9 00
44		Dust Door for Burbige & Healy Boilers; Frame, 8×8 in.; Opening, 5½×5½ in.,	60
45		Fire Front, 2 ft. 5 in. high, by 1 ft. 7 in. wide; Fire Door, 12 in. high, by 15 in. wide; Ash Door, 10 in. high, by 15 in. wide, fitted,	6 50
45		" 2 ft. 3½ in. " 1 ft. 5 in. " " 12 in. " 12 in. " " 9 in. " 12 in. " "	5 60
45		" 1 ft. 8 in. " 1 ft. 0 in. " " 8 in. " 8 in. " " 6½ in. " 8 in. " "	2 00
46		Fire Front, 2 ft. 11 in. high, by 2 ft. 4 in. wide, "Sylvester" doors, (with Dead Plates;) Fire Door, 9 in. high, by 11 in. wide, Ash Door,	23 00
46		12½ in. high, by 11 in. wide, fitted,	
46		Frame, 3 ft. high, by 2 ft. 5 in. wide, by 4½ in. deep, (forming recess,)	
47		Bearer Bars, per pair, for 28 in. boiler, \$1.85; for 20 in. boiler, \$1.85; for 16 in. boiler, 70 cents.	
48		Grate Bars, per set, for 28 in. boiler, 24×24 in. \$7.10; for 20 in. boiler, 20×24 in. \$5.70; for 16 in. boiler, 14×18 in. \$3.50.	
49		Dead Plates, for Sylvester fronts,	2 00
52	PLATE 3	Bake Oven Door with dead plate, Frame, 1 ft. 11¼ in. high, by 2 ft. 7½ in. wide; Opening, 1 ft. 4 in. high, by 1 ft. 11½ in. wide, fitted,	11 50
53		" " " " 1 " 2½ " 2 " 1 " " 1 " 0 " 1 " 6¼ " " "	7 70
54		" " " " 1 " 1 " 2 " 4½ " " 1 " 0 " 1 " 9½ " " "	9 50
55		Flue or Dust Door with Frame, Frame, 0 ft. 7 in. high, by 0 ft. 10½ in. wide; Opening, 0 ft. 5 in. high, by 0 ft. 6 in. wide, fitted with anchor bolts,	1 00
56		" " " " 1 " 7¾ " 1 " 7¾ " " 1 " 3¾ " 1 " 2 " " " "	4 60
56		" " " " 1 " 4½ " 1 " 4½ " " 11½ " 11½ " " " "	3 85
56		" " " " 1 " 0½ " 1 " 4½ " " 9 " 1 " 0½ " " " "	3 05
56		" " " " 11 " 1 " 2¾ " " 8½ " 11½ " " " "	2 15
56		" " " " 1 " 0¾ " 11 " " 10 " 8 " " " "	1 20
57		Manhole " " " 2 " 5 " 1 " 7½ " " 1 " 10 " 1 " 2½ " " " "	5 65
58		Flue or Dust " " " 1 " 2½ " 1 " 7 " " 1 " 0 " 1 " 4 " " " "	3 70
59		Ash Pit " " " 1 " 1½ " 1 " 1½ " " 9½ " 9½ " " " "	2 30
60		Manhole " " " 4 " 5 " 2 " 1 " " 4 " 0 " 1 " 8 " " " "	15 25
61		" " " " 4 " 10¼ " 1 " 8½ " " 4 " 6 " 1 " 4¼ " " " "	12 00
62		Brick Kiln Fire Front, " 2 " 9½ " 1 " 2 " Fire Door, 1 " 11 " 11 Ash Door, 1 ft. 2 in. by 11 in. fitted,	5 90
63		Flue or Dust Door with Frame, " 1 " 1 " 1 " 3½ " Opening, 10½ " 1 " 1 in. wide, fitted with anchor bolts,	2 10
64		" " " " 1 " 0¾ " 10½ " " 10½ " 8 " " " "	1 25
65		Smoke Flue Dampers (sliding), " 11¾ " 11¾ " " 8¾ " 8¾ in wide,	80
66		" " " " 10 " 2 " 0½ " " 4 " 1 " 7 " " " "	3 90
67		" " " " 1 " 10½ " 1 " 2 " " 10 " 10 " " " "	6 35
68		" " " " 1 " 6 " 1 " 0 " " 7¾ " 7¾ " " " "	4 00
69		" " (throttle,) " 1 " 4½ " 1 " 0½ " " 1 " 4 " 1 " 0 " box frame,	4 25
69		" " " " 3 " 5½ " 1 " 5 " " 3 " 0 " 1 " 0 " flat " "	12 00
69		Arrow and Quadrant, radius 6 inches,	1 25
69		Damper Rods and Tubes, to accompany 69, at per foot of length, ¾ in. 30 cents; 1 in. 45 cents.	
70		Sash-lifting Apparatus, 1½ in. tube shaft, for first window, \$4.50, and each additional window, \$1.75.	
70		" " 1 in. " " 3.50, " " 1.25.	
		Tube used extra.	



CLASS SEVENTH.—*Continued.*

## HOUSE HEATING APPARATUS AND MATERIALS.

No.	PLATE		Nominal Dimensions.	Area of Grate.	Capacity. Number of feet of heating surface.	Cubic feet of space which can be heated varies with circumstances from	External radiating surface available for heating.	Price for either Anthracite or Bitum's Coal.
74	4	Tasker's Self-Regulating Hot Water Furnace, . . . . .	36 inches. 30 " 24 " 20 "	9 $\frac{6}{10}$ square feet. 6 $\frac{5}{10}$ " 4 $\frac{5}{10}$ " 3 $\frac{1}{10}$ "	2,775 square feet. 1,875 " 1,300 " 900 "	92,500 to 55,500 62,500 to 37,500 43,000 to 26,000 30,000 to 18,000	148 square feet. 133 " 125 " 115 "	\$775 00 673 00 540 00 455 00
IN ORDERING STATE WHETHER ANTHRACITE OR BITUMINOUS COAL IS USED.								
75		* Ribbed Radiators for hot water, 1 ft. deep, 3 ft. 6 in. long, 2 $\frac{3}{4}$ in. wide, 15.2 sq. ft. radiating surface.					Number of feet of heating surface,	\$7 20
76		* Ribbed Radiators for steam heating, 9 in. deep, 3 ft. 6 in. long, 2 $\frac{3}{4}$ in. wide, 12.2 sq. ft. radiating surface,					Inside radiators,	6 00
		Number of feet of heating surface, . . . . .					Outside "	6 50
77		Radiator Elbows, for 3 inch pipe, . . . . .						70
78		" Sockets, " " . . . . .						60
79		" Tees, " " . . . . .						80
80		" Caps, " " . . . . .						45
81		" Separating piece, " " . . . . .						45
Radiator Tees, Sockets, Elbows, and Caps, are made with or without fillets, as required.								
82		Ring Packing, per pair, . . . . .						10
* In estimating the effective heating surface of Ribbed Radiators as compared with that of plain surfaces, the Hot Water Radiators should be taken at 12 square feet, and the Steam Radiators at 9 square feet.								
PLATE 5		Settings of Burbige & Healy's Green-House Boilers.						

## NOTES ON HEATING.

## RULES FOR THE HEATING OF GREEN-HOUSES IN THE VICINITY OF PHILADELPHIA, OR WHEREVER THE MINIMUM TEMPERATURE DOES NOT GO BELOW THE ZERO OF FAHRENHEIT.

Lowest temperature to be maintained in house, . . . . .	45°	50°	60°	70°	80°	90°
Feet of glass or panel surface exposed, which will be heated by each foot of 4 inch Green-house pipe at the temperature of 200°, . . . . .	5 ft.	4 $\frac{3}{4}$ ft.	3 $\frac{3}{10}$ ft.	2 $\frac{7}{10}$ ft.	2 $\frac{1}{8}$ ft.	1 $\frac{3}{4}$ ft.

It is safe for ordinary green-house temperature to take an average of four feet of glass or panel surface to each foot of four inch pipe. The walls, if of stone, or of brick with an air-space, may be neglected. Eight square feet of nine inch brick wall calls for about one foot of four inch pipe to heat it. The exposure modifies this rule. Vertical North exposed glass walls should have 1 foot of pipe to 2 feet of glass; Vertical East or West glass walls 1 foot of pipe to 4 feet of glass; and Vertical South glass walls can be heated by 1 foot of pipe to 6 feet of glass—the horizontal glass surfaces needing the average of 1 foot of pipe to 4 feet of glass. For warming water for use in the house, the water of the heating circulation should not be taken. The proper arrangement is a transfer pipe led through the water trough.

Bottom heat tanks should have their heat supplied also by a transfer pipe from the circulation, and not be connected with the boiler directly. A bottom heat tank can have one line of 4 inch pipe laid in it for each 4 feet of width of the tank. Transfer pipes should be controlled by valves, to prevent too great absorption of heat in cold weather from the boiler.

## RULES FOR THE HEATING OF DWELLING HOUSES.

For heating satisfactorily by low temperature currents, we can take for average city houses in blocks, three feet of radiating surface heated below the boiling point to each 100 cubic feet of space, but in exposed buildings as much as five feet of radiating surface to each 100 cubic feet of surface is needed.

The heating and ventilating flues should be ample. Both should enter the rooms at or near the floor; and, if possible, they should be on opposite sides of the rooms. The following dimensions of heating flues will insure a supply of warm air:

Height of bottom of Register above top of Radiators, . . . . .	1 ft.	2 ft.	3 ft.	4 ft.	6 ft.	8 ft.	10 ft.	15 ft.	20 ft.	25 ft.	30 ft.	40 ft. and above,
Square inches of Flue needed for each square foot of Radiating surface which the room requires, . . . . .	2 in.	1.41 in.	1.16 in.	1 in.	0.82 in.	0.71 in.	0.63 in.	0.52 in.	0.45 in.	0.40 in.	0.36 in.	0.32 in.

To the area obtained by this rule should be added for all flues 20 square inches, to compensate for the resistance of the mouth or discharge, or to give a practical magnitude to small flues. The ventilating flues follow the same law, only the height is to be taken from the Register to top of chimney. Example: A room of 3000 cubic feet capacity of average exposure, at 3 square feet of radiating surface to the 100 cubic feet of space, will need 90 square feet of radiating surface.

Suppose the Radiators be placed 2 feet below the Register, then  $90 \times 1.41 = 126.9$ ; adding 20 square inches will give  $= 146.9$ , or a heating flue of  $9 \times 16$  in sectional area should be provided.

Suppose the top of ventilating chimney to be 40 feet above the Register, then  $90 \times 0.32 = 28.8$ ; adding 20 square inches  $= 48.8$  or  $9 \times 5 \frac{1}{2}$  will be needed.

Boilers to supply heat to pipe or radiating surface as above, should have one square foot of grate surface, or area, to each 300 square feet of radiating surface; and there should be added to the grate surface given by this rule, one-third square foot, to give a practical area to the smaller grates.



THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION

500 N. 5TH ST. NEW YORK, N. Y.

THE NEW YORK PUBLIC LIBRARY ASTOR LENOX TILDEN FOUNDATION




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS SEVENTH.


Plate 1.

No 1.



Green house Pipe.

No 2.




Green house Evaporating Pipe.




Flanged Ell.

No 4.




Flanged Bell.

No 5.



Saddle flanged Bell.

No 10.



Reducer (Bell small end)

No 11.



Double Bell.

No 12.



Sleeve.

No 8.



Plug.

No 9.




Cap.

No 6.



Eighth Bend.

No 7.




Ell or Bend.

No 13.




Offset Pipe, Bell one End.

No 14.




Return Bend, Bell one end.

No 15.




Return Bend, Bell both ends.

No 16.



Back Outlet Return Bend.

No 17.




Y Cross.

No 18.



Y Branch.

No 19.




Cross, 3 Bell Ends.

No 20.



Tee, 2 Bell ends.

No 21.




Eighth Bend (extra length.)

No 29.




Expansion Pipe Roller.

No 22.




Reducing Tee.

No 23.



Back Outlet Return Bend.

No 24.




Back Outlet Return Bend.

No 25.




Back Outlet Return Bend.

No 30.




6 Pipe Roller Stand.

No 31.




4 Pipe Roller Stand.

No 32.




2 Pipe Roller Stand (2 high)

No 33.




3 Pipe Roller Stand.

No 26.




H Branch, with bottom Bell Outlet.

No 27.












Three Branch Tee.

No 28.



Two Branch Tee.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS SEVENTH.


Plate 2.




"Burbige & Healy" 28 inch Corrugated Boiler.



Sectional Ring Boiler.




Portable Greenhouse Boiler Setting.



Single Wedge Valve




Throttle Valve.



Greenhouse Box Valve.



Dust Door.



Fire Front.

No. 47.




Bearer bars

No. 48.




Grate bars.




"Burbige & Healy" 20 inch Ribbed Boiler.

No. 38.




"Burbige & Healy" 16 inch Ribbed Boiler.

No. 46.








Fire Front "Sylvester Doors."

No. 49.



Dead Plate.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS SEVENTH.


Plate 3.

No 52.




Bake Oven Door with Dead Plate.

No 53.




Bake Oven Door with Dead Plate.

No 54.




Bake Oven Door with Dead Plate.

No 55.



Flue or Dust Door with Frame.


No 56.



Flue or Dust Door.


No 60.

No 57.




Manhole Door.

No 61.




Manhole Door with Frame.

No 58.



Flue or Dust Door with Frame.


No 59.



No 70.

Window Lifting Apparatus.


No 69.



Throttle Damper.


Arrow & Quatrant.

No 63.




Flue or Dust Door with Frame.

No 64.




Flue or Dust Door with Frame.

No 65.




Smoke Flue Damper (sliding.)

No 62.




Brick Kiln Fire Front.




Smoke Flue Damper (sliding)

No 67.








No 68.



Smoke Flue Damper (sliding.)









# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION



CLASS SEVENTH.

Plate 4.


No 75.  
Ribbed Radiators for Hot Water.



No 76.  
Ribbed Radiators for Steam Heating.



No 74.




"Tasker" Self Regulating Hot Water Furnace.  
(Section showing construction.)

No 77.




Radiator Ell.

No 78.



Radiator Socket.

No 79.



Radiator Tee.

No 80.




Cap.

No 81.



Separating Piece.

No 82.



Ring Packing.




[BLANK PAGE]




CCA




## SETTINGS OF BURRIGE & HEALEY'S GREEN-HOUSE BOILERS.




Horizontal Section at A B.




Vertical Section on C D.



Front View.



Horizontal Section at E F.  
Surface of Grate.



Half Front View,  
showing Brick work  
back of Sylvester Front.  
Section at G H.

The Sylvester Front is the same for all sizes of Boilers.

The grate of 28 in. Boiler is 2 ft. 0 in. long by 2 ft. 0 in. wide.

" " 20 " " 2 " 0 " " 1 " 6 " "

" " 16 " " 1 " 6 " " 1 " 2 " "

The ash pits of all the Boilers are the same size as the grates. The height of the bottom of each Boiler is given on the vertical section.

The outside sizes of the brick work in the plan:

For 28 in. Boiler, 4 ft. 10 in. square.


" 20 " " 4 " 6 " "

" 16 " " 4 " 2 " "


The fire chamber is drawn in from the size and shape of the grate, to a circle one inch larger all round, than the projections of the Boiler.



SECTIONS OF THE NEW YORK CITY AND HUDSON RIVER RAILROAD



SECTION OF THE NEW YORK CITY AND HUDSON RIVER RAILROAD



SECTION OF THE NEW YORK CITY AND HUDSON RIVER RAILROAD



SECTION OF THE NEW YORK CITY AND HUDSON RIVER RAILROAD



SECTION OF THE NEW YORK CITY AND HUDSON RIVER RAILROAD



SECTION OF THE NEW YORK CITY AND HUDSON RIVER RAILROAD

SECTION OF THE NEW YORK CITY AND HUDSON RIVER RAILROAD



*Persons in ordering will please state the "Edition" they order from.*

## CLASS EIGHTH.

Every order for special articles must have accurate plans and dimensions attached; and no order, "same as before," will be received.  
Any article for which no price is quoted on the list will be made only to special order, although such article may be shown in the illustrations.

### APPARATUS FOR SOUNDING FOR MINERALS, ETC.

No. PLATE.

1	1	Drill or Sounding Rods, 1 $\frac{1}{4}$ " Square Iron Body, 1 $\frac{1}{4}$ " Tube Screw; length, . . . . .	10'	5'	2' 6"	1' 3"
		Price, each length, . . . . .	\$8.50	\$5.50	\$4.00	\$2.25

SIZE, . . . . .		2	2 $\frac{1}{2}$	3	3 $\frac{1}{2}$	4
		\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
2	1	Cross Head for Drilling or Sounding, . . . . . \$11.00	...	...	...	...
3	1	Shackle Joint for Drilling with Rods, . . . . . 15.50	...	...	...	...
4	1	Worm Augur, Taper, . . . . .	5.70	6.75	7.80	8.85
5	1	Spiral Augur, (4 twists), . . . . .	7.20	8.50	9.90	11.25
6	1	Pod Augur, . . . . .	6.30	7.50	8.70	9.90
7	1	Tool for Enlarging Hole below Well Pipe, . . . . .	8.60	10.00	12.00	13.50
8	1	Thief Bucket, . . . . .	7.20	8.35	9.90	11.25
9	1	Drill, pointed end, . . . . .	6.30	7.50	8.70	9.90
10	1	Drill, chisel end, . . . . .	6.30	7.50	8.70	9.90
11	1	H Drill, or Reamer, . . . . .	9.30	10.75	12.20	13.65
12	1	Broach, . . . . .	9.10	10.80	12.30	14.80
13	1	Swivel, . . . . .	2.80	3.00	3.25	3.75
14	1	Y or Fork, . . . . .	2.70	2.70	2.70	2.70
15	1	Drawing Hook, . . . . .	2.70	2.70	2.70	2.70
16	1	Iron Blocks, per pair, . . . . . \$19.00	...	...	...	...
17	1	Clamp, . . . . .	3.20	4.00	...	...
18	1	Wrench, . . . . .	1.50	1.50	1.50	1.50
19	1	Strap Joints, . . . . .	1.60	2.00	2.50	3.00

### WROUGHT IRON TUBULAR FLUSH JOINT PUMP RODS.

Internal Diameter, Nominal.	External Diameter, Actual.	Price, per Foot, including Joint.
Inches.	Inches.	\$ c.
$\frac{1}{2}$	...	...
$\frac{3}{4}$	1.05	.28
1	1.32	.35
1 $\frac{1}{4}$	1.66	.45
1 $\frac{1}{2}$	1.9	.56

Additional charge for Pump Rods of extra heavy tube.

21	1	PIPE TONGS. NUMBER IN CLASS THIRD, TENTH EDITION, 48.				
		Size, . . . . .	$\frac{1}{2}$	$\frac{3}{4}$	1	1 $\frac{1}{4}$
		Price, per pair, . . . . .	\$1.30	\$1.55	\$2.00	\$2.55



## CLASS EIGHTH.—Continued.

## ARTESIAN WELL BORING TOOLS.

No.	PLATE.	SIZE, IN INCHES	6	8	10	12
22	2	Boring Rod, 1½" Square Iron, for Sinking Wells; 4" to 12" internal diam., @ \$4.80 per pair of ends, and 60c. per foot of length; 1½" square. Per piece, complete,	\$ c. 8.40	\$ c. 9.60	\$ c. 10.80	\$ c. 12.00
		Boring Rod, 1½" Square Iron, for Sinking Wells; 2" to 3½" internal diam., @ \$3.00 per pair of ends, and 42c. per foot of length; 1½" square. Per piece, complete,	6.42	7.06	8.10	10.52

	SIZE,	2	2½	3	3½	4	5	6	8	10	12
23	2	Pod Augur, with Steel Cutting Edge,	\$ c. 6.20	\$ c. 7.50	\$ c. 8.70	\$ c. 9.90	\$ c. 11.10	\$ c. 13.50	\$ c. 15.90	\$ c. 20.70	\$ c. 25.50
24	2	Lip Augur, " "	6.20	7.50	8.70	9.90	11.10	13.50	15.90	20.70	25.50
25	2	Worm Augur, (8 twists),	8.70	10.50	12.30	14.10	15.70	19.50	23.10	30.30	37.50
26	2	" (4 twists),	7.20	8.50	9.90	11.25	12.60	15.30	18.00	23.40	28.80
27	2	" (2 twists),	6.00	7.20	8.40	9.60	10.80	13.20	15.60	20.50	25.20
28	2	" Conical,	5.70	6.75	7.80	8.85	9.90	12.00	14.10	18.30	22.50
29	2	" Tapering,	5.70	6.75	7.80	8.85	9.90	12.00	14.10	18.30	22.50
30	2	Spiral Augur, flat, }	5.70	6.75	7.80	8.85	9.90	12.00	14.10	18.30	22.50
31	2	" " }	5.70	6.75	7.80	8.85	9.90	12.60	15.30	20.70	26.10
32	2	Wrench Bar,	...	2.70	...	...	...	3.60	...	...	...
33	2	Y or Fork,	...	2.70	...	...	...	3.90	...	...	...
34	2	Lifter,	...	4.75	...	...	...	6.00	...	...	...
35	2	Well Hook,	...	5.40	...	...	...	7.20	...	...	...
36	2	Spring Catch for Hauling Pipe,	5.40	6.30	7.20	8.10	9.00	10.80	12.60	16.20	19.20
37	2	Drill Stock, and Drill for Soft Rock,	21.00	24.00	27.00	30.00	33.00	...	...	...	23.45
38	2	Boulder Cracker,	6.60	10.20	13.80	17.45	21.00	28.20	35.40	...	...
39	2	Drift Hammer,	2.50	...	...	...	...	...	...	...	...
40	2	Cross Head,	4.80	5.70	6.60	7.30	8.40	10.25	12.60	15.60	19.20
41	2	Hook,	...	2.10	...	...	...	3.10	...	...	22.80
42	2	"	...	3.30	...	...	...	...	...	...	...
43	2	"	...	.60	...	...	...	...	...	...	...
44	2	"	...	2.90	...	...	...	...	...	...	...
45	2	Catch Hook for Hauling Pipe,	8.00	8.00	8.00	8.00	9.00	9.00	9.00	9.00	9.00
46	2	Wrench Handle,	...	13.20	...	...	...	18.00	...	...	...
47	3	Gin Pulley, (12" Wheels),	...	16.20	...	...	...	...	...	...	...
48	3	Broach for Rock Work,	9.10	10.80	12.30	14.80	17.30	...	...	...	...
49	3	Socket Hook for Lifting Rods,	...	8.40	...	...	...	10.80	...	...	...
50	3	Bit,	...	18.00	...	...	...	...	...	...	...
51	3	Reamer,	...	18.00	...	...	...	...	...	...	...
52	3	Drill Stock and Drill for Soft Rock, with Cutters as ordered,	...	...	...	...	...	...	...	...	...
53	3	Valve Socket for Catchall,	...	30.00	...	...	...	...	...	...	...
54	3	Pair of Jars,	...	...	...	...	...	...	...	...	...
55	3	Sand Pump, (Galvanized Iron), 7' long, 3" diam., heavy iron,	...	20.00	...	...	...	...	...	...	...
56	3	Combination Augur,	...	...	...	...	...	...	...	...	...
57	3	Drill,	6.30	7.50	8.70	9.90	11.10	...	...	...	...
58	3	H Drill,	9.45	11.25	13.00	14.85	16.65	...	...	...	...
59	3	Drill,	6.30	7.50	8.70	9.90	11.10	...	...	...	...
60	3	Catchall for various sizes,	57.00	58.50	60.00	61.50	63.00	66.00	...	...	...
61	3	Catchall,	57.00	58.50	60.00	61.50	63.00	66.00	69.00	75.00	90.00



CLASS EIGHTH.—*Continued.*No. PLATE.  
62 4

## CAST IRON ARTESIAN WELL PIPE, WITH BOLLES' PATENT FLUSH JOINT.

Nominal Diameter.	Inside Diameter at Joint.	Outside Flush Diameter.	Length of each Pipe.	Price, per Foot, with Connecting Band.	Price of each Bottom Pipe and Connecting Band, with Bottom Band and Steel Cutting Edge.
Inches.	Inches.	Inches.	Feet.	\$ c.	\$ c.
12	11 $\frac{7}{8}$	13 $\frac{3}{4}$	10	6.65	99.67
10	10	11 $\frac{5}{8}$	9	5.90	72.21
8	7 $\frac{7}{8}$	9 $\frac{5}{8}$	8	3.90	47.60
6	5 $\frac{5}{8}$	6 $\frac{15}{16}$	8	2.63	32.55
5	5	6 $\frac{1}{4}$	9	2.26	26.15

63 4

## CAST IRON DRIVING PIPE, BOLLES' PATENT FLUSH JOINT.

THE ENDS OF THE PIPES TURNED ACCURATELY TO RING GAUGES, AND SQUARED OFF IN LATHE. THE WROUGHT IRON BAND, OF THE BEST IRON, CAREFULLY WELDED AND SIZED TO SHRINK ON. LENGTHS EIGHT FEET.

DIAMETER, INCHES,	12	10	8	6	5
	\$ c.	\$ c.	\$ c.	\$ c.	\$ c.
Price, per foot, including Connecting Bands,	16.80	13.00	7.09	4.79	4.14
Price, per foot, without Bands,	15.62	12.00	6.33	4.42	3.80
Price for Connecting Band, separate,	9.62	8.00	6.23	2.80	2.62
Price for Bottom Band with steel edge, separate,	15.00	12.82	7.13	5.03	4.57
Price for heavy Top Band,	10.31	9.26	8.55	5.35	5.02

64 4

## HEAVY WROUGHT IRON ARTESIAN WELL TUBE,

WITH SCREW AND SOCKET, OR WITH FLUSH JOINTS, FINISHED SMOOTH INSIDE.

Inside Diameter, inches,	1 $\frac{1}{2}$	2	2 $\frac{1}{2}$	3	3 $\frac{1}{2}$	4	4 $\frac{1}{2}$	5	6	7	8
Price, per foot,	.30	.45	.65	.94	\$1.16	\$1.44	\$1.75	\$2.00	\$2.88	\$4.00	\$5.00

65 4

## LIGHT WROUGHT IRON ARTESIAN WELL TUBE, OR OIL WELL CASING,

WITH SCREW AND SOCKET, OR WITH INSERTED JOINT, FINISHED SMOOTH INSIDE.

Diameter. Actual Outside.	Diameter. Nominal Inside.	Price, Per Foot.
1 $\frac{3}{4}$ in.	1 $\frac{1}{2}$ in.	\$0.33
2 $\frac{1}{4}$ in.	2 in.	.38
2 $\frac{1}{2}$ in.	2 $\frac{1}{4}$ in.	.42
2 $\frac{3}{4}$ in.	2 $\frac{1}{2}$ in.	.48
3 in.	2 $\frac{3}{4}$ in.	.55
3 $\frac{1}{4}$ in.	3 in.	.60
3 $\frac{1}{2}$ in.	3 $\frac{1}{4}$ in.	.66
3 $\frac{3}{4}$ in.	3 $\frac{1}{2}$ in.	.83
4 in.	3 $\frac{3}{4}$ in.	1.00
4 $\frac{1}{4}$ in.	4 in.	1.12
4 $\frac{1}{2}$ in.	4 $\frac{1}{4}$ in.	1.24
5 in.	4 $\frac{3}{4}$ in.	1.50
5 $\frac{1}{4}$ in.	5 in.	1.60
5 $\frac{1}{2}$ in.	5 $\frac{3}{16}$ in.	1.75
6 in.	5 $\frac{5}{8}$ in.	1.85
6 $\frac{5}{8}$ in.	6 $\frac{1}{4}$ in.	2.25
7 in.	6 $\frac{5}{8}$ in.	2.50
8 in.	7 $\frac{5}{8}$ in.	3.75
8 $\frac{5}{8}$ in.	8 $\frac{1}{4}$ in.	4.50



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS EIGHTH.

Plate 7.










# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS EIGHTH.

Plate 2.

No 22.



Boring Rod.

No 23.



Pod Augur.

No 24.



Lip Augur.

No 25.



Worm Augur, 8 twists.

No 26.




Worm Augur, 4 twists.

No 27.



Worm Augur, 2 twists.

No 28.




Worm Augur, conical.

No 29.




Worm Augur, tapering.

No 30.



Spiral Augur, flat.

No 32.



No 31.



Spiral Augur, flat.

No 33.



Wrench Bar.

Yor Fork.

No 39.



Drift hammer.

No 40.



Cross head.



No 34.

Lifter.



No 35.

Well hook.



No 36.

Spring catch, for hauling Pipe.



No 37.

Drill stock & Drill for soft rock.



No 38.


No 41.



No 42.




No 43.



No 44.




No 45.



Catch hook for hauling Pipe.

No 46.



Wrench handle.

Hooks.

Boulder Cracker.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS EIGHTH.

Plate 3.



Apparatus for sinking Artesian Wells.








# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS EIGHTH.


Plate 4.

No 62.



*Cast Iron Artesian Well Pipe, with Bolles' Patent Flush Joint.*


No 63.



*Cast Iron Driving Pipe, Bolles' Patent Flush Joint.*


No 64.

*Sect. of Bottom End with Steel edged Bottom Band.*




*Heavy Wrought Iron Artesian Well Tube, Flush Joint.*

No 65.




*Light Wrought Iron Artesian Well Tube, Inserted Joint.*

No 64.



*Heavy Wrought Iron Artesian Well Tube, with Screw & Socket.*

No 65.



*Light Wrought Iron Artesian Well Tube, with Screw & Socket.*





Large Wardrobe with Glass Doors and Drawers



Large Wardrobe with Glass Doors and Drawers



Large Wardrobe with Glass Doors and Drawers



*Persons in ordering will please state the "Edition" they order from.*

## CLASS NINTH.

Every order for special articles must have accurate plans and dimensions attached; and no order, "same as before," will be received.

Any article for which no price is quoted on the list will be made only to special order, although such article may be shown in the illustrations.

No.	PLATE.		PRICE.		No.	PLATE.		PRICE.
			Plain.	Bronzed.				
1	1	Garden Seat, . . . . .	7.50	9.00	39	3	Mantel Bracket, . . . . .	.30
2	1	" " . . . . .	7.00	8.50	40	3	" " . . . . .	.50
3	1	Battlement Bracket, . . . . .	9.50		41	3	Window " . . . . .	.70
4	1	Brush Scraper, . . . . .	1.40		42	3	Mantel Slab, O. G. edge, 2' 10" X 9" . . . . .	1.25
5	1	Smoke Flue, . . . . . @		per lb.			" " " " 2' 6" X 9" . . . . .	1.15
6	1	" " . . . . . @		per lb.	43	3	Gas Light Bracket, . . . . .	15.00
7	1	Carpet Winding Machine, . . . . .	9.00		44	3	" " . . . . .	5.00
8	1	Pan Scraper, . . . . .	1.20		45	3	" " . . . . .	16.80
9	1	Umbrella Stand, . . . . .	3.00	4.50	46	3	" " . . . . .	2.00
10	1	" " . . . . .	3.00	4.50	47	3	" " . . . . .	1.60
11	2	Cast Iron Columns, any thickness, as ordered; also, special lengths, by stopping off in the sand, . . . . . @			48	3	Gallery " . . . . .	6.00
12	2				49	4	Philadelphia City Pattern Lamp Post, . . . . .	15.00
13	2						Lantern and Glass, . . . . .	5.10
14	2						Lamp Tube, Stem, Cock, and Burner, . . . . .	2.25
15	2						Boxing for shipment, . . . . .	.95
16	2				50	4	Gallery Lamp Post, without Lantern, . . . . .	5.00
17	2				51	4	Park " " " " . . . . .	8.00
18	2				52	4	Gothic Column for Lantern, without Lantern, . . . . .	50.00
19	2				53	4	Park Lamp Post, without Lantern, . . . . .	8.00
20	2				54	4	Lamp Post, Morris, Tasker & Co.'s Pattern, . . . . .	12.00
21	2	Foundation Column, . . . . . @					Lantern and Glass, . . . . .	5.10
22	2						Lamp Tube, Stem, Cock, and Burner, . . . . .	2.25
23	2						Boxing for Shipment, . . . . .	.95
24	2				55	4	Plain Hitching Post, . . . . .	4.50
25	2				56	4	Horse Head Hitching Post, . . . . .	5.50
26	2				57	4	Octagon Hitching Post, . . . . .	6.00
27	2				58	4	Ornamental Column Hitching Post, . . . . .	4.50
28	3	Balcony Bracket, . . . . .		5.00	59	4	Cap for Awning Post, . . . . .	.82
29	3	Mantel " . . . . .		1.90			Base " " " . . . . .	2.04
30	3	Window " . . . . .		.70	60	4	Cap " " " . . . . .	1.86
31	3	Balcony " . . . . .		1.40			Base " " " . . . . .	1.00
32	3	Mantel " . . . . .		.60	61	4	Cap " " " . . . . .	1.40
33	3	" " . . . . .		1.30			Base " " " . . . . .	1.00
34	3	" " . . . . .		.70	62	4	Cap " " " . . . . .	1.46
35	3	" " . . . . .		.80			Base " " " . . . . .	.68
36	3	Mantel and Shelf Bracket, . . . . .		.50	63	4	Cap " " " . . . . .	1.90
37	3	" " " . . . . .		.60			Base " " " . . . . .	2.88
38	3	" " " . . . . .		.25	64	4	Cap " " " . . . . .	.90
							Base " " " . . . . .	.41



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS NINTH.


Plate 1.

No 7.




Park or Garden Seat.

No 2.




Park or Garden Seat.

No 3.




Battlement Bracket.

No 4.




Brush Scraper.

No 7.




Carpet Winding Machine.

No 5.



Smoke Flue.

No 6.



Smoke Flue.

No 9.



Umbrella Stand.

No 8.



Pan Scraper.

No 10.



Umbrella Stand.



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS NINTH.

Plate 2.

## CAST IRON COLUMNS





[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.


10<sup>th</sup> EDITION

CLASS NINTH.

Plate 3.




*Balcony Bracket*



*Balcony Bracket.*




*Shelf Bracket.*




*Balcony Bracket.*




*Shelf Bracket.*




*Mantel Bracket.*



*Shelf Bracket.*




*Shelf Bracket.*



*Shelf Bracket.*




*Mantel Bracket.*



*Mantel Bracket.*



*Window Bracket.*




*Mantel Slab.*



*Mantel Bracket.*



*Gas Light Bracket.*



*Gas Light Bracket.*




*Gas Light Brackets*



*Gas Light Brackets*



*Gas Light Bracket.*



*Gas Light Bracket.*



[BLANK PAGE]



CCA




# MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.

10<sup>th</sup> EDITION

CLASS NINTH.

Plate 4





[BLANK PAGE]



CCA



## CANE MILL.

To extract the juice from the cane three cast-iron horizontal rollers are generally used, which have over the vertical rollers the advantage of being fed and worked more easily and smoothly.

These rollers are made of different sizes, to suit the capacity of the different mills.

The two lower rollers have edges, to keep the cane from falling off sideways.

On the shaft of the rollers are cog-wheels, to turn all the rollers at the same time.

On the side of the mill where the cane is put in, there is a space between the rollers of  $\frac{3}{4}$  to  $\frac{7}{8}$  of an inch; while on the other side, the rollers almost touch each other.

The greatest velocity with which the circumference of the rollers revolves is about ~~ten~~ <sup>18</sup> feet per ~~second~~ <sup>minute</sup>.

The cane is carried to the mill by a cane conductor, which is from 60 to 80 feet long, and sometimes still longer. The bagass is taken away by a movable platform of the same construction.

The juice gathers on the bed-plate and runs into a tank, from which it has to be pumped as quickly as possible into the defecators.

## MOLINO DE CAÑAS.

Para extraer el jugo de la caña, se usan generalmente tres rollos ó cilindros horizontales de hierro colado, los cuales agarran y machacan las cañas con mas facilidad y regularidad que los cilindros verticales.

Los cilindros son de tamaños diferentes segun el caso. <sup>o' molduro</sup>

Los dos cilindros inferiores tienen un borde levantado á cada extremidad á fin de impedir las cañas de alejarse del molino.

Sobre los ejes de los cilindros se encuentran ruedas de encaje para moverlos todos al mismo tiempo.

Por el lado, por donde las cañas vienen deslizandose hácia el aparato, la distancia entre los cilindros es de  $\frac{3}{4}$  á  $\frac{7}{8}$  de una pulgada, mientras, al otro lado, casi se tocan los cilindros.

La mayor velocidad de los cilindros en su circunferencia es de ~~10~~ <sup>18</sup> piés, poco mas ó ménos, por ~~segundo~~ <sup>minuto</sup>.

Se lleva la caña al molino por medio de un conductor de caña, el cual tiene unos 60 ó 80 piés de largo, y algunas veces aun mas. El bagazo se lleva afuera mediante una plataforma móvil de una construccion análoga al conductor de caña.

El jugo ó guarapo cayendo sobre la cama del aparato corre en un tanque, ó recipiente de donde se ha de sacar por una bomba lo mas pronto que sea posible para llevarse en las defecadoras.

## MOINHO DA CANNA.

Para extrair o succo da canna se usa geralmente tres cilindros horizontaes de ferro fundido, os quaes tem sobre os cilindros verticaes a vantagem de ser fornecidos e trabalhados com mais facilidade e suavidade.

Estes cilindros se fazen de diferentes tamanhos segúndo a capacidade dos diferentes moinhos.

Os dois ultimos cilindros tem molduras para não deixar cair a canna d'os lados.

Sobre o eixo d'os cilindros ha rodas dentadas para girar todos elles a hum mesmo tempo.

Da banda do moinho de adonde se pon a canna ha hum espaço entre os cilindros de  $\frac{3}{4}$  a  $\frac{7}{8}$  de pollegada e d'outra banda os cilindros quasi tocaõ hum a outro.

A mais grande velocidade com que a circonference d'os cilindros revolve he cerca de ~~10~~ <sup>18</sup> pes por ~~segundo~~ <sup>minuto</sup>.

A canna he conducida a o moinho por hum conductor que he de 60 a 80 pes de comprimento e algumas veces ahinda mais comprido. O bagaço se remove por huma plataforma movibel da mesma construcção.

O succo se recolhe sobre a calha de baixo e passa entre hum tanque do qual precisa bombarse entre os defecadores.

## MOULIN A CANNES.

Pour extraire le jus de la canne, on fait usage généralement de trois rôles ou cylindres en fonte horizontaux, qui offrent le double avantage d'une alimentation plus facile et d'un fonctionnement plus régulier que les cylindres verticaux.

Ces cylindres sont de différentes dimensions selon les besoins de l'exploitation.

Les deux cylindres inférieurs ont un rebord à chaque extrémité, afin d'empêcher que les cannes ne tombent de côté.

Sur les axes des trois cylindres se trouvent des roues d'engrenage qui les font mouvoir tous en même temps.

Du côté où la canne arrive pour s'engager dans l'appareil, l'espace entre les cylindres est de  $\frac{3}{4}$  à  $\frac{7}{8}$  d'un pouce, tandis que de l'autre côté, les cylindres se touchent presque.

Le mouvement de révolution de la circonférence des cylindres, à son maximum, est d'environ ~~10~~ <sup>18</sup> pieds par ~~second~~ <sup>minute</sup>.

Les cannes sont amenées par une porteuse ou tablier sans fin, généralement de 60 à 80 pieds de long, mais parfois d'une longueur encore plus considérable. La bagasse est enlevée par un tablier mobile analogue au précédent.

Le vesou tombe sur la table qui supporte l'appareil et coule ensuite dans un réservoir d'où il faut le pomper le plus tôt possible et le faire passer dans les défécateurs.

## MUEHLE.

Zur Gewinnung des Saftes dienen meistens drei horizontal liegende Walzen, die das Rohr am bequemsten und regelmaessigsten einbringen lassen. Die gusseisernen Walzen haben verschiedene Durchmesser je nach der zu vollbringenden Arbeit. Die zwei untern sind mit Raendern versehen damit das Rohr nicht seitwaerts entweichen kann.

An den Achsen der Walzen sind in einander greifende Zahnraeder.

Die Walzen an der Seite, wo das Rohr zuerst eintritt haben einen Zwischeraum von  $\frac{3}{4}$  bis  $\frac{7}{8}$  Zoll, wohingegen an der andern Seite sich die Walzen fast beruehren.

Fuer die beste Drehungs geschwindigkeit an der Peripherie der Walzen wird ~~10~~ <sup>18</sup> Fuss in der ~~Secunde~~ <sup>minute</sup> angegeben.

Das Rohr wird durch einen Cane Conductor, der 60 bis 80 auch mehr Fuss lang ist zur Muehle gebracht und der Rueckstand oder die Bagasse wird durch eine aehnliche sich fort bewegende Platform von der Muehle entfernt.

Der Saft sammelt sich an der Bodenplatte und fliesst in einen Behaelter aus dem derselbe so schnell als moeglich zu den Defekatoren oder Scheidepfannen gepumpt wird.



[BLANK PAGE]




CCA



**MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.**  
**CLASS ELEVENTH.**

**MILL, DOUBLE GEAR & ENGINES  
 WITH CANE & BAGGASS CARRIER.**



**MORRIS, TASKER & CO.**

**PASCAL IRON WORKS,  
 PHILADELPHIA,  
 PENN'A.**



**TASKER IRON WORKS,  
 NEW CASTLE,  
 ON DELAWARE.**

*Chas. Frankenhoff, Engineer.*

*L. Hagg Lith Phila.*




[BLANK PAGE]



CCA



COPPER DEFECATORS WITH CAST IRON JACKET.




MORRIS, TASKER & CO.

PASCAL IRON WORKS,  
PHILADELPHIA,  
PENNA.


L. Haugbult Phila.

TASKER IRON WORKS,  
NEW CASTLE,  
ON DELAWARE.


Chas. Frankenhoff, Engineer




Waste-Water Valve



Steam Valve



Discharge Lock



Discharge Nozzle



[BLANK PAGE]




CCA



**MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.**  
**CLASS ELEVENTH.**

**FILTERERS.**



**MORRIS, TASKER & CO.**

**PASCAL IRON WORKS,  
 PHILADELPHIA,  
 PENN'A.**

*L. Henry Lith. Phila.*

**TASKER IRON WORKS,  
 NEW CASTLE,  
 ON DELAWARE.**

*Chas. Franckenhoff, Engineer.*



[BLANK PAGE]





CCA



**MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.**  
**CLASS ELEVENTH.**

**SUGAR BOILING APPARATUS**  
**WITH RILLIEUX EVAPORATORS.**





**MORRIS, TASKER & CO.**  
**PASCAL IRON WORKS,**  
**PHILADELPHIA,**  
**PENN'A.**  
*L. Hagg Lith Phil'a*

**TASKER IRON WORKS,**  
**NEW CASTLE,**  
**ON DELAWARE.**  
*Chas. Franckenhoff, Engineer.*



SUGAR BOILING APPARATUS  
WITH RILLIEUX EVAPORATORS.



MORRIS, TASKER & CO.

TASKER IRON WORKS,  
NEW CASTLE,  
ON DELAWARE.  
Spec. Greenleaf & Co. Engineers.



PASCAL IRON WORKS,  
PHILADELPHIA,  
PENNA.  
L. Brugg & Co. Eng'rs.



### STRIKE PAN.

In many cases, the last evaporation takes place "in vacuum," with considerably less pressure. A quicker evaporation and higher condensation are thus obtained with a reduced temperature, and by those means the juice is protected against the dangerous effects of a high degree of heat.

The rapid evaporation at a low temperature gives a better crystallization and lessens the disadvantageous influence of remaining coloring substances.

---

### CALDERA O TACHO DE PUNTO.

Muy á menudo, se hace la ultima evaporacion "en el vacío," bajo una presion muy reducida. Entónces la temperatura está mas baja, la evaporacion mas rápida, la condensacion mas completa y se halla el jugo resguardado de las malas influencias que ejerce una temperatura muy alta.

Mediante la rapidez de la evaporacion y la baja temperatura se logra una cristalización superior y quedan disminuidos los perniciosos efectos que podrian resultar de las materias colorantes mezcladas con el jugo.

---

### TAXO DE PONTO.

Em muitos casos a ultima evaporação se faz no vacuo com muito menos pressaõ. Assim se obtem huma evaporação mais prompta e huma condesação mais alta com huma tempertura mais baixa e por estes meios o sùcco é protegido contra os effeitos perigosos d'altos graos de calor.

A evaporação rapida com huma temperatura baixa da melhor cristalização e diminue a influencia desvantajosa das substancias colorantes que se quedaõ.

---

### BATTERIE OU CHAUDIERÈ A CUITE.

Dans un grand nombre de cas, la dernière évaporation s'effectue "dans le vide," sous une pression considérablement réduite. La température est alors plus basse, l'évaporation plus rapide, la condensation plus complète, et le jus se trouve à l'abri des inconvénients qui résultent d'une température élevée.

Grâce à la rapidité de l'évaporation dans ces conditions, on obtient une cristallisation supérieure et l'on a moins à craindre les pernicious effets des matières colorantes qui pourraient se trouver encore dans le jus.

---

### STRIKE PFANNE.

Meistens findet die letzte Abdampfung im Vacuum unter vermindertem Druck statt, weil die hier zu erlangende-Verminderung der Temperatur durch rasche Verdampfung bei der gesteigerten Concentration des Saftes denselben gegen den nachtheiligen Einfluss einer hoehern Temperatur shuetzt, die rasche Verdampfung bei niedrigerer Temperatur erhaelt die Crisallisationsfaehigkeit des Zuckers und vermindert den nachtheiligen Einfluss der noch vorhandenen Verunreinigungen.



[BLANK PAGE]




CCA



MORRIS, TASKER & CO.'S ILLUSTRATED CATALOGUE.  
CLASS ELEVENTH.

STRIKE PAN.




MORRIS, TASKER & CO.  
PASCAL IRON WORKS,  
PHILADELPHIA,  
PENN'A.



TASKER IRON WORKS,  
NEW CASTLE,  
ON DELAWARE.  
Chas. Franckenhoff, Engineer.



STIRRED PAIL.




PASCAL IRON WORKS,  
PHILADELPHIA,  
PENNA.

MORRIS, TASKER & CO.,  
TASKER IRON WORKS,  
NEW CASTLE,  
ON DELAWARE.



**MORRIS, TASKER & CO.'S ILLUSTRATED CATALOGUE.**  
**CLASS ELEVENTH.**

**WET VACUUM ARRANGEMENT.**



**MORRIS, TASKER & CO.**

**PASCAL IRON WORKS,**  
**PHILADELPHIA,**  
PENNA.

*L. Hagg Lith Phil.<sup>a</sup>*




**TASKER IRON WORKS,**  
**NEW CASTLE,**  
ON DELAWARE.

*Chas. Franckenhoff, Engineer.*



WET VACUUM AIR-BRAKE SYSTEM.



MORRIS, TASKER & CO.  
TASKER IRON WORKS,  
NEW CASTLE,  
ON DELAWARE.  
SPECIAL PATENT OFF. ENGINEERS.




PASCAL IRON WORKS,  
PHILADELPHIA,  
PENNA.  
L. H. H. & S. P. H. & S.



**MORRIS, TASKER & CO.'S ILLUSTRATED CATALOGUE.**  
**CLASS ELEVENTH.**

**WET VACUUM ARRANGEMENT.**



**MORRIS, TASKER & CO.**

**PASCAL IRON WORKS,**  
**PHILADELPHIA,**  
PENN'A.

*L. Hagg Lith Phil<sup>a</sup>*




**TASKER IRON WORKS,**  
**NEW CASTLE,**  
ON DELAWARE.

*Chas. Franckenhoff, Engineer*



WET VACUUM ARRANGEMENT.



MORRIS, TASKER & CO.  
TASKER IRON WORKS  
NEW CASTLE  
ON DELAWARE  
Geo. F. Mendenhall, Engineer



PASCAL IRON WORKS,  
PHILADELPHIA  
PENNA.  
J. H. B. 1877



**MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.**  
**CLASS ELEVENTH.**


**MORRIS, TASKER & CO.**

**PASCAL IRON WORKS,  
 PHILADELPHIA,  
 PENN'A.**

**TASKER IRON WORKS,  
 NEW CASTLE,  
 ON DELAWARE.**

**Ch. Franckenhoff, Engineer.**


**DRY VACUUM ARRANGEMENT**





MORRIS, TASKER & CO.  
PASCAL IRON WORKS,  
PHILADELPHIA,  
PENNA.  
TASKER IRON WORKS,  
NEW CASTLE,  
ON DELAWARE.  
G. Frankfort, Engineer.

DRY VACUUM ARRANGEMENT





## DESCRIPTION OF SUGAR BOILING MACHINERY.

The Cane Juice coming from the mill is pumped into the tank A, passing from there into the clarifiers B (the bottoms of which are covered with horizontal pipes, so arranged as to receive either exhaust or direct steam), where, after adding the lime-water, the Cane Juice is boiled to 15° Beaumé, and being carefully skimmed, is run off into tank C, which holds enough to fill evaporators D, the bottom being covered with a coil sufficiently large to heat the Cane Juice to the boiling point, when it is again carefully skimmed and conducted into a tank below the ground floor, being pumped from there into bag-filter G, which delivers clean syrup into tank H. From here it is drawn by vacuum into the Strike Pan, where it is boiled (in vacuum) up to the striking point, then carried into the Strike Heater, where it is allowed a sufficient time for cooling, after which it is passed through the Centrifugal Machines, which are below the Heater.

The boiling in the Vacuum Pan and Clarifiers is materially assisted by the exhaust steam from the Engine. The Furnaces under the Boilers are arranged to burn Bagass, which makes a very economical and intense heat. The Defecators and Evaporators being in duplicate gives an opportunity of cleaning one while the other is boiling.

## APARATO DE COCER AZÚCAR.

El jugo de las cañas ó guarapo viniendo del molino se lleva por medio de una bomba en el Tanque, Pila, ó Recipiente A, pasando despues en las Clarificadores B, cuyos fondos están cubiertos con tubos horizontales ordenados para recibir sea el vapor directo de la caldera, sea el vapor que ya ha servido en la máquina. Despues de añadir el agua de cal, se concentra el jugo hasta 15° Beaumé. Se quita entonces cuidadosamente la espuma y se conduce el caldo en el Recipiente ó Tanque C, de una cabida suficiente para llenar las Evaporadoras D, el fondo de aquellas estando cubierto con una Serpentina ó Gusano de tamaño bastante grande para calentar el jugo hasta el punto de ebullicion. La espuma se quita otra vez cuidadosamente y pasa el caldo en un Tanque debajo del piso, de donde le lleva una bomba en el Filtro G, provisto de sacos, el que entrega sirop claro ó meladura en el Tanque H. De acá, se saca por el vacío y pasa en la caldera ó Tacho de Punto, en el que se cuece en el vacío hasta el punto. Entonces se lleva a la Calentadora en donde se deja hasta que se enfrie, pasando despues por las Maquinas Centrifugas, que se encuentran debajo de la Calentadora.

La evaporizacion en el vacío y en las Clarificadoras es materialmente ayudada por el vapor que sale de la maquina. Los hornos debajo de las calderas de vapor estan ordenados para quemar Bagazo, que produce un fuego muy intenso y muy economico. El aparato conteniendo dos Defecadoras y dos Evaporadoras, se puede limpiar una, mientras se usa la otra.

## DESCRIÇÃO DA MAQUINA PARA FERVER ASSUCAR.

O sugo da canna vindo do moinho se bomba no tanque A, passando depois nos clarificadores B (os fundos dos quaes estão cobertos com tubos horizontaes arranjados de maneira que recebaõ o vapor dereito da caldeira ou o exhausto). Depois de ajuntar agua de cal o sugo da canna se ferve ate a 15° de Baumé, e sendo espumado com cuidado passa-se no tanque C, que contem bastante por encher os evaporadores D, os fundos dos quaes sendo cobertos com huma cobra (coil) bastante grande para queantar o sugo a o ponto de fervidura, quando se espuma outra vez com cuidado e se conduz em hum tanque de baixo do piso baixo, bombandose então no sacco de filtro G o qual entrega o xarope limpo no tanque H. D'aqui se força por meio de vacuo no taxo de ponto, ahonde se ferve (em vacuo) ate o ponto; passa depois no queantador de ponto ahonde se le da tempo necessario para enfriarse, passandose depois entre as maquinas centrifugas que são de baixo do queantador.

A evaporação no taxo do vacuo e clarificadores vem assistido materialmente com o vapor exhausto da maquina. Os fornos de baixo das caldeiras estando arranjados para quemar o bagaço daõ hum calor intenso e muito economico. Os Defecadores e evaporadores sendo duplicados daõ o meio de limpar hum em quanto outro ferve.

## APPAREIL DE FABRICATION DU SUCRE.

Le jus de cannes ou vesou arrivant du moulin est amené par le moyen d'une pompe dans le bassin ou réservoir A, d'où il passe dans les Défécateurs B. Le fond de ces Défécateurs est garni de tubes placés horizontalement et disposés de façon à recevoir soit la vapeur d'échappement de la machine soit la vapeur directe de la chaudière. Le jus de cannes arrivé dans les Défécateurs y recoit la lessive d'eau de chaux et est soumis à une évaporation qui le porte à 15° Beaumé; il est alors écumé avec soin et dirigé dans le bassin ou réservoir C, lequel est de capacité suffisante pour remplir les Evaporateurs D. Le fond des Evaporateurs est garni d'un serpentín de dimensions assez grandes pour chauffer le vesou jusqu'au point d'ébullition. Le jus ou vesou est alors écumé de nouveau avec soin et conduit dans un réservoir à un niveau inférieur, d'où il est pompé dans le Filtre G, garni de sacs, qui fournit du sirop épuré au Bassin H. De là le sirop est amené par le vide dans la "Batterie" où il est concentré dans le vide jusqu'au point de cuite. La cuite arrive ensuite dans le Réchauffoir d'où, après un temps nécessaire pour refroidir, elle passe dans les Centrifuges placés au dessous du Réchauffoir.

L'évaporation dans les Défécateurs et dans la chaudière à vide est considérablement aidée par la vapeur d'échappement de la machine. Les fourneaux sous les chaudières à vapeur sont disposés pour la combustion de la Bagasse, qui fournit une chaleur très intense et économique.

Il y a deux Défécateurs et deux Evaporateurs, ce qui permet de nettoyer l'un de ces appareils pendant que le travail de fabrication se poursuit avec l'autre.

## BESCHREIBUNG VON ZUCKERKOCH MASCHINERIE.

Der Zuckerrohrsaft von der Muehle kommend sammelt sich in Behälter A, leuft von da in die Clarifier B deren Boeden mit horizontale Heizroehren bedeckt sind, welche mit direktem oder abgehenden Dampf der Maschinen geheizt werden koennen, hier wird Kalkwasser zu gesetzt und der Rohrsaft bis auf 15° Beaumé eingedickt und sorgfaeltig abgescheumt und in den Behälter C abgelassen, der genug haelt, einen Evaporator D zu fuellen, deren Boeden mit kupferne Wuerme bedeckt sind, die gross genug sind den Saft auf den Kochpunkt zu erhalten, hier wird wieder sorgfaeltig abgescheumt und fliesst dann in einen Behälter unter den Boden von welchem aus in die Sackfilter G gepumpt wird und in den Syrupbehälter H abfliesst. Von hier wird der Syrup durch das Vacuum in die Strickpfanne gezogen und fertig zu Zucker gekocht; dann in einen Strickheater abgelassen, nach einiger Zeit, die noethig ist zur Abkuehlung wird der Zucker durch die Centrifugen, die unter demselben sind, von der Molasses getrennt.

Das Kochen in der Vacuumpfanne und Clarifiers geschieht hauptsaechlich mit abgehendem Dampf der Maschinen und Dampfpumpen. Die Kesselfeuerung ist eingerichtet den Abfall, des von der Muehle kommenden Rohrs zu verbrennen. Die Defecatoren und Evaporatoren sind doppelt um Gelegenheit zur Reinigung zu geben, wenn der andere zum kochen verwendet wird.



[BLANK PAGE]




CCA



**MORRIS, TASKER & CO'S ILLUSTRATED CATALOGUE.**  
CLASS ELEVENTH.

**SUGAR BOILING APPARATUS  
MILL, GEARING & ENGINE.**



*L. Haug Lith. Phila.*

**MORRIS, TASKER & CO.**

**PASCAL IRON WORKS,**

**PHILADELPHIA,**

**PENNA.**

*L. Haug Lith. Phila.*

**TASKER IRON WORKS,**


**NEW CASTLE,**

**ON DELAWARE.**

*Chas. Franckenhoff, Engineer.*



PHILADELPHIA  
BENNY  
TASKER IRON WORKS  
NEW CASTLE  
ON DELAWARE  
MORRIS, TASKER & CO.



WILT-GEARING & ENGINE  
SUGGAR BOTTLING MACHINES



## HERSEY'S PATENT SUGAR GRANULATOR.

We desire to call your attention to our apparatus for granulating sugar, now in operation in many of the refineries of New England, New York, Pennsylvania, Peru and other sections, and pronounced by the refiners a very valuable invention.

The cuts accompanying this show an elevation in perspective, a longitudinal section through the centre of the machine, and a transverse section on line A B, seen in the longitudinal section.

The heating cylinder C, which is fastened inside of the conveyor-cylinder D, and revolves with it, is filled with steam through the pipe E in one end, and the water of condensation is delivered from the opposite end, through the pipe shown at F, so that the heating cylinder is always full of steam.

The sugar is fed into one end through a spout G, by a set of rolls placed above the machine, and by the lifting shelves H H H H, on the inside of the outer cylinder, is carried up and dropped in a continuous shower upon the heating cylinder, and rolls off by the rotation of the machine, to be again carried up, working forward to the opposite end by the inclination of the apparatus, and is there delivered into the screen, for separating into the different grades.

The heater-cylinder is put central within the conveyor-cylinder, and is adjusted and secured by means of the adjusting screws I I I I. The conveyor-cylinder is made of iron; the heater is constructed of steel plate. The conveyor-cylinder is made 23 feet long and 6 feet in diameter, with the heater-cylinder 20 feet long and 36 inches in diameter, and makes five revolutions per minute. The striker shown at K is for the purpose of passing off any sugar that may adhere to the cylinder when first entering the machine, and is operated by the cams L L. The machine is rotated by means of gear M upon the outside of conveyor-cylinder, driven by pinion on the shaft N.

The current of air constantly passing through the machine, carries off the moisture from the sugar through the pipe O.

One of the important features of the machine is, that the sugar, being delivered from the end into which the cold air is passing, is cool, so that it does not cake, and can be immediately barreled, and will not cause the barrels to shrink.

The sugar being granulated or dried, not so much from extreme heat, but by the moisture being constantly carried from the machine, is brought out clear and white, so that the sugar made from our granulator is whiter than sugar made by any other process.

The machine will granulate much more than any other before used, and the quality of the sugar is greatly improved.

## ESTUFA PARA AZUCAR.

### O SEA SECADOR DE AZÚCAR CON PRIVILEGIO DE "HERSEY."

Deseamos llamar la atencion sobre nuestro aparato de secar azúcar que ahora funciona en la mayor parte de las refinarias de Nueva-Inglaterra, en Nueva-York, en Cuba, etc., y se califica por los refinadores de azúcar como una de las invenciones mas útiles para los fabricantes y refinadores de azúcar.

El dibujo que acompañamos representa la máquina con un corte longitudinal por su centro y un trasversal por la linea A B vista a lo largo.

El cilindro calentador C, que se encuentra adherido al interior del cilindro conductor D y se mueve con él, se llena de vapor por medio del tubo E por una cabeza y el agua de condensacion sale por la estremidad opuesta por el tubo marcado F, de modo que el cilindro calentador está siempre lleno de vapor.

El azúcar se introduce por uno de los extremos por una canal G, despues de haber pasado por entre dos rolletes colocados cerca del orificio superior de la canal, á fin de pulverizar el azúcar. Mediante las paletas elevadoras H H H H, que se ven en el interior del cilindro exterior, es elevado y lanzado el azúcar en forma de lluvia sobre el cilindro secador, y arrojado fuera por el movimiento de rotacion de la máquina, para ser nuevamente llevado arriba caminando en direccion del otro extremo, consecuencia del plano inclinado del aparato, cayendo ahi sobre un givé para separar las diferentes clases.

El cilindro secador es colocado en el centro del cilindro conductor, y afirmado por medio de tornillos I I I I. El cilindro conductor está hecho de hierro; el secador, de acero. El cilindro conductor tiene 23 pies de largo por 6 de diametro, con el cilindro secador de 20 pies de largo por 30 pulgadas de diametro, y hace cinco revoluciones por minuto. El martillo marcado K tiene por objeto el desprender todo el azúcar que pudiera adherirse al cilindro, cuando entra fresco, y esto se efectua por medio del mecanismo L. La maquina se pone en movimiento de rotacion por la rueda dentada M colocado al exterior del cilindro secador, movida por un piñon puesto en el eje N.

Una corriente de aire atravezando continuamente la máquina por el tubo O lleva fuera la humedad que resulta del azúcar.

Una de las ventajas mayores de la máquina es que, saliendo el azúcar por el extremo donde entra el aire frio, no forma bollos y puede envasarse inmediatamente sin que se recoja en el vaso.

Secándose el azúcar no tanto por el exceso de calor, como por la espulsion constante de la humedad fuera de la máquina, sale limpio y blanco, de tal modo que el azúcar secado por nuestro secador es mas blanco que otro secado por cualquier otro sistema.

Como la accion sobre el azúcar es inmediata á su entrada en el cilindro, no se pega en lo mas mínimo y por consiguiente no recibe daño ni se quema, como sucede con frecuencia con las otras máquinas; la ventilacion es tan bien combinada que el polvo no daña absolutamente. La fuerza que requiere la máquina para su marcha es ménos de la de un caballo, y la presion de vapor que necesita el cilindro secador es entre veinte y treinta libras.

La maquina seca fácilmente treinta barriles ó sea treinta veces doscientas libras por hora, ó cinco veces mas que la mejor máquina en uso hasta ahora, y la calidad muy mejorada.

Reclamamos para nuestras máquinas las ventajas siguientes: que seca seis mil libras de azúcar por hora ó sea quince cajas, entrega este frio, blanco y limpio, ahora manipulacion, espacio y tiempo, da ménos desperdicios y azúcar mejor granulado que otra máquina cualquiera usada hasta el dia.

## ESTUFA PARA ASSUCAR.

### O SECCADOR D'ASSUCAR PATENTIADO.

Desejamos chamar a attencao sobre o nosso apparatus para seccar o assucar que ja funciona na maior parte das refinarias da Nova Inglaterra de Nova York e nos engenhos de Cuba e desde ja qualificado como huma das invenções mais uteis para os fabricantes e refinadores d'assucar.

O desenho adjunto representa a maquina cortada longitudinalmente no centro e transversalmente por a linha A B vista a o comprido.

O cilindro quentador C que se encontra pegado no interior do cilindro conductor e que gira com elle se enche de vapor por meio do tubo E por huma cabeça e a agua da condensação sae na extremidade opposta por o tubo F de modo que o cilindro quentador seja sempre cheio de vapor.

O assucar se introduz por huma das extremidades por o canal G depois de haver passado entre dois rolletes collocados cerca do orificio superior do canal a fim de pulverizar o assucar mediante as palas elevadoras H H H H que se vêm no interior do cylindro exterior. O assucar vem levantado e lançado em forma de chuva sobre o cylindro seccador e lançado fora com hum movimento de rotacão da maquina para ser de novo levantado andando na direcção da outra extremidade em consequencia do plano inclinado do apparatus caindo sobre huma joeira para separar as diferentes classes.



O cylindro seccador está collocado no centro do conductor e pegado por meio dos parafusos I I I I. O cylindro conductor é de ferro e o seccador d'ago. O cylindro conductor tem 23 pes de comprido por 6 de diametro. O seccador 20 pes de comprido por 30 pollegadas de diametro e fazem cinco revoluções por minuto. O martello K faz cair o assucar que fique pegado a o cylindro quando ahinda está fresco e este se effectua por meio do mecanismo L. A maquina se pone em movimento de rotação com a roda dentada M collocada a o exterior do cylindro seccador e movida por os dentes postos no eixo N.

Huma corrente d'ar atravessando continuamente a maquina por o tubo O destrue a humidade que deixa o assucar.

Huma das maiores vantagens da maquina é que o assucar saindo da extremidade ahonde entra o ar frio não forma bolas e se pode por immediatamente em vacilla.

O assucar se secca não tanto por excesso do calor como por a expulção constante da humidade fora da maquina, e sae limpo e branco, de tal maneira que o assucar seccado por o nosso seccador é mais branco que o seccado por qualquer outro sistema.

Como o processo sobre o assucar principia na sua entrada no cylindro, não se pega e por consequencia não recebe danmo nenhum como succede frequentemente com as outras maquinas; a ventilação e tão bem combinada que o pó não faz absolutamente mal nenhum, a força que precisa a maquina e menos que hum cavallo e a pressão que precisa o cylindro seccador é entre 20 e 30 libras.

A maquina secca facilmente 30 barris, igual a treinta vezes 200 libras por hora ou cinco vezes mais que a melhor maquina que se usa ate agora e de qualidade superior.

As nossas maquinas possuem as seguintes vantagens. Seccaõ 6000 libras d'assucar por hora e produzem este frio branco e limpo com menos manipulação, espaço e tempo, percas menores e assucar melhor que qualquer outra maquina ate agora conhecida.

## APPAREIL POUR LA DESSICATION DU SUCRE.

(BREVET DE HERSEY).

Nous désirons recommander à votre attention notre appareil pour la dessication du sucre.

Cet appareil fonctionne aujourd'hui dans un grand nombre de Raffineries de la nouvelle Angteterre, de New-York, de la Pensylvanie eto anisi que dans les sucreries des Antilles. De l'avis unanime des personnes compétentes en la matière c'est une invention de haute utilité pour les Rafineurs et les Fabricants de sucre.

La gravure qui accompagne la circulaire represente une coupe ou section longitudinale par le centre de l'appareil, et une section transversale selon la ligne désignée par les lettres A, B, dans la section longitudinale.

Le cylindre C, qui est fixé dans l'intérieur du cylindre D, et le suit dans son mouvement de révolution, se remplit de vapeur au moyen du tube E adapté à l'une de ses extrémités; l'eau qui résulte de la condensation s'écoule, à l'extrémité opposée, par le tube F; le cylindre C, est ainsi toujours rempli de vapeur. Le sucre est introduit, à l'une des extrémités, par un conduit G, après avoir passé entre deux petits rôles ou cylindres placés à l'orifice du conduit G, et ayant pour objet de pulvériser le sucre.

Les palettes ou lames horizontales H H H H, sur la circonférence interne du cylindre B, saisissent le sucre au passage et le font tomber sur le cylindre C, d'où il est rejeté par le mouvement de rotation, pour être ramené de nouveau, puis rejeté encore par le même mécanisme. Il s'achemine ainsi vers l'extrémité opposée par l'effet de l'inclination de l'appareil et tombe sur un tamis qui sépare les différentes qualités.

Le cylindre à vapeur est placé au centre du cylindre extérieur et y est assuré et fixé au moyen des vis I I I I. Le cylindre extérieur est en fer, a 23 pieds de long, 6 pieds de diamètre, et fait 5 revolutions par minute. Le cylindre intérieur C, est en acier et a 20 pieds de long, et 36 pouces de diamètre.

Le mécanisme K a pour objet de détacher le sucre qui pourrait, en arrivant, adhérer au cylindre D. C'est un bras K qui est soulevé au passage par les projections L L et frappe, en retombant, sur le cylindre. Le mouvement de rotation est transmis à l'appareil par l'engrenage M, à l'extérieur du cylindre, et dans lequel s'engage le pignon situé sur l'axe N.

Un courant d'air traverse constamment l'appareil par le tube O et enlève l'humidité causée par le sucre.

Un avantage important, c'est que le sucre sortant par l'extrémité par laquelle entre le courant d'air froid, arrive au dehors dégagé de toute chaleur et peut être mis immédiatement en barrils sans craindre qu'il s'y affaisse ou qu'il s'y forme en pâte.

La granulation ou dessication s'opérant moins par l'excès de chaleur que par l'expulsion continuelle de toute humidité, le sucre est blanc et pure.

Le produit de notre appareil l'emporte en blancheur sur les résultats de tout autre procédé.

Le travail de dessication commence aussitôt après l'arrivée du sucre; on n'a donc pas à craindre qu'il adhère aux parois et qu'il s'y brûle.

La force motrice nécessaire n'est que d'environ un cheval-vapeur. La pression de la vapeur dans le cylindre C est de 20 à 30 livres. On peut aisément effectuer la dessication de trente barrils ou trente fois deux cents livres par heure, résultats cinq fois supérieurs à ceux de tout autre appareil aujourd'hui en exploitation.

## HERSEY'S PATENT ZUCKER GRANULATOR.

FABRIZIERT BY MORRIS, TASKER & CO.

Wir erlauben uns auf diesen Zucker granulier Apparat aufmerksam zu machen, der jetzt in so vielen Raffinerien von New England, New York, Pensylvanien, Peru und andere Laender in Gebrauch ist und von den Raffineurs als eine werthvolle Erfindung ausgegeben wird.

Die beifolgende Zeichnung zeigt eine perspectivische Ansicht und einen Laengendurchschnitt durch die Mitte der Maschine und Querschnitt an Linie A B sichtbar im Laengendurchschnitt.

Der Heizcylinder C welcher in dem bewegenden Cylinder D befestigt ist und sich mit diesem um seine Achse dreht ist vermittelst Rohr E an einem Ende mit Dampf-gefüllt und das kondensierte Wasser am andern Ende durch das Rohr F ausgeblasen, so dass der Heizcylinder immer voll Dampf ist.

Zucker wird fortwaehrend durch Kanal G eingefuellt in welchem ein paar Rollen angebracht sind, zwischen welchen der Zucker durchgeht und dann von den Schaufeln H H H H an der innern Seite des aeußern Cylinders auf den innern Heizcylinder in bestaendiger Schauer geworfen wird und bei der Umdrehung wieder herunter faellt und zuletzt auf ein Sieb kommt um in verschiedene Groessengrade vertheilt zu werden.


Der Heizcylinder ist central im bewegenden Cylinder angebracht und ist vermittelst verstellbaren Schrauben I I I I befestigt. Der bewegende Cylinder ist 23 Fuss lang und 6 Fuss Durchmesser, der Heizcylinder ist 20 Fuss lang und 36 Zoll Durchmesser, und macht 5 Umdrehungen per minute. Der Klopfbalken K, durch die Kaemme L L bewegt, hat den Zweck, etwa festklebenden Zucker beim Eintreten in den Cylinder durch seine Erschuetterung abzuschuettern. Die Maschine wird durch Zahnraeder M am aeußern bewegenden Cylinder und Pinion mit Shaft N herumgedreht.

Der bestaendige Luft durchzug der Maschine fuehrt die feuchte Luft durch das Rohr O ab. Eine besondere Eigenschaft der Maschine ist dass der Zucker an der Seite heraus kommt wo die kalte Luft eintritt somit kalt ist und nicht zusammen backt und sofort in Faesser verpackt werden kann, ohne dass sich die Dauben derselben zusammenziehen. Der nicht durch grosse Hitze, sondern durch fortwaehrendes Ableiten von Feuchtigkeit, granuliert und getrocknete Zucker, kommt klarer und weisser heraus als durch eine andere Operation fabrizierte.


Diese Maschine granu'iert viel mehr als jede andere die vorher in Gebrauch war und die Qualitaet des Zuckers ist sehr verbessert.



# HERSEY BROTHERS' SUGAR DRIER.



T. BEDGE. SC.



MORRIS, TASKER & CO.

TASKER IRON WORKS:

PASCAL IRON WORKS:

Philadelphia, Pa.

New Castle on Delaware.

CHARLES FRANKENHOFF, Engineer.



[BLANK PAGE]



CCA



[BLANK PAGE]



CCA



# DIFFUSION PROCESS

## FOR THE

# MANUFACTURE OF CANE SUGAR.

The Diffusion Process is founded on the principle or law of osmosis, by which two liquids of different density, separated by a membrane substance, will tend to pass through it and mingle with each other until an equality of density is established on both sides of the membrane.

The cane being cut into slices, each slice represents a porous vessel containing juice of a certain density, which during the operation is surrounded by water or juice of less strength, thus bringing the law into action and extracting the juice from the Cane. "Diffusion" deals with the closed cell and avoids the foreign and noxious elements crushed out of the lacerated cell by the roller process. Hence much less defecation is necessary.

The operation is as follows :

The Cane is cut into slices about one-eighth of an inch thick by revolving knives moved by an engine. Extractor No. 1 is then filled with cane while No. 2 is being filled and steam is let into the bottom until the whole mass is penetrated, then the steam is shut off and water let on from a tank overhead through the Heater *E* until the vessel is full, when it is tightly closed. No. 2 being filled with chips and duly steamed, water is let down from the tank through the Heater into No. 1, driving the liquid by hydrostatic pressure out of No. 1 into No. 2, through the connecting pipe which has in the mean time been opened. No. 3 is filled, steamed and charged with juice as above. When No. 4 is filled with chips water is let directly from the tank into No. 1, driving the juice which was in it through the Heater into No. 2, and from 2 to 3 and 3 to 4. Cold water into No. 1, and from No. 1 to 2, from No. 2 through the heater into No. 3, then directly into 4 and 5, and so on, care being taken to preserve the temperature of the last vessels filled at about 190° or 200° Fahrenheit. When the hot juice has passed through No. 7, it is sufficiently concentrated and discharged into the sugar house for subsequent treatment. No. 1 is now emptied, and No. 2 becomes the first vessel in the battery and the work goes on as before, there being always seven vessels working, one being emptied and two being refilled, so that practically, when the work is in full operation, as fast as one vessel is filled, a charge of concentrated juice goes into the sugar house, and one vessel with exhausted cane is emptied.

It is well to begin with hot water or juice to accelerate the process, but the subsequent diffusion may be made with cold juices.

Fig. 1, of sketch is a side elevation of a battery of ten Extractors with pipes and heaters.

Fig. 2, plan of Extractors and Pipes.

Fig. 3, Transverse section.

A. A. etc., represents a single battery of extractors, arranged in two rows. B is a trough for conveying the thick juice from the extractors to the sugar house for subsequent treatment. C, a trough for carrying off the wash water. D.D. are pipes connecting the bottom of the extractors with an overhead cold water reservoir, and a heater *E*, in such a way that it can be run directly to the extractors, or through the said heater when hot water is required. F is a pipe carrying thick juice from the extractors to the trough or canal B. G is a heater for heating the juice in case the latter is not of the proper temperature for the next vessel. H and I are pipes leading to and from the said heater, and connecting the extractors at the bottom through the pipes D/D', the inlet communication to heater being controlled by a valve *b* on the pipe H, and the outlet by a valve *c* on the pipe J.

A steam pipe *d* communicates with the bottom of vessel through the pipe D', and on the latter are valves *K* for waste from the bottom of the vessels into either the troughs B or C. The pipes and valves, as will be seen by referring to the drawing, are so arranged that the water or steam can be run in at the bottom of one extractor, and from the top of the same to the bottom of the next extractor, or through the heater to the next, when it is not of the required temperature, no stop being necessary; the juice also, after it has passed through the requisite number of vessels, can be run off to the trough from any one of the vessels. Thus the operation may be carried on continually and in succession, in all the diffusion stages, without interference for one with another, the water flowing from the reservoir through pipe D into and through Nos. 1, 2, 3, 4, 5, 6, 7, 8, 9 into 9 at the bottom, while the thick juice from No. 10 is escaping into the trough B.

Or one or more of the Extractors may be cut off for filling, and for matters to remain at rest while the others are in connection for progressive operations.







# DIFFUSION PROCESS

## FOR THE

# MANUFACTURE OF CANE SUGAR.

The Diffusion Process is founded on the principle or law of osmosis, by which two liquids of different density, separated by a membrane, will tend to pass through it and mingle with each other until an equality of density is established on both sides of the membrane.

The cane being cut into slices, each slice represents a porous vessel containing juice of a certain density, which during the operation is surrounded by water or juice of less strength, thus bringing the law into action and extracting the juice from the Cane. "Diffusion" deals with the closed cell and avoids the foreign and noxious elements crushed out of the lacerated cell by the roller process. Hence much less defecation is necessary.

The operation is as follows :

The Cane is cut into slices about one-eighth of an inch thick by revolving knives moved by an engine. Extractor No. 1 is then filled with cane while No. 2 is being filled and steam is let into the bottom until the whole mass is penetrated, then the steam is shut off and water let on from a tank overhead through the Heater E until the vessel is full, when it is tightly closed. No. 2 being filled with chips and duly steamed, water is let down from the tank through the Heater into No. 1, driving the liquid by hydrostatic pressure out of No. 1 into No. 2, through the connecting pipe which has in the mean time been opened. No. 3 is filled, steamed and charged with juice as above. When No. 4 is filled with chips, water is let directly from the tank into No. 1, driving the juice which was in it through the Heater into No. 2, and from 2 to 3 and 3 to 4. Cold water into No. 1, and from No. 1 to 2, from No. 2 through the heater into No. 3, then directly into 4 and 5, and so on, care being taken to preserve the temperature of the last vessels filled at about 190° or 200° Fahrenheit. When the hot juice has passed through No. 7, it is sufficiently concentrated and discharged into the sugar house for subsequent treatment. No. 1 is now emptied, and No. 2 becomes the first vessel in the series and the work goes on as before, there being always seven vessels working, one being emptied and two being refilled, so that practically, when work is in full operation, as fast as one vessel is filled, a charge of concentrated juice goes into the sugar house, and one vessel with exhausted cane is emptied.

It is well to begin with hot water or juice to accelerate the process, but the subsequent diffusion may be made with cold juices.

Fig. 1, of sketch is a side elevation of a battery of ten Extractors with pipes and heaters.

Fig. 2, plan of Extractors and Pipes.



Fig. 3, Transverse section.

A. A. etc., represents a single battery of extractors, arranged in two rows. B is a trough for conveying the thick juice from the extractors to the sugar house for subsequent treatment. C, a trough for carrying off the wash water. D.D. are pipes connecting the bottom of the extractors with an overhead cold water reservoir, and a heater E, in such a way that it can be run directly to the extractors, or through the said heater when hot water is required. F is a pipe carrying thick juice from the extractors to the trough or canal B. G is a heater for heating the juice in case the latter is not of the proper temperature for the next vessel. H and I are pipes leading to and from the said heater, and connecting the extractors at the bottom through the pipes D'D', the inlet communication to heater being controlled by a valve *b* on the pipe H, and the outlet by a valve *c* on the pipe J.


A steam pipe *d* communicates with the bottom of vessel through the pipe D', and on the latter are valves K for waste from the bottom of vessels into either the troughs B or C. The pipes and valves, as will be seen by referring to the drawing, are so arranged that the water can be run in at the bottom of one extractor, and from the top of the same to the bottom of the next extractor, or through the heater to the next, when it is not of the required temperature, no stop being necessary; the juice also, after it has passed through the requisite number of vessels, can be run off to the trough from any one of the vessels. Thus the operation may be carried on continually and in succession, in all the stages, without interference for one with another, the water flowing from the reservoir through pipe D into and through Nos. 1, 2, 3, 4, 5, 6, 7, 8, 9 into 9 at the bottom, while the thick juice from No. 10 is escaping into the trough B.

Or one or more of the Extractors may be cut off for filling, and for matters to remain at rest while the others are in connection with progressive operations.









be run on the same shaft, and the water flowing from the reservoir through pipe D into and through Nos. 1, 2, 3, 4, 5, 6, 7, 8, and into 9 at the bottom, while the thick juice from No. 10 is escaping into the trough B.

Or one or more of the Extractors may be cut off for filling, and for matters to remain at rest while the others are in connection for the progressive operations.



# PRICE LIST

FOR

MORRIS, TASKER & CO., LIMITED,

# ILLUSTRATED CATALOGUE.

CLASS TWELFTH.

FIRST EDITION, 1877.

CASTINGS, &c. FOR SIEMEN'S GAS-PRODUCER.

No.	PLATE.	PRICE.	No.	PLATE.	PRICE.
1	Siemen's Gas Producer and Parts shown in position,		14	2	
2	Hopper, . . . . .		15	} Binders, . . . . .	
3	Poker Plate, . . . . .		16		
4	Floor Plates, . . . . .		17		
5	Fire Plates, . . . . .		22	3	
6	Damper for Supply Flue, . . . . .		23	} Stoker Tools, . . . . .	
7	Sight Hole, . . . . .		24		
8	Bracket, . . . . .		25		
9	Door, . . . . .		26		
10	Safety Valve, . . . . .		26a		
11	Man Hole Ring and Cover, . . . . .		27		
12	" " " . . . . .		28		
13	" " " . . . . .		29		
	Taking down plates, . . . . .		30		
	Man Hole Plate and Cover, . . . . .		31		
			32	Grate Bar, . . . . .	
			33	False Grate Bar, . . . . .	

CASTINGS, &c. FOR SIEMEN'S GAS FURNACE.

No.	PLATE.	PRICE.	No.	PLATE.	PRICE.
18	3	Wall Box, . . . . .	43	Beam for Floor, . . . . .	
19		Gas Box, . . . . .	44	} Floor Plates, . . . . .	
20		Damper for Chimney Flue, . . . . .	45		
21		Roller, . . . . .	46		
34		Keystone, . . . . .	50		
35		Floor Column, . . . . .	51		
36		Draft Damper Column, . . . . .	52		
37		Air or Gas Valve Column, . . . . .	47	Truss Bracket, . . . . .	
38		Roller Plate, . . . . .	48	Chain Wheel, . . . . .	
39		Regulating Damper, . . . . .	49	Tie Rod Bracket, . . . . .	
40	4	Bed Plate for Furnace, . . . . .	53	Damper for cut-off, . . . . .	
41		Fore Plate, . . . . .	54	} Tie Rods, . . . . .	
42		Corner Binder, . . . . .	55		



CLASS TWELFTH.—*Continued.*

## ROTARY AND ADJUSTABLE ROTARY SLITTING SHEARS, PULLEYS, &amp;c.

No. PLATE.		PRICE.	No. PLATE.		PRICE.
1	5 Rotary Shears, . . . . .		9	Rack, . . . . .	
2	Adjustable Rotary Slitting Shears, . . . . .		10	{ Coupling, . . . . .	
3	{ Cone Pulleys, . . . . .		11	{ " . . . . .	
4			12	{ Pedestal, . . . . .	
5			13	{ " . . . . .	
6	6 Pulleys, . . . . .		14	{ Hangers, . . . . .	
7	Spur Wheel, . . . . .		15	{ Portable Angle Countershaft, . . . . .	
8	Bevil or Mitre Wheel, . . . . .		16		

## LIST OF PATTERNS OF GEAR WHEELS, PULLEYS, PEDESTALS, &amp;c.

## SPUR WHEELS.

$\frac{3}{8}$ " PITCH.						$\frac{3}{4}$ " PITCH.					
No. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PRICE.	REMARKS.	No. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PRICE.	REMARKS.
	Inches.		Inches.				Inches.		Inches.		
	$1\frac{3}{4}$	15	$1\frac{1}{4}$		Internal.	95	$3\frac{1}{8}$ f.	16	$1\frac{3}{8}$		
	$4\frac{1}{4}$	36	$1\frac{1}{4}$		"	100	$3\frac{9}{16}$ f.	15	$2\frac{1}{8}$		
136	$2\frac{3}{8}$	20	$1\frac{3}{16}$			102	$3\frac{23}{32}$ f.	15	2		
165	$3\frac{5}{8}$	29	$1\frac{1}{4}$			94	$3\frac{1}{4}$	14	$1\frac{7}{8}$		
						121	$12\frac{7}{8}$	52	1		Iron.
						144	$2\frac{7}{8}$	12	$1\frac{3}{8}$		
$\frac{5}{8}$ " PITCH.						$\frac{7}{8}$ " PITCH.					
160	$19\frac{7}{8}$	100	$1\frac{5}{8}$		Iron.	87	$4\frac{23}{32}$	17	$2\frac{3}{8}$		
159	$9\frac{1}{2}$	50	$1\frac{5}{8}$		"	142	$23\frac{1}{4}$	84	$2\frac{1}{2}$		
127	$11\frac{27}{32}$	60	$1\frac{1}{4}$			96	6	22	$2\frac{1}{2}$		
137	$4\frac{1}{2}$	22	$1\frac{1}{4}$			103	$3\frac{1}{2}$	12	3		
162	$3\frac{3}{4}$	15	$1\frac{1}{2}$			123	10	36	3		Iron.
$\frac{1}{2}$ " PITCH.						1" PITCH.					
79	$7\frac{5}{8}$	48	$1\frac{1}{4}$		Iron.	169	$6\frac{5}{8}$	21	$2\frac{1}{2}$		
158	$3\frac{1}{2}$	21	$\frac{3}{4}$			168	$20\frac{5}{8}$	65	$2\frac{1}{2}$		
105	$7\frac{25}{32}$	48	$1\frac{1}{4}$			106	$7\frac{7}{8}$	25	$2\frac{1}{2}$		
107	$3\frac{1}{2}$	22	$1\frac{1}{4}$			108	$9\frac{1}{4}$	30	$2\frac{1}{2}$		
47	$5\frac{13}{32}$	34	$1\frac{1}{4}$			128	$14\frac{5}{8}$	46	2		
161	$2\frac{11}{16}$ f.	17	$1\frac{1}{4}$			101	$3\frac{7}{8}$	12	$2\frac{1}{4}$		
75	$7\frac{5}{8}$	48	$1\frac{1}{2}$			150	$32\frac{3}{4}$	104	$1\frac{7}{8}$		
97	$3\frac{1}{2}$	22	1			106	$7\frac{3}{32}$	25	$1\frac{1}{2}$		
117	$3\frac{5}{8}$	23	1			13	$38\frac{7}{32}$ f.	120	$2\frac{1}{2}$		
164	$2\frac{3}{4}$	18	$1\frac{1}{4}$			15	$4\frac{7}{8}$	15	$2\frac{1}{2}$		
166	$7\frac{1}{2}$	47	$1\frac{3}{4}$		Round Teeth.	154	$47\frac{3}{4}$	150	$1\frac{1}{2}$		
167	$2\frac{1}{2}$	16	$1\frac{3}{4}$		" "						



CLASS TWELFTH.—*Continued.*LIST OF PATTERNS OF GEAR WHEELS, PULLEYS, PEDESTALS, &c.  
SPUR WHEELS.

1" PITCH.					
No. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PRICE.	REMARKS.
	Inches.		Inches.		
157	33 <sup>7</sup> / <sub>16</sub> f.	105	2 <sup>1</sup> / <sub>2</sub>		
12	30 <sup>9</sup> / <sub>16</sub> f.	96	2 <sup>1</sup> / <sub>2</sub>		
14	3 <sup>7</sup> / <sub>8</sub>	12	2 <sup>1</sup> / <sub>2</sub>		
22	7 <sup>5</sup> / <sub>8</sub>	24	4		
20	9	28	4		
21	15 <sup>1</sup> / <sub>4</sub>	48	4		
149	5 <sup>1</sup> / <sub>10</sub>	16	3		
145	20 <sup>2</sup> / <sub>5</sub>	64	3		
147	22 <sup>9</sup> / <sub>10</sub>	72	3		
146	26 <sup>1</sup> / <sub>5</sub>	82	3		
11	23 <sup>7</sup> / <sub>8</sub>	75	2 <sup>1</sup> / <sub>2</sub>		
19	9	28	2		
23	7 <sup>5</sup> / <sub>8</sub>	24	2		
82	12 <sup>5</sup> / <sub>8</sub>	40	1 <sup>1</sup> / <sub>2</sub>		
89	3 <sup>7</sup> / <sub>8</sub>	12	1 <sup>5</sup> / <sub>8</sub>		
92	6 <sup>3</sup> / <sub>8</sub>	20	2		
78	24	76	3 <sup>1</sup> / <sub>2</sub>		
148	15 <sup>1</sup> / <sub>4</sub>	48	3		
151	24	76	2		Iron.
152	6	19	2		"
153	4 <sup>3</sup> / <sub>16</sub>	13	2		

1 <sup>1</sup> / <sub>8</sub> " PITCH.					
27	27 <sup>15</sup> / <sub>16</sub>	78	3		
112	6 <sup>7</sup> / <sub>16</sub> f.	18	3 <sup>1</sup> / <sub>8</sub>		
110	7 <sup>1</sup> / <sub>2</sub>	20	3		
74	6 <sup>3</sup> / <sub>2</sub> s.	17	4		
52	24 <sup>3</sup> / <sub>8</sub>	67	4		
79	3 <sup>1</sup> / <sub>2</sub>	10	2 <sup>1</sup> / <sub>4</sub>		

1 <sup>1</sup> / <sub>4</sub> " PITCH.					
126	13 <sup>3</sup> / <sub>4</sub>	36	2 <sup>1</sup> / <sub>4</sub>		
122	13 <sup>1</sup> / <sub>2</sub>	34	2 <sup>1</sup> / <sub>2</sub>		Iron.
138	9 <sup>1</sup> / <sub>2</sub>	25	9		
170	5 <sup>1</sup> / <sub>4</sub>	13	5 <sup>1</sup> / <sub>2</sub>		

3 <sup>3</sup> / <sub>8</sub> " PITCH.					
45	39	89	3		
71	11 <sup>3</sup> / <sub>4</sub>	27	3		
72	7	16	3		
57	10 <sup>1</sup> / <sub>2</sub>	24	4		
73	4 <sup>13</sup> / <sub>16</sub> f.	11	4		
114	9 <sup>1</sup> / <sub>2</sub>	22	3		
70	13	30	3		

1 <sup>1</sup> / <sub>2</sub> " PITCH.					
No. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PRICE.	REMARKS.
	Inches.		Inches.		
117	6 <sup>5</sup> / <sub>8</sub>	14	4		
61	16 <sup>5</sup> / <sub>8</sub>	35	3		
133	11 <sup>1</sup> / <sub>2</sub>	24	3		
118	6 <sup>3</sup> / <sub>4</sub>	14	5		
130	11 <sup>3</sup> / <sub>8</sub>	24	4		
93	4 <sup>3</sup> / <sub>4</sub>	10	3 <sup>1</sup> / <sub>4</sub>		
44	32	67	3		
53	24 <sup>3</sup> / <sub>8</sub>	51	3		
58	25 <sup>1</sup> / <sub>8</sub>	53	4		
116	10	21	4		
132	12	25	5		
43	31	65	3		
33	40 <sup>1</sup> / <sub>8</sub>	84	4		
55	26 <sup>5</sup> / <sub>8</sub>	56	3 <sup>1</sup> / <sub>2</sub>		
37	25 <sup>5</sup> / <sub>16</sub>	53	4		
90	7 <sup>5</sup> / <sub>32</sub> f.	15	4		
155	14 <sup>13</sup> / <sub>16</sub> f.	31	4		
35	28 <sup>3</sup> / <sub>16</sub> f.	59	4		
51	23 <sup>7</sup> / <sub>8</sub>	50	4		
156	17 <sup>11</sup> / <sub>16</sub> s.	37	4		
88	6 <sup>6</sup> / <sub>16</sub>	14	4		
10	46	96	3		
16	5 <sup>13</sup> / <sub>16</sub>	12	3		
84	25 <sup>1</sup> / <sub>8</sub>	53	5 <sup>1</sup> / <sub>2</sub>		
129	8 <sup>1</sup> / <sub>2</sub>	18	3 <sup>1</sup> / <sub>2</sub>		
60	21	33	3		1 <sup>5</sup> / <sub>8</sub> " Pitch
141	7 <sup>1</sup> / <sub>4</sub>	15	4		
67	7 <sup>1</sup> / <sub>4</sub>	15	4 <sup>1</sup> / <sub>2</sub>		

3 <sup>3</sup> / <sub>4</sub> " PITCH.					
62	21 <sup>1</sup> / <sub>4</sub>	38	3 <sup>1</sup> / <sub>2</sub>		
98	6 <sup>1</sup> / <sub>8</sub>	11	3 <sup>1</sup> / <sub>2</sub>		
81	17 <sup>1</sup> / <sub>2</sub>	32	3		Round Teeth.
38	23 <sup>3</sup> / <sub>8</sub>	42	3 <sup>1</sup> / <sub>2</sub>		
111	9 <sup>3</sup> / <sub>8</sub>	17	4		
113	8 <sup>11</sup> / <sub>32</sub> f.	15	3 <sup>1</sup> / <sub>2</sub>		
63	21 <sup>1</sup> / <sub>4</sub>	38	3 <sup>1</sup> / <sub>2</sub>		Round Teeth.



CLASS TWELFTH.—*Continued.*

## LIST OF PATTERNS OF GEAR WHEELS, PULLEYS, PEDESTALS, &amp;c.

## SPUR WHEELS.

2" PITCH.						2½" PITCH.					
NO. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PRICE.	REMARKS.	NO. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PRICE.	REMARKS.
	Inches.		Inches.				Inches.		Inches.		
65	16⅜	25	6			39	25⅝	32	8		
104	10⅞	17	6			85	60⅞ f.	76	7		
17	7¾	12	4			51	25⅝	32	8		
18	9¾	15	4			136	9½ f.	12	6		
66	18½	28	6			40	32¼	40	6		
91	7	11	8½			50	22	27	6		
120	9½	14	5			26	30	37	8		
131	12¾	20	6			115	7⅜ s.	10	6⅜		
125	12½	19	4½			8	29½	36	6		
54	21¾	34	4			40	32¼	40	7		
119	11⅜	17	4			49	22	27	8		
124	13¼	21	4			135	35½	45	8		
140	14½	23	4			2¾" PITCH.					
77	33	52	4			134	10¾	12	5½		2⅞" Pitch.
34	29¼	46	4			3" PITCH.					
48	21¾	34	6			42	34¼ s.	35	8		
143	66½ f.	104	6			6	68¾ f.	72	10		
24	9¾	15	6¼			139	34⅝	36	10		
36	36½	57	4			1	87⅞	92	10		
109	9⅝	14	4½			5	78	82	10		
32	59⅞	94	4			3½" PITCH.					
31	47½	73	4⅝			83	43⅝ s.	39	14		
7	81½	128	6			3	46⅝ s.	42	14		Bore 14" in hal's.
56	24⅞ f.	38	6			76	47⅝	43	14		" 12" "
46	39½	62	6			2	53⅝	48	17		" 14" "
9	72⅝	114	4		16" Bore.	4	41⅝	37	17		
2¼" PITCH.						64	19¾	18	10		
29	68	95	5			86	44¼	40	10		In halves.
59	28	39	5			4" PITCH.					
2½" PITCH.											
63	20	25	8								
25	60⅞ f.	76	8		Bore 8" in halves.						
68	16	20	8								
80	14 f.	18	7								
69	13	16	8		Long tooth.						
30	47¾	60	6								
28	35⅝	45	8								
41	32⅝	41	7								



CLASS TWELFTH.—*Continued.*

# LIST OF PATTERNS OF GEAR WHEELS, PULLEYS, PEDESTALS, &c.

BEVIL WHEELS.

$\frac{1''}{2}$ PITCH.					
NO. OF PATTERN.	DIAMETER. Inches.	COGS.	FACE. Inches.	PRICE.	REMARKS.
40 {	$12\frac{3}{4}$ s.	80	$1\frac{1}{4}$		
	$1\frac{1}{2}$ f.	10	$1\frac{1}{4}$		
20 {	$4\frac{1}{2}$	27	$1\frac{1}{4}$		
	$10\frac{5}{16}$	63	$1\frac{1}{4}$		
$\frac{5''}{8}$ PITCH.					
18 {	$3\frac{5}{8}$	18	$1\frac{1}{2}$		
	11	54	$1\frac{1}{2}$		
21 {	$8\frac{1}{2}$	39	$1\frac{1}{2}$		
	$4\frac{1}{2}$	23	$1\frac{1}{2}$		
39 {	$10\frac{3}{4}$	54	2		
	$4\frac{5}{8}$	23	2		
$\frac{3''}{4}$ PITCH.					
35 {	$17\frac{5}{16}$	75	$1\frac{3}{8}$		
	$5\frac{1}{2}$	25	$1\frac{3}{8}$		
22 {	$3\frac{1}{2}$	15	$1\frac{1}{2}$		
	$10\frac{3}{8}$	42	$1\frac{1}{2}$		
36 {	$9\frac{3}{8}$	40	$1\frac{3}{4}$		
	$4\frac{1}{4}$	20	$1\frac{3}{4}$		
1" PITCH.					
37 {	$15\frac{1}{2}$ s.	50	$2\frac{1}{2}$		
	$4\frac{3}{4}$ f.	15	$2\frac{1}{2}$		
6 {	14	44	2		
	$3\frac{1}{2}$	11	2		
$\frac{1''}{8}$ PITCH.					
15 {	$20\frac{1}{2}$ f.	57	$2\frac{3}{4}$		
	$5\frac{1}{4}$ s.	16	$2\frac{3}{4}$		
$\frac{1''}{4}$ PITCH.					
33 {	$17\frac{3}{4}$	45	$2\frac{3}{4}$		
	$8\frac{1}{2}$	23	$2\frac{3}{4}$		
12 {	$14\frac{5}{8}$ f.	36	3		
	$8\frac{1}{2}$ f.	21	3		
7 {	$15\frac{9}{16}$	40	4		
	$12\frac{9}{16}$	30	4		
3 {	Segment for $50.93$	128	3		
	$4\frac{3}{4}$	12	3		
4 {	16	40	3		
	12	20	3		
$\frac{3''}{8}$ PITCH.					

$\frac{1''}{2}$ PITCH.					
NO. OF PATTERN.	DIAMETER. Inches.	COGS.	FACE. Inches.	PRICE.	REMARKS.
9 {	$7\frac{1}{2}$ s.	14	$4\frac{1}{2}$		
	$15\frac{1}{2}$ f.	28	$4\frac{1}{2}$		
$\frac{3''}{4}$ PITCH.					
11 {	15	24	4		
	$29\frac{3}{8}$	47	4		
8 {	$30\frac{1}{2}$ s.	48	6		
	$12\frac{5}{8}$ s.	19	6		
32 {	$19\frac{1}{8}$	30	6		
	$22\frac{1}{2}$	36	6		
$2\frac{1''}{4}$ PITCH.					
23 {	$19\frac{1}{4}$	27	6		
	$38\frac{3}{4}$	54	6		
13 {	53	74	7		
	$10\frac{3}{4}$	15	7		
$2\frac{1''}{2}$ PITCH.					
24 {	$21\frac{5}{8}$	27	6		
	$32\frac{1}{4}$	40	6		
2 {	$31\frac{3}{8}$ f.	40	8		
	$47\frac{3}{4}$	60	8		
3" PITCH.					
27 {	$36\frac{1}{4}$	38	12		
	$72\frac{1}{2}$	76	12		
25 {	21	22	7		
	42	44	7		
28 {	$34\frac{3}{8}$ f.	36	7		
	$22\frac{1}{2}$ s.	24	7		
$3\frac{1''}{2}$ PITCH.					
26 {	$27\frac{7}{8}$	25	8		
	$34\frac{9}{16}$	31	8		
4" PITCH.					



CLASS TWELFTH.—*Continued.*

## LIST OF PATTERNS OF GEAR WHEELS, PULLEYS, PEDESTALS, &amp;c.

## MITRE WHEELS.

NO. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PITCH.	PRICE.	NO. OF PATTERN.	DIAM-ETER.	COGS.	FACE.	PITCH.	PRICE.
	Inches.		Inches.	Inches.			Inches.		Inches.	Inches.	
38	$5\frac{7}{8}$	28	$1\frac{1}{4}$	$\frac{5}{8}$		10	$13\frac{1}{8}$	25	5	$1\frac{3}{4}$	
36	30	85	$2\frac{1}{4}$	$1\frac{1}{8}$		5	$12\frac{3}{8}$	34	$2\frac{1}{2}$	$1\frac{1}{8}$	
41	$3\frac{1}{2}$	20	$1\frac{1}{4}$	$\frac{9}{16}$ s.		31	$34\frac{3}{8}$	31	8	$3\frac{1}{2}$	
16	$7\frac{5}{8}$ s.	20	$2\frac{3}{4}$	$1\frac{1}{8}$		30	$27\frac{7}{8}$	25	8	$3\frac{1}{2}$	
17	$3\frac{3}{5}$	18	$1\frac{5}{16}$	$\frac{5}{8}$		29	30	24	11	$3\frac{7}{8}$	
1	26	24	8	$3\frac{4}{10}$							

## RACKS.

NO.	FACE.	PITCH.	PRICE.	NO.	FACE.	PITCH.	PRICE.
	Inches.	Inches.			Inches.	Inches.	
1	$1\frac{1}{4}$	$\frac{3}{4}$		4	3	$1\frac{1}{2}$	
2	$1\frac{1}{2}$	1		5	$2\frac{1}{2}$	$\frac{3}{4}$	
3	$2\frac{1}{2}$	1					

## HANGERS.

SIZE.	DROP.	PRICE.	SIZE.	DROP.	PRICE.
Inches.	Inches.		Inches.	Inches.	
1	8		$2\frac{1}{8}$	20	
$1\frac{7}{8}$	10		$3\frac{7}{8}$	20	
$1\frac{1}{2}$	16		5	30	
$2\frac{7}{8}$	16				

## PULLEYS.

DIAM.	FACE.	PRICE.	DIAM.	FACE.	PRICE.	DIAM.	FACE.	PRICE.
In.	In.		In.	In.		In.	In.	
24	$7\frac{1}{4}$		$17\frac{1}{4}$	6		$10\frac{5}{8}$	$1\frac{1}{2}$	
$16\frac{1}{2}$	$4\frac{1}{4}$		12	4		7	$1\frac{3}{4}$	
9	$4\frac{1}{2}$		10	$7\frac{1}{2}$		18	4	
$15\frac{1}{2}$	$3\frac{1}{2}$		30	9		$10\frac{1}{2}$	$2\frac{1}{2}$	
$9\frac{1}{2}$	6		36	12		$11\frac{1}{2}$	$2\frac{1}{2}$	
24	$9\frac{1}{2}$		$5\frac{3}{4}$	$1\frac{1}{2}$		24	$7\frac{1}{8}$ f	
$14\frac{1}{2}$	5		$4\frac{1}{2}$	1				

## PEDESTALS.

SIZE.	PRICE.	SIZE.	PRICE.
Inches.		Inches.	
2		7	
$2\frac{1}{2}$		8	
3		9	
4		10	
5		12	
6			


## CONE PULLEYS.

DIAMETER.	FACE.	PRICE.	DIAMETER.	FACE.	PRICE.
Inches.	In.		Inches.	In.	
$12 \times 15 \times 18$	$4\frac{1}{8}$		$16\frac{1}{2} \times 14\frac{1}{2} \times 12\frac{1}{2}$	$7\frac{1}{2}$	
$8\frac{1}{2} \times 7\frac{1}{8}$	3		$10 \times 8 \times 6$	$1\frac{3}{4}$	
$16\frac{1}{2} \times 20\frac{1}{2} \times 24\frac{1}{2}$	$4\frac{1}{4}$		$2\frac{1}{2} \times 3\frac{1}{2} \times 4\frac{1}{2} \times 6$	$1\frac{5}{8}$	
$29 \times 25 \times 21$	$4\frac{1}{4}$		$12\frac{1}{2} \times 10\frac{1}{2} \times 8\frac{1}{2} \times 6$	$2\frac{1}{2}$	
$15 \times 17 \times 19\frac{1}{2}$	$3\frac{1}{4}$		$15\frac{1}{2} \times 10\frac{1}{4} \times 5\frac{1}{2}$	$2\frac{1}{2}$	
$16\frac{1}{4} \times 13\frac{1}{4} \times 10\frac{1}{4}$	$4\frac{1}{8}$		$8 \times 6 \times 4$	$1\frac{7}{8}$	
$14\frac{1}{2} \times 11$	$3\frac{1}{4}$		$12\frac{3}{8} \times 11\frac{1}{2} \times 10\frac{1}{2}$	$1\frac{1}{2}$	

## COUPLINGS.

SIZE.	PRICE.	SIZE.	PRICE.
Inches.		Inches.	
$1\frac{1}{8}$		5	
$2\frac{7}{8}$		6	
$2\frac{1}{8}$		7	
$3\frac{7}{8}$		8	
$3\frac{1}{8}$		9	
$4\frac{7}{8}$			





SIEMENS' GAS PRODUCER.








# MORRIS, TASKER & CO LIMITED. ILLUSTRATED CATALOGUE.




1<sup>st</sup> Edition.

CLASS TWELFTH.

Plate 2.










# MORRIS, TASKER & CO LIMITED. ILLUSTRATED CATALOGUE.


1<sup>st</sup> Edition.

CLASS TWELFTH.

Plate 3.



Wall Box.



No. 20.

Damper  
for Chimney Flue.

No. 21.



No. 35

Roller.


Shapes.

No. 22.

Valve.

Shapes.

No. 38.



Roller Plate.



Floor Column.



No. 23.



No. 24.



No. 25.



No. 26.



No. 26a.



No. 27.



No. 28.



No. 29.



No. 30.



No. 31.



No. 32. Grate Bar.




No. 33. False Grate Bar.



No. 34.



Keystone.



No. 36.



No. 37.

Draft Damper Column.

Air or Gas Valve Column.

No. 39.




Regulating Damper.

Stoker Tools for Gas Producer.











[BLANK PAGE]



CCA




MORRIS, TASKER & CO LIMITED. ILLUSTRATED CATALOGUE.


1<sup>st</sup> Edition.

CLASS TWELFTH.


Plate 5.



*Rotary Shears.*



*Pat. Adjustable Slitting Shears.*



*Cone Pulleys.*



THE HISTORY OF THE  
CITY OF LONDON



THE HISTORY OF THE  
CITY OF LONDON






# MORRIS, TASKER & CO LIMITED. ILLUSTRATED CATALOGUE.

1<sup>st</sup> Edition.

CLASS TWELFTH.

Plate 6.

No. 6.



Pulley.

No. 8.




Bevil or Mitre Wheel.

No. 9.




Rack.

No. 10.




Coupling.

No. 11.




Coupling.

No. 15.




Hanger.

No. 12.




Pedestal.

No. 13.




Pedestal.

No. 16.




Portable Angle Counter Shaft.

No. 7.



Gear Wheel.

No. 14.



Hanger.



[BLANK PAGE]



CCA



[BLANK PAGE]



CCA



[BLANK PAGE]



CCA



[BLANK PAGE]



CCA



